


Qty	Label	Arrangement	Lum. Lumens	Lum. Watts	LLF	Description
8	AF-E	SINGLE	36341	428.6	0.900	CREE + (1) ARE-EHO-AF-xx-12-E-UL-xx-1000-40K
2	OS3-2	2 @ 90 DEGRE	20860	134.2	0.900	CREE + (2) ARE-EHO-3M-12-UL-1000-40K
6	OS4	SINGLE	30657	426	0.900	ARE-EHO-4M...12-E-UL-1000-40K (1000mA)
3	OS5-2	BACK-BACK	64656	431.2	0.900	CREE + (2) ARE-EHO-5M-xx-12-E-UL-xx-1000-40K
7	OS5-4	4 @ 90 DEGRE	51224	132.4	0.900	CREE + (2) ARE-EHO-SS-12-UL-1000-40K
7	4MB-E	SINGLE	9015	132.8	0.900	For use with Series E Edge, Edge High Output, 228.
1	OS4-2	BACK-BACK	61314	426	0.900	ARE-EHO-4M...12-E-UL-1000-40K (1000mA)

Label	CalcType	Units	Avg	Max	Min	Avg/Min	Max/Min
PROP LINE	Illuminance	Fc	1.54	10.8	0.0	N.A.	N.A.
SITE	Illuminance	Fc	6.31	29.2	0.0	N.A.	N.A.
DISPLAY	Illuminance	Fc	10.12	12.3	7.6	1.33	1.62
FRONT LINE	Illuminance	Fc	22.94	29.2	10.7	2.14	2.73


Enterprise Lighting LTD

**FIELD'S JAGUAR/VOLVO
WAUKESHA, WISCONSIN**

**CREE EDGE HIGH OUT-PUT
LIGHTING PLAN**

DATE: DEC. 5, 2015	SCALE: 1" = 20'-0"	SHEET NUMBER: E1
-----------------------	-----------------------	---------------------