



PREMIUM LED WALL PACK – SMALL 36-WATT LED (E-WP6L SERIES)

Applications: Security, pathway and perimeter lighting; ideal for entryways and other applications where control of spill light is important.

Typical Mounting Height: 8 to 15 feet

Typical Spacing: 1 to 2 times the mounting height

GOOD HARVEST FOODS

TYPE OD



4-1/2"H x 8-3/4"W x 9-1/2"D

| Catalog # | Description | Input Voltage | Delivered Lumen Output | CCT | CRI | Lifetime (L ₇₀ at 25°C) | Weight | Comparable To: |
|-------------------|-----------------------|---------------------|------------------------|-------|-----|------------------------------------|--------|----------------|
| E-WP6L03CZ | 36W LED Cool white | Universal 120V-277V | 3350 Lumens | 5000K | 70 | 50,000 Hours | 7 lbs | 100W PSMH |
| E-WP6L03NZ | 36W LED Neutral white | Universal 120V-277V | 3350 Lumens | 4000K | 70 | 50,000 Hours | 7 lbs | 100W PSMH |

Features

- 50,000 hours of maintenance-free operation to L₇₀ at 25°C
- Non-dimmable
- Low copper, die-cast aluminum housing and lens frame
- Dark bronze polyester powder-coat finish
- Fixed cutoff glare shield to reduce light pollution
- Tempered glass lens, thermal shock and impact resistant
- Patented lens design delivers true IES Type III distribution
- Mounts over recessed Junction box or with conduit
- Die-cast detachable back box for easy mounting
- 75°C minimum supply wire required
- Universal voltage (120V through 277V)
- Minimum starting temperature: -40° F
- Heat dissipating fins
- Conduit entries on all sides of the fixture
- Two knockouts provided on back for conduit or J-box mounting
- RoHS compliant
- UL Listed for wet locations
- Cree® LEDs inside
- 3-year warranty

Accessories



Photocell is field installed.
Drilling of the back box
in the field is required.

CAT.#: E-ACP1 (120 volts)

CAT.#: E-ACP2 (208/240/277 volts)