


| Statistics | | | | | | |
|--------------------|--------|---------|---------|---------|---------|---------|
| Description | Symbol | Avg | Max | Min | Max/Min | Avg/Min |
| Calc Zone #2 | + | 17.1 fc | 27.8 fc | 0.0 fc | N/A | N/A |
| Front Row Plan | X | 52.4 fc | 76.3 fc | 22.7 fc | 3.4:1 | 2.3:1 |
| Front Row Plan Top | X | 58.2 fc | 77.8 fc | 38.0 fc | 2.0:1 | 1.5:1 |

| SSL - LED Source | Pole Height | Pole Spacing | Fixture Needed* | Foot Candles |
|-------------------|---------------------|--------------------|-------------------------------|--------------|
| Front Row | 16'-20' 6" base | 20'-30' on centers | Twin 27,000 Lumen LED | 40-50 FC |
| Interior Row | 20'-25' 30" base | 60" on centers | Twin 27,000 Lumen LED | 30 FC |
| Vehicle Inventory | 20'-25' 30" base | 100' on centers | Twin or Quad 27,000 Lumen LED | 6-8 FC |



RSX3 LED
Area Luminaire



View the full catalog for this product's availability, options, and more.

Introduction

The new RSX LED Area family delivers maximum value by providing significant energy savings, long life and outstanding photometric performance at an affordable price. The RSX3 delivers 25,000 to 41,000 lumens allowing it to replace 400W to 1000W HID luminaires.

The RSX features an integral universal mounting mechanism that allows the luminaire to be mounted on most existing drill hole patterns. This "no-drill" solution provides significant labor savings. An easy-access door on the bottom of mounting arm allows for wiring without opening the electrical compartment. A mast arm adapter, adjustable integral slipfitter and other mounting configurations are available.

Ordering Information

| EXAMPLE: RSX3 LED P4 40K R3 MVOLT SPA DDBXD | | | | | |
|---|---------------------|-------------------|---------------------|--------------------------------|--|
| RSX3 LED | Performance Package | Color Temperature | Distribution | Voltage | Mounting |
| P1 | 3M 3000K | R2 | Type II&III | MVOLT: RSX3 LED P4 3000K MVOLT | SPA: Spine pole mounting (112° incl. 90° back for 1.4 to 60°) |
| P2 | 4K 4000K | R3 | Type III&IV | MVOLT: RSX3 4000K MVOLT | SPA: Access pole mounting (112° incl. 90° back for 1.4 to 60°) |
| P3 | 5K 5000K | R5 | Type I&II | MVOLT: RSX3 5000K MVOLT | SPA: Max arm height (90°) 2.18" (55 mm) dia 80D (dia 100) |
| P4 | | R4 | Type IV&V | MVOLT: RSX3 4000K MVOLT | MA: Mast arm adapter (90°) 2.18" (55 mm) dia 80D (dia 100) |
| | | R5 | Type V&VI | 120° 277° | IS: Adjustable height (0 to 3.10" (0 to 80 mm)) |
| | | R5S | Type V&VI | 204° 347° | WBA: Wall bracket |
| | | AW | Automatic Face Rot. | 240° 446° | ASAC: Adjustable arm surface mount |
| | | AWH | Automatic Face Rot. | | ASAF: Adjustable arm surface mount* |
| | | AWH2 | Automatic Face Rot. | | ASAB: Adjustable arm with ball bracket* |
| | | AWH3 | Automatic Face Rot. | | ASAC2: Adjustable arm with ball bracket and surface cast base* |

| System | Finish |
|--|---|
| Shipped Installed | |
| HS | Dark bronze |
| PE | Black |
| PEL | Brushed aluminum |
| PERF | White |
| PERL | Painted black |
| CEP | Painted black (less than 0.5% reflectance) |
| CF | Cast aluminum (0.5% reflectance) |
| CP | Cast aluminum (0.5% reflectance) |
| SP2000 | Cast aluminum (0.5% reflectance) |
| FAB | Cast aluminum (0.5% reflectance) |
| DMG | Cast aluminum (0.5% reflectance) |
| Shipped Separately Requires some field assembly | |
| ES | External glass shield |
| ESV | External glass full cover (90° around light fixture)* |
| BS | Bird shield |
| *Note: PIBB with C/Light Air can be used as a transom or networked solution. Sensor coverage pattern is directed when luminaire is tilted. | |
| Shipped Separately Requires some field assembly | |
| ES | External glass shield |
| ESV | External glass full cover (90° around light fixture)* |
| BS | Bird shield |

LITHONIA
LIGHTING
COMMERCIAL OUTDOOR

One Lithonia Way • Conyers, Georgia 30012 • Phone: 1-800-705-SEXY (7399) • www.lithonia.com

Lithonia RSX3 Area LED
Rev 03/24/21
Page 1 of 2

| Schedule | | | | | | | | | | |
|----------|-------|-------|-----|-------------------|---------------------|---|----------|---|------------|-------|
| Symbol | Label | Image | QTY | Manufacturer | Catalog Number | Description | Wattage | Distribution | Polar Plot | Notes |
| | A | | 15 | Lithonia Lighting | RSX3 LED P4 40K AFR | RSX Area Fixture Size 3 P4 Lumen Package 4000K CCT Type AFR Distribution | 623.84 | TYPE II, SHORT, BUG: RATING: B3 - U0 - G3 | | 1 |
| | B | | 7 | Lithonia Lighting | RSX3 LED P4 40K RS | RSX Area Fixture Size 3 P4 Lumen Package 4000K CCT Type RS Distribution | 623.84 | TYPE V5, BUG: RATING: B5 - U0 - G5 | | 1 |
| | C | | 0 | Lithonia Lighting | RSX3 LED P4 40K R3 | RSX Area Fixture Size 3 P4 Lumen Package 4000K CCT Type R3 Distribution | 623.84 | TYPE III, SHORT, BUG: RATING: B3 - U0 - G5 | | 1 |
| | D | | 1 | Lithonia Lighting | RSX3 LED P4 40K R3 | RSX Area Fixture Size 3 P4 Lumen Package 4000K CCT Type R3 Distribution | 623.84 | TYPE III, SHORT, BUG: RATING: B3 - U0 - G5 | | 1 |
| | F | | 5 | Lithonia Lighting | RSX3 LED P6 40K R3 | RSX Area Luminaire Size 4 P6 Lumen Package 4000K CCT Type R3 Distribution | 545.6631 | TYPE III, SHORT, BUG: RATING: B4 - U0 - G5 | | 1 |

Designer:
KY
Date:
04/09/2021
Scale:
Not to Scale
Drawing No.:
Drawing
Summary: