

FIXTURE SCHEDULE - HALL AUTOMOTIVE WAUKESHA, WI

TYPE	DESCRIPTION	LAMP		VOLT	WATTS	MANUFACTURER	CATALOG NUMBER	EQUALS	NOTE
		TYPE	QTY						
A2	2'X4' GRID LED TROFFER	4000K LED	-	277	38	METALUX	2-GR-FA-LD1-38-A125-UNV-L840-CD1-PAF	LITHONIA, DAY-BRITE, COLUMBIA	
A2E	2'X4' GRID LED TROFFER - EMERGENCY MODULE	4000K LED	-	277	38	METALUX	2-GR-FA-LD1-38-A125-UNV-EL14-L840-CD1-PAF	LITHONIA, DAY-BRITE, COLUMBIA	
A3	2'X4' GRID LED TROFFER	4000K LED	-	277	49	METALUX	2-GR-FA-LD1-48-A125-UNV-L840-CD1-PAF	LITHONIA, DAY-BRITE, COLUMBIA	
A5	2'X2' GRID LED TROFFER	4000K LED	-	277	36	METALUX	2-GR-FA-LD1-32-A125-UNV-L840-CD1-PAF	LITHONIA, DAY-BRITE, COLUMBIA	
A5E	2'X2' GRID LED TROFFER - EMERGENCY MODULE	4000K LED	-	277	36	METALUX	2-GR-FA-LD1-32-A125-UNV-EL14-L840-CD1-PAF	LITHONIA, DAY-BRITE, COLUMBIA	
B2	1'X4' GRID LED TROFFER	4000K LED	-	277	36	METALUX	GR-FA-LD1-32-A125-UNV-L840-CD1-PAF	LITHONIA, DAY-BRITE, COLUMBIA	
C3	2'X4' GRID LED DIRECT/INDIRECT - CENTER MOUNT PERFORATED BASKET	4000K LED	-	277	74	FOCAL POINT	FLUL-24-PS-5000L-40K-1C-UNV-LD1-G-WH	-	
D1	4' REFLECTOR LED STRIPLIGHT	4000K LED	-	277	29	METALUX	SNLED-LD1-28-UNV-RW-L840-CD-1	LITHONIA, DAY-BRITE, COLUMBIA	
D1E	4' REFLECTOR LED STRIPLIGHT - EMERGENCY MODULE	4000K LED	-	277	29	METALUX	SNLED-LD1-28-UNV-RW-EL-L840-CD-1	LITHONIA, DAY-BRITE, COLUMBIA	
D2	8' REFLECTOR LED STRIPLIGHT	4000K LED	-	277	65	METALUX	8T-SNLED-LD1-59-UNV-RW-L840-CD-2	LITHONIA, DAY-BRITE, COLUMBIA	
D2E	8' REFLECTOR LED STRIPLIGHT - EMERGENCY MODULE	4000K LED	-	277	65	METALUX	8T-SNLED-LD1-59-UNV-RW-EL-L840-CD-2	LITHONIA, DAY-BRITE, COLUMBIA	
D4	4' MEDIUM DUTY INDUSTRIAL - WIRE GUARD - 2 LAMP	F32T8/841	2	277	55	METALUX	DCIF-2-32-WG	LITHONIA, DAY-BRITE, COLUMBIA	
D8	8' MEDIUM DUTY INDUSTRIAL - WIRE GUARD - 2 LAMP CROSS SECTION	F32T8/841	4	120-277	118	METALUX	8T-DCIF-2-32-WG	LITHONIA, DAY-BRITE, COLUMBIA	
D12E	8' MEDIUM DUTY INDUSTRIAL - WIRE GUARD - 2 LAMP CROSS SECTION - EMERGENCY BALLAST	F54T5H0/841	4	277	232	METALUX	8T-DCIF-2-54T5-WG	LITHONIA, DAY-BRITE, COLUMBIA	5
E1	GREEN LED THERMOPLASTIC EXIT - BATTERY BACKUP - SINGLE/DOUBLE FACE	GREEN LED	-	277	3	ISOLITE	RL-EM-G-WW	LITHONIA, MCPHILBEN, DUAL-LITE	1
E2	EXTERIOR REMOTE LED EMERGENCY LIGHT - TIME DELAY	LED	-	277	2	LITHONIA	AFN-EXT-FWD	-	2
E3	125W COMPACT LIGHTING INVERTER - CEILING RECESSED	-	-	277	-	ISOLITE	IMI-12-LC-V2-RE	LITHONIA, MCPHILBEN, DUAL-LITE	2
E4	GREEN LED WET LOCATION EXIT - BATTERY BACKUP - SINGLE FACE	GREEN LED	-	277	3	ISOLITE	MAX-EM-G-S-WW-WM	LITHONIA, MCPHILBEN, DUAL-LITE	1
G2	RLM 16' WAREHOUSE SHADE - 20' STRAIGHT ARM W/ WALL MOUNTING BRACKET & ANGLED ARM - WET LOCATION - REMOTE BALLAST	100W PSMH	1	277	130	BASELITE	W516-PRT4-WM31	-	2
H1	TRAPEZOID WALL PACK - TYPE II	70W PSMH	1	277	90	MCGRAW-EDISON	IST-70-MP-2S	LSI, MCGRAW EDISON, SPAULDING, GARDCO	2
H2	TRAPEZOID WALL PACK - WIDE THROW	150W PSMH	1	277	210	LITHONIA	WST-150M-WT-SCWA	LSI, MCGRAW EDISON, SPAULDING, GARDCO	2
H3	TRAPEZOID WALL PACK - TYPE III	250W PSMH	1	277	292	MCGRAW-EDISON	IMT-250-MP-3S	LSI, MCGRAW EDISON, SPAULDING, GARDCO	2
H4	TRAPEZOID WALL PACK - TYPE IV	250W PSMH	1	277	292	MCGRAW-EDISON	IMT-250-MP-4S	LSI, MCGRAW EDISON, SPAULDING, GARDCO	2
J2E	FLUORESCENT HIGH-BAY INDUSTRIAL - MEDIUM BEAM - CLEAR LENS - WET LOCATION HOSE DOWN - 4 LAMP - EMERGENCY BALLAST	F54T5H0/841	4	277	232	METALUX	2-HBHD-4-54T5-CL-EL	SPECLIGHT, DAY-BRITE, COLUMBIA	6
J3	FLUORESCENT HIGH-BAY INDUSTRIAL - MEDIUM BEAM - CLEAR LENS - WET LOCATION HOSE DOWN - 6 LAMP	F54T5H0/841	6	277	353	METALUX	2-HBHD-6-54T5-CL	SPECLIGHT, DAY-BRITE, COLUMBIA	6
J4	FLUORESCENT HIGH-BAY INDUSTRIAL - MEDIUM BEAM - CLEAR LENS - 4 LAMP	F54T5H0/841	4	277	232	METALUX	HBI-4-54T5-M-CL-NUA-G2-MC6	SPECLIGHT, DAY-BRITE, COLUMBIA	
J4E	FLUORESCENT HIGH-BAY INDUSTRIAL - MEDIUM BEAM - CLEAR LENS - 4 LAMP - EMERGENCY BALLAST	F54T5H0/841	4	277	232	METALUX	HBI-4-54T5-M-CL-NUA-G2-MC6-EM	SPECLIGHT, DAY-BRITE, COLUMBIA	5
K1	6" LED RECESSED DOWNLIGHT	4000K LED	-	277	44	PORTFOLIO	LD6A-30-D010TE-ERM6A30-9-40-6LM1-LI	GOTHAM, KIRLIN, PRESCOLITE	
K1E	6" LED RECESSED DOWNLIGHT - EMERGENCY MODULE	4000K LED	-	277	44	PORTFOLIO	LD6A-30-D010TE-EMBOD-ERM6A30-9-40-6LM1-LI	GOTHAM, KIRLIN, PRESCOLITE	
K2E	6" LED RECESSED DOWNLIGHT - EMERGENCY MODULE	4000K LED	-	277	23	PORTFOLIO	LD6A-15-D010TE-EMBOD-ERM6A15-9-40-6LM1-LI	GOTHAM, KIRLIN, PRESCOLITE	
K3	6" LED RECESSED DOWNLIGHT	4000K LED	-	277	23	PORTFOLIO	LD6A-15-D010TE-ERW6A15-9-40-6LW1-LI	GOTHAM, KIRLIN, PRESCOLITE	
K4	6" LED RECESSED DOWNLIGHT	4000K LED	-	277	32	PORTFOLIO	LD6A-20-D010TE-ERW6A20-9-40-6LW1-LI	GOTHAM, KIRLIN, PRESCOLITE	
K4E	6" LED RECESSED DOWNLIGHT - EMERGENCY MODULE	4000K LED	-	277	32	PORTFOLIO	LD6A-20-D010TE-EMBOD-ERW6A20-9-40-6LW1-LI	GOTHAM, KIRLIN, PRESCOLITE	
K5	6" LED RECESSED DOWNLIGHT - 0-10V DIMMABLE	4000K LED	-	277	32	PORTFOLIO	LD6A-20-D010TE-ERW6A20-9-40-6LW1-LI	GOTHAM, KIRLIN, PRESCOLITE	
K6	6" LED RECESSED DOWNLIGHT	4000K LED	-	277	14	PORTFOLIO	LD6A-10-D010TE-ERW6A10-9-40-6LW1-LI	GOTHAM, KIRLIN, PRESCOLITE	
K7	6" LED RECESSED DOWNLIGHT	4000K LED	-	277	14	PORTFOLIO	LD6A-10-D010TE-ERM6A10-9-40-6LM1-WH	GOTHAM, KIRLIN, PRESCOLITE	
K8	4" LED RECESSED DOWNLIGHT	4000K LED	-	277	14	PORTFOLIO	LD4A-09-D010TE-ERM4A09-9-40-4LM1-LI	GOTHAM, KIRLIN, PRESCOLITE	
N1	12-1/8" LINEAR LED COVE STRIP - 0-10V DIMMABLE	4000K LED	-	277	6	LUMENPULSE	LCNHO-120-12-40K-CL-WH-DIM	-	4
N4	47-1/2" LINEAR LED COVE STRIP - 0-10V DIMMABLE	4000K LED	-	277	24	LUMENPULSE	LCNHO-120-48-40K-CL-WH-DIM	-	4
P1	DECORATIVE FLUORESCENT PENDANT	18W TTT/841	1	120	20	CON-TECH	CMCFP-18-125-S	-	3
R8	8' PERIMETER RECESSED DIRECT LED WALL WASH - 4" CEILING OPENING	4000K LED	-	277	128	LITECONTROL	WS-L60-08-HO-40K-CWM-DP-NDM-277-LCD	-	
W2	8' VAPORTITE INDUSTRIAL - SPECULAR REFLECTOR - 2 LAMP CROSS SECTION	F54T5H0/841	4	277	232	METALUX	8T-VT3-2-54T5-DR50-WL-M4-SSL	LITHONIA, DAY-BRITE, COLUMBIA	
W8	8' VAPORTITE INDUSTRIAL - SPECULAR REFLECTOR - 2 LAMP CROSS SECTION	F32T8/841	4	277	118	METALUX	8T-VT3-2-32-DR50-WL-M4-SSL	LITHONIA, DAY-BRITE, COLUMBIA	
Y1	TYPE III AREA FIXTURE - HOUSESIDE SHIELD - 2 @ 180° - ROTATED OPTICS	400W PSMH	2	277	904	LITHONIA	KAD-400M-SR3-SCWA-SPD-04-HS	LSI, MCGRAW EDISON, SPAULDING, GARDCO	2,7,8
Y2	TYPE III AREA FIXTURE - HOUSESIDE SHIELD - SINGLE	400W PSMH	1	277	452	LITHONIA	KAD-400M-SR3-SCWA-SPD-04-HS	LSI, MCGRAW EDISON, SPAULDING, GARDCO	2,8
Y3	TYPE III AREA FIXTURE - SINGLE	400W PSMH	1	277	452	LITHONIA	KAD-400M-SR3-SCWA-SPD-04	LSI, MCGRAW EDISON, SPAULDING, GARDCO	2,8
Y4	TYPE IV AREA FIXTURE - 2 @ 180°	250W PSMH	2	277	584	LITHONIA	KAD-250M-SR4SC-SCWA-SPD-04	LSI, MCGRAW EDISON, SPAULDING, GARDCO	2,8
Y5	TYPE IV AREA FIXTURE - HOUSESIDE SHIELD - SINGLE	400W PSMH	1	277	452	LITHONIA	KAD-400M-SR4SC-SCWA-SPD-04-HS	LSI, MCGRAW EDISON, SPAULDING, GARDCO	2,8
Y6	TYPE III AREA FIXTURE - 2 @ 180°	400W PSMH	2	277	904	LITHONIA	KAD-400M-SR3-SCWA-SPD-04	LSI, MCGRAW EDISON, SPAULDING, GARDCO	2,8
Y7	TYPE III AREA FIXTURE - HOUSESIDE SHIELD - SINGLE	250W PSMH	1	277	292	LITHONIA	KAD-250M-SR3-SCWA-SPD-04-HS	LSI, MCGRAW EDISON, SPAULDING, GARDCO	2,8
LP1	18'-0" STRAIGHT SQUARE STEEL 5" POLE - SINGLE	-	-	-	-	LITHONIA	SSS-18-5C-DM19	LSI, MCGRAW EDISON, SPAULDING, GARDCO	2
LP2	18'-0" STRAIGHT SQUARE STEEL 5" POLE - 2 @ 180°	-	-	-	-	LITHONIA	SSS-18-5C-DM28	LSI, MCGRAW EDISON, SPAULDING, GARDCO	2
LP3	18'-0" STRAIGHT SQUARE STEEL 5" POLE - SINGLE - GFCI RECEPTACLE	-	-	-	-	LITHONIA	SSS-18-5C-DM19-FDL2.3A	LSI, MCGRAW EDISON, SPAULDING, GARDCO	2
LP4	18'-0" STRAIGHT SQUARE STEEL 5" POLE - 2 @ 180° - GFCI RECEPTACLE	-	-	-	-	LITHONIA	SSS-18-5C-DM28-FDL2.3A	LSI, MCGRAW EDISON, SPAULDING, GARDCO	2

GENERAL NOTES:

- SEE SPECIFICATIONS FOR LAMP AND BALLAST REQUIREMENTS.
- ALTERNATE FIXTURES TO HAVE EQUAL CHARACTERISTICS OF SPECIFIED FIXTURES.
- ALL PULSE START METAL HALIDE LAMPS TO BE 4000K WITH A CRI OF 70+.

PLAN NOTES:

- PROVIDE ALL NECESSARY MOUNTING CANOPIES.
- ARCHITECT TO SELECT STANDARD COLOR AND FINISH.
- FIXTURE TO BE MOUNTED 6'-0" AFF TO BOTTOM.
- TILT FIXTURE 45 DEGREES TOWARD CEILING AT CENTER OF ROOM. PROVIDE ALL NECESSARY LEADER AND JUMPER CABLES AS REQUIRED.
- PROVIDE FIXTURE WITH BODINE B30 EMERGENCY BALLAST CAPABLE OF ILLUMINATING (1) 54W T5HO LAMP UP TO 2650 LUMENS FOR 90 MIN. MOUNT BALLAST ON TOP OF FIXTURE. MOUNT INDICATOR LIGHT AND TEST SWITCH ON OUTSIDE OF FIXTURE.
- FIXTURE TO BE HARDWIRED WITH LIQUID-TIGHT FLEXIBLE METAL CONDUIT.
- ROTATE OPTICS WHERE INDICATED ON DRAWINGS.
- ALTERNATE MANUFACTURERS MUST SUBMIT SITE LIGHTING PHOTOMETRIC CALCULATION WITH SHOP DRAWINGS FOR APPROVAL.