



These products are suitable for big spaces such as arenas or any type of closed off spaces that need a lot of light. They produce up to 12000 lumens depending on the wattage. These lights are a perfect solution for your exteriors. They operate with a large angle beam, much more than any other product on the market.

## SPECIFICATIONS

Hyperikon Code	Model Name	Wattage	Voltage	Lumens	Kelvin	Beam Angle	Base	CRI
552001001	HyperWall45-501	45 W	120-277 V	3900 Lm	5000 K	90°	Mounted	85+
552001002	HyperWall70-501	70 W	120-277 V	6000 Lm	5000 K	90°	Mounted	85+
552001003	HyperWall90-501	90 W	120-277 V	7800 Lm	5000 K	90°	Mounted	85+
552001004	HyperWall135-501	135 W	120-277 V	12000 Lm	5000 K	90°	Mounted	85+

## LED WALL PACK by Hyperikon®



CRI  
85+



Voltage  
120-277 V



Photocell  
Compatible



Lifespan  
45,000+ Hrs



5 Years  
Warranty



Efficacy  
82-100 Lm/W



Beam Angle  
90°



UV free  
Mercury free



Damp location  
suitable

- Device complies with Part 15 of the FCC Rules
- Sealed die-casting profile for outdoor applications
- Polycarbonate optical lens with UV stabilizers
- Built-in UL class 2 driver, optional for photocell
- UL/cUL listed and DLC qualified

## DIMENSIONS



## ACCESSORIES

A complimentary die cast aluminum housing is included. The "Dark Sky" approved metal hood features a high-quality, shatter-resistant epoxy lens, designed to withstand damaging effects of outdoor environments.



## WARNINGS AND CAUTIONS

- Turn power off before inspection, installation or removal. Risk of electric shock - do not use where directly exposed to water or weather
- Suitable for damp locations outside as well as inside
- This device is not intended for use with emergency exit fixtures or emergency exit lights