



Exterior Lighting Sconce Fixtures

**Program Details**

Supplier	E Sam Jones Gexpro Regency Lighting
Product Description	Slim12 *Specification sheet is attached
Customer Service	E Sam Jones: 800-624-9349 Gexpro: 800-243-4040 Regency: 800-284-2024 x5240
Net Pricing	E Sam Jones: \$127.50 Regency: \$133.00 GexPro \$129.71
Price Protection	December 31, 2016
Lead-Time	Factory Stock (subject to prior sale) 1 week for standard delivery
Warranty	5 Year
FOB	Atlanta, GA
ARCOP Internal Program Contact	Sam Kim (678)514-4300 <a href="mailto:skim@arbys.com">skim@arbys.com</a>



# SLIM12

## RAB

LIGHTING



12, 18 and 26 Watt SLIM wallpacks are ultra efficient and deliver impressive light distribution with a compact low-profile design that's super easy to install as a downlight or uplight.

Color: Bronze  
Weight: 4.5 lbs

<b>Project:</b>	<b>Type:</b>
<b>Prepared By:</b>	<b>Date:</b>

### Driver Info

Type: Constant Current

120V: 0.12A

208V: 0.08A

240V: 0.07A

277V: 0.06A

Input Watts: 14W

Efficiency: 87%

### LED Info

Watts: 12W

Color Temp: 5100K (Cool)

Color Accuracy: 67 CRI

L70 Lifespan: 100,000

Lumens: 1,531

Efficacy: 111 LPW

### Technical Specifications

#### Listings

##### UL Listing:

Suitable for wet locations. Suitable for mounting within 1.2m (4ft) of the ground.

##### ADA Compliant:

SLIM™ is ADA Compliant.

##### DLC Listed:

This product is on the Design Lights Consortium (DLC) Qualified Products List and is eligible for rebates from DLC Member Utilities.

**Dark Sky Approved:**

The International Dark Sky Association has approved this product as a full cutoff, fully shielded luminaire.

**IESNA LM-79 & LM-80 Testing:**

RAB LED luminaires have been tested by an independent laboratory in accordance with IESNA LM-79 and LM-80, and have received the Department of Energy "Lighting Facts" label.

**Construction**

**IP Rating:**

Ingress Protection rating of IP66 for dust and water.

**Cold Weather Starting:**

The minimum starting temperature is -40°F/-40°C.

**Ambient Temperature:**

Suitable for use in 40°C (104°F) ambient temperatures.

**Thermal Management:**

Superior heat sinking with internal Air-Flow fins.

**Housing:**

Precision die-cast aluminum housing.

**Mounting:**

Heavy-duty mounting bracket with hinged housing for easy installation.

**Recommended Mounting Height:**

Up to 8 ft.

**Lens:**

Tempered glass lens.

**Reflector:**

Specular thermoplastic.

**Gaskets:**

High-temperature silicone.

**Finish:**

Our environmentally friendly polyester powder coatings are formulated for high-durability and long-lasting color, and contains no VOC or toxic heavy metals.

**Green Technology:**

Mercury and UV free, and RoHS compliant.

**LED Characteristics**

**LED:**

Multi-chip, long-life LED.

**Lifespan:**

100,000-hour LED lifespan based on IES LM-80 results and TM-21 calculations.

**Color Consistency:**

7-step MacAdam Ellipse binning to achieve consistent fixture-to-fixture color.

**Color Stability:**

LED color temperature is warranted to shift no more than 200K in CCT over a 5 year period.

**Color Uniformity:**

RAB's range of CCT (Correlated Color Temperature) follows the guidelines for the American National Standard for Specifications for the Chromaticity of Solid State Lighting (SSL) Products, ANSI C78.377-2011.

**Electrical**

**Driver:**

Constant Current, Class 2, 100-277V, 50/60 Hz., 4KV surge protection, 350mA, 100-240VAC 0.3-0.15 Amps, 277VAC 0.15Amps, Power Factor 99%.

**THD:**

10.1% at 120V

**Other**

**HID Replacement Range:**

The SLIM12 can be used to replace 70W MH based on delivered lumens.

**California Title 24:**

SLIM12 complies with 2013 California Title 24 building and electrical codes as a residential outdoor fixture. See SLIM12/PC for a model that complies as a commercial outdoor non-pole-mounted fixture, ≤30 Watts.

**Patents:**

The design of the SLIM™ is protected by patents in U.S. Pat D681,864, and pending patents in Canada, China, Taiwan and Mexico.

**Optical**

**BUG Rating:**


B1 U0 G0

Need help? Tech help line: 888 RAB-1000 Email: [sales@rabweb.com](mailto:sales@rabweb.com) Website: [www.rabweb.com](http://www.rabweb.com)

Copyright © 2014 RAB Lighting Inc. All Rights Reserved Note: Specifications are subject to change at any time without notice

Page 1 of 2

**SLIM12**  
**RAB**  
LIGHTING  
Dimensions



**Features**

- Full cutoff, fully shielded LED wallpack
- Can be used as a downlight or uplight
- Contractor friendly features for easy installation

- 100,000-hour LED Life
- 5-Year Warranty

**Ordering Matrix**

Family	Watts	Color Temp	Finish	Photocell	Dimming
SLIM					
	<ul style="list-style-type: none"> <li>• <b>26</b> = 26W</li> <li>• <b>18</b> = 18W</li> <li>• <b>12</b> = 12W</li> </ul>	<ul style="list-style-type: none"> <li>• <b>Blank</b> = Cool</li> <li>• <b>Y</b> = Warm</li> <li>• <b>N</b> = Neutral</li> </ul>	<ul style="list-style-type: none"> <li>• <b>Blank</b> = Bronze</li> <li>• <b>W</b> = White</li> </ul>	<ul style="list-style-type: none"> <li>• <b>Blank</b> = No Photocell</li> <li>• <b>/PC</b> = 120V Button</li> <li>• <b>/PC2</b> = 277V Button</li> </ul>	<ul style="list-style-type: none"> <li>• <b>Blank</b> = No Dimming</li> <li>• <b>/D10</b> = Dimmable</li> </ul>

Need help? Tech help line: **888 RAB-1000** Email: [sales@rabweb.com](mailto:sales@rabweb.com) Website: [www.rabweb.com](http://www.rabweb.com)  
 Copyright © 2014 RAB Lighting Inc. All Rights Reserved Note: Specifications are subject to change at any time without notice  
 Page 2 of 2

Inserted from <<http://www.rabweb.com/specSheet.php?product=SLIM12>>

# SLIM12W

## RAB LIGHTING



12, 18 and 26 Watt SLIM wallpacks are ultra efficient and deliver impressive light distribution with a compact low-profile design that's super easy to install as a downlight or uplight.

Color: White  
Weight: 4.5 lbs

<b>Project:</b>	<b>Type:</b>
<b>Prepared By:</b>	<b>Date:</b>

### Driver Info

Type: Constant Current

120V: 0.12A

208V: 0.08A

240V: 0.07A

277V: 0.06A

Input Watts: 14W

Efficiency: 87%

### LED Info

Watts: 12W

Color Temp: 5100K (Cool)

Color Accuracy: 67 CRI

L70 Lifespan: 100,000

Lumens: 1,531

Efficacy: 111 LPW

### Technical Specifications

#### Listings

##### UL Listing:

Suitable for wet locations. Suitable for mounting within 1.2m (4ft) of the ground.

##### ADA Compliant:

SLIM™ is ADA Compliant.

##### DLC Listed:

This product is on the Design Lights Consortium (DLC) Qualified Products List and is eligible for rebates from DLC Member Utilities.

**Dark Sky Approved:**

The International Dark Sky Association has approved this product as a full cutoff, fully shielded luminaire.

**IESNA LM-79 & LM-80 Testing:**

RAB LED luminaires have been tested by an independent laboratory in accordance with IESNA LM-79 and LM-80, and have received the Department of Energy "Lighting Facts" label.

**Construction**

**IP Rating:**

Ingress Protection rating of IP66 for dust and water.

**Cold Weather Starting:**

The minimum starting temperature is -40°F/-40°C.

**Ambient Temperature:**

Suitable for use in 40°C (104°F) ambient temperatures.

**Thermal Management:**

Superior heat sinking with internal Air-Flow fins.

**Housing:**

Precision die-cast aluminum housing.

**Mounting:**

Heavy-duty mounting bracket with hinged housing for easy installation.

**Recommended Mounting Height:**

Up to 8 ft.

**Lens:**

Tempered glass lens.

**Reflector:**

Specular thermoplastic.

**Gaskets:**

High-temperature silicone.

**Finish:**

Our environmentally friendly polyester powder coatings are formulated for high-durability and long-lasting color, and contains no VOC or toxic heavy metals.

**Green Technology:**

Mercury and UV free, and RoHS compliant.

**LED Characteristics**

**LED:**

Multi-chip, long-life LED.

**Lifespan:**

100,000-hour LED lifespan based on IES LM-80 results and TM-21 calculations.

**Color Consistency:**

7-step MacAdam Ellipse binning to achieve consistent fixture-to-fixture color.

**Color Stability:**

LED color temperature is warranted to shift no more than 200K in CCT over a 5 year period.

**Color Uniformity:**

RAB's range of CCT (Correlated Color Temperature) follows the guidelines for the American National Standard for Specifications for the Chromaticity of Solid State Lighting (SSL) Products, ANSI C78.377-2011.

**Electrical**

**Driver:**

Constant Current, Class 2, 100-277V, 50/60 Hz., 4KV surge protection, 350mA, 100-240VAC 0.3-0.15 Amps, 277VAC 0.15Amps, Power Factor 99%.

**THD:**

10.1% at 120V

**Other**

**HID Replacement Range:**

The SLIM12 can be used to replace 70W MH based on delivered lumens.

**California Title 24:**

SLIM12 complies with 2013 California Title 24 building and electrical codes as a residential outdoor fixture. See SLIM12/PC for a model that complies as a commercial outdoor non-pole-mounted fixture, ≤30 Watts.

**Patents:**

The design of the SLIM™ is protected by patents in U.S. Pat D681,864, and pending patents in Canada, China, Taiwan and Mexico.

**Optical**

**BUG Rating:**

B1 U0 G0


Need help? Tech help line: **888 RAB-1000** Email: [sales@rabweb.com](mailto:sales@rabweb.com) Website: [www.rabweb.com](http://www.rabweb.com)

Copyright © 2014 RAB Lighting Inc. All Rights Reserved Note: Specifications are subject to change at any time without notice

Page 1 of 2

## SLIM12W

**RAB**  
LIGHTING  
Dimensions



**Features**

- Full cutoff, fully shielded LED wallpack
- Can be used as a downlight or uplight
- Contractor friendly features for easy installation



- 100,000-hour LED Life
- 5-Year Warranty

**Ordering Matrix**

Family	Watts	Color Temp	Finish	Photocell	Dimming
SLIM					
	<ul style="list-style-type: none"> <li>• <b>26</b> = 26W</li> <li>• <b>18</b> = 18W</li> <li>• <b>12</b> = 12W</li> </ul>	<ul style="list-style-type: none"> <li>• <b>Blank</b> = Cool</li> <li>• <b>Y</b> = Warm</li> <li>• <b>N</b> = Neutral</li> </ul>	<ul style="list-style-type: none"> <li>• <b>Blank</b> = Bronze</li> <li>• <b>W</b> = White</li> </ul>	<ul style="list-style-type: none"> <li>• <b>Blank</b> = No Photocell</li> <li>• <b>/PC</b> = 120V Button</li> <li>• <b>/PC2</b> = 277V Button</li> </ul>	<ul style="list-style-type: none"> <li>• <b>Blank</b> = No Dimming</li> <li>• <b>/D10</b> = Dimmable</li> </ul>

Need help? Tech help line: **888 RAB-1000** Email: [sales@rabweb.com](mailto:sales@rabweb.com) Website: [www.rabweb.com](http://www.rabweb.com)  
 Copyright © 2014 RAB Lighting Inc. All Rights Reserved Note: Specifications are subject to change at any time without notice  
 Page 2 of 2

Inserted from <<http://www.rabweb.com/specSheet.php?product=SLIM12W>>