

# Summit Credit Union – Waukesha Branch Waukesha, Wisconsin Stormwater Management and Erosion Control Plan

[www.JSDinc.com](http://www.JSDinc.com)



Planning & Development  
Site/Civil Engineering  
Transportation Engineering  
Structural Engineering  
Water Resources  
Landscape Architecture  
Surveying & Mapping  
Construction Management

Prepared for:  
**Summit Credit Union**  
4800 American Parkway  
Madison, WI 53718

JSD Project No.: 18-8469

April 6, 2018

Prepared by: Corey Huhta, P.E., C.F.M

**JSD** Professional Services, Inc.  
• Engineers • Surveyors • Planners

# TABLE OF CONTENTS

|   |   |
|---|---|
| 1.0 INTRODUCTION .....                                      | 1 |
| 2.0 EXISTING CONDITIONS.....                                | 1 |
| 3.0 DESIGN CRITERIA.....                                    | 1 |
| 3.1 Municipal Code of the City of Waukesha, Wisconsin ..... | 1 |
| 3.3 Waukesha County Code of Ordinances.....                 | 1 |
| 3.4 Wisconsin Administrative Code .....                     | 1 |
| 4.0 ANALYSIS.....   | 1 |
| 5.0 DESIGN.....   | 2 |
| 5.1 Peak Discharge .....                                    | 3 |
| 5.2 Sediment Control .....                                  | 3 |
| 6.0 EROSION CONTROL .....                                   | 3 |
| 7.0 CONCLUSION.....   | 4 |

## APPENDICES

APPENDIX 1 – ALTA/NSPS LAND TITLE SURVEY

APPENDIX 2 – SOILS INFORMATION

APPENDIX 3 – PRELIMINARY PLANS

APPENDIX 4 – PRE-DEVELOPMENT HYDROLOGIC CALCULATIONS

APPENDIX 5 – POST-DEVELOPMENT HYDROLOGIC CALCULATIONS

APPENDIX 6 – SEDIMENT CALCULATIONS

APPENDIX 7 – STORM SEWER SIZING CALCULATIONS

APPENDIX 8 – USLE INFORMATION

APPENDIX 9 – MAINTAINANCE AGREEMENT

### Future questions and comments can be directed to:

Corey Huhta, P.E., C.F.M.  
Project Engineer

[corey.huhta@jsdinc.com](mailto:corey.huhta@jsdinc.com)  
Phone: 608.848.5060  
Fax: 608.848.2255

**JSD Professional Services, Inc.**  
• Engineers • Surveyors • Planners  
*Madison Regional Office*

161 Horizon Drive, Suite 101  
Verona, WI 53593  
[www.jsdinc.com](http://www.jsdinc.com)

## 1.0 INTRODUCTION

This technical report shall serve as the stormwater management design report for the Summit Credit Union project in the City of Waukesha, Waukesha County, Wisconsin.

The proposed project is a 1.13-acre project located on Lot of Certified Survey Map (CSM) 10663. The site is a redevelopment of the existing Sonic Drive-in restaurant between East Moreland Road (USH 18) and Heritage Lane. The project scope includes the demolition of the existing building, drive-in, parking canopies, and associated parking lots. The project consists of a 3,900 square foot building, 20 parking stalls, reconnection of access drives, and an underground water quality chamber. The stormwater facilities are reconnected to the storm sewer pipe connection in Heritage Lane. The proposed construction start date is anticipated for Spring 2019 with project completion by Fall 2019.

## 2.0 EXISTING CONDITIONS

The existing impervious area of the site is 0.752 acres consisting of asphalt parking, driveways, sidewalk, and building footprint. The proposed impervious of the site is 0.706 acres consisting of the same. There is a decrease of 0.044 acres of impervious area with an overall site impervious ratio of 62.4%. The existing site drains to an existing private stormwater system that connects to public storm sewer within Heritage Lane to the north. The existing site generally slopes to the north with a relief of 11 feet across the site. Refer to **Appendix 1** for the ALTA/NSPS Land Title Survey for the project.

A geotechnical report is being prepared for the site and will be provided during permitting. The NRCS web soil survey report was consulted for hydrologic soil groups. The NRCS web soil survey report is located in **Appendix 2**.

Stormwater runoff from the existing site consists of a single watershed. An existing watershed map can be found in **Appendix 4**.

## 3.0 DESIGN CRITERIA

### *3.1 Municipal Code of the City of Waukesha, Wisconsin*

Chapter 32 – Stormwater Management and Erosion Control

### *3.3 Waukesha County Code of Ordinances*

Chapter 14, Article VIII – Stormwater Management and Erosion Control Ordinance

### *3.4 Wisconsin Administrative Code*

WDNR – Technical Standards (NR 151 and NR 216)

The site will need to meet the criteria for a redevelopment site. Therefore, the requirements for this site include:

- Maintain pre-development peak discharges for the 1-, 5-, and 100-year, 24-hour storm events.
- Reduce the total suspended solids by 40% during the 1-year, 24-hour storm event assuming no re-suspension.

## 4.0 ANALYSIS

The stormwater management and erosion control plan have been written and analyzed for the development. Construction will include both on-site stormwater management and erosion control.

HydroCAD® stormwater modeling system (Version 10.00-20) has been used to analyze stormwater characteristics for the development. HydroCAD uses the accepted TR-55 – Urban Hydrology for Small Watersheds methodology for determining peak discharge runoff rates. The NOAA Atlas 14 rainfall depths for Waukesha County and the MSE 3 rainfall distribution were used in the hydrologic model. Due to the urbanization of the site, the minimum time of concentration of 6 minutes has been used per TR-55 standard methodology.

Curve numbers for the post-development ground cover were selected using the standard values specified TR-55. The maximum pre-development curve numbers were set per the WDNR Technical Standard NR 151. The curve number used for grassland was used in post-development conditions for pervious ground cover.

See **Table 1** below for the curve numbers that used for hydrologic modeling.

| Runoff Curve Number | Hydrologic Soil Group |     |     |     |
|---------------------|-----------------------|-----|-----|-----|
|                     | A                     | B   | C   | D   |
| Woodland            | 30                    | 55  | 70  | 77  |
| Grassland           | 39                    | 61  | 71  | 78  |
| Cropland            | 55                    | 69  | 78  | 83  |
| Impervious          | 98                    | 98  | 98  | 98  |
| Water Bodies        | 100                   | 100 | 100 | 100 |

Refer to **Appendix 4 and 5** for further information on pre-development and post-development hydrologic modeling for the development.

Sediment control used separate WinSLAMM Version 10.3 to account for total suspended solids (TSS) removal for the site. Refer to **Appendix 7** for further information on sediment control calculations.

The storm sewer peak flow rates were calculated using the Rational Method to determine peak flow rates for the 10-year storm event. The storm sewer was analyzed per the Wisconsin Department of Natural Resources Facility Design Manual (FDM) for a closed conduit system. Refer to **Appendix 9** for further information on the storm sewer sizing.

## 5.0 DESIGN

The underground water quality chamber proposed will provide total suspended solids reduction and peak discharge control for the project. Parking lot runoff will be collected within private storm sewer, treated within the underground water quality chamber, and ultimately discharged to the existing storm sewer within Heritage Lane. The roof runoff will be collected through roof drain connections and route to the private storm sewer system. A small portion of the access driveways and pervious area totaling 0.30 acres will match existing drainage patterns and will leave the site untreated and drain to Heritage Road public storm sewer.

The private storm sewer system consist of 5 curb inlets which are connected to an underground water quality chamber. The underground chamber will have a three foot sump below the outlet which acts as a sedimentation basin and provides settlement for suspended solids. The water quality chamber ultimately connects to the public storm sewer in Heritage Lane. The water quality chamber will settle out up to 20 micron particle. As designed, the stormwater management facility provides approximately 40.5% TSS reduction for the site.

Due to existing drainage patterns, approximately 0.13 acres of off-site area surface drains onto the project. This runoff will be collected into the private storm sewer and routed through the chamber. However, this off-site drainage was not considered in the TSS calculations as it is an off-site area.

A proposed watershed map can be referenced in **Appendix 5**. Preliminary construction plans of improvements can be found in **Appendix 3**.

### 5.1 Peak Discharge

#### Municipal Code of the City of Waukesha, WI Sec. 13.10 (d)(1). Total Sediment Control

A. Minimum requirement. To minimize downstream bank erosion and the failure of downstream conveyance systems, the calculated post-development peak storm water discharge rate shall not exceed the calculated pre-development discharge rates for the 2-year, 10-year, and 100-year, 24-hour design storms.

The proposed redevelopment of the site maintains existing drainage patterns and removes existing impervious surfaces on-site. This reduction reduces the uncontrolled peak discharges for the 2-, 10-, and 100-year, 24-hour design storms. The water quality chamber provides additional peak discharge reduction as runoff is routed through the system.

TABLE 2: PRE-SETTLEMENT VERSUS POST-DEVELOPMENT PEAK RUNOFF RATES

|  | 2-year | 10-year | 100-year |
|--|--------|---------|----------|
| Rainfall for each 24-hour storm event (inches)   | 4.17   | 6.47    | 11.35    |
| Pre-development peak discharge rate (cfs)  | 4.17   | 6.47    | 11.35    |
| Post-Development peak discharge rate without controls (cfs)  | 4.04   | 6.34    | 11.23    |
| Post-Development peak discharge rate with detention (cfs)  | 3.30   | 5.10    | 10.74    |
| Difference: Post-Development peak discharge rates with detention vs. Pre-Development peak discharge Rate (cfs) | -0.87  | -1.37   | -0.61    |

**Table 2** above shows the overall development pre-development, the uncontrolled post-development, and post-development peak runoff rates comparison.

### 5.2 Sediment Control

#### Municipal Code of the City of Waukesha, WI Sec. 13.10 (d)(2). Total Sediment Control

By design, each storm water management plan shall meet the following post-development total suspended solids reduction targets, based on average annual rainfalls, as compared to no runoff management controls:

- (i.) For new land development, 80% reduction in total suspended solids load;
- (ii.) For redevelopment, 40% reduction of total suspended solids load;
- (iii.) For in-fill development that occurs prior to October 1, 2012, 40 % reduction total suspended solids load.
- (iv.) For in-fill development that occurs after October 1, 2012, 80% reduction of total suspended solids load.

The underground water quality chamber has been designed to provide sediment control for the site. Due to existing drainage patterns, approximately 0.30 acres of drainage area will bypass treatment. The overall development yields approximately 470 pounds of particulate solids. The underground water quality chamber removes approximately 190 pounds of particulate solids for a 40.5% total suspended solids reduction. The development was modeled using WinSLAMM Version 10.3.4. See **Appendix 6** for the sediment control modeling inputs and outputs.

## 6.0 EROSION CONTROL

Erosion control measures onsite will conform to the Wisconsin Department of Natural Resources Technical Standards and City of Waukesha requirements. These measures include, but are not

limited to: construction entrances, silt fencing, check dams, grading, seeding, mulching, and erosion matting. Construction sequencing shall be as follows:

1. Install silt fence in the appropriate locations and stone tracking pads on the entrances to be used by the construction vehicles to access the site.
2. Remove existing pavement and structures.
3. Install storm sewer system.
4. Excavate building foundations.
5. Complete all other grading.
6. Install storm sewer and inlet protection measures.
7. Install aggregate base course and paving in parking areas.
8. Stabilize newly graded soils.
9. Complete exterior building work and downspouts
10. Remove temporary erosion control practices.

For more detailed requirements regarding erosion control, refer to the proposed construction plans in **Appendix 3** and Universal Soil Loss Equation (USLE) worksheet in **Appendix 9**.

## 7.0 CONCLUSION

Stormwater management features for Summit Credit Union – Waukesha Branch have been designed in accordance with applicable standards per Chapter 32 of the Municipal Code of the City of Waukesha, Chapter 14 of the Waukesha County Code of Ordinances, and WDNR standards NR151 and NR216. The development features an underground water quality chamber and public storm sewer. These facilities will treat for sediment, oil and grease, runoff rate, infiltration, and outlet controls. Erosion control practices will limit soil loss to 7.5 tons per acre annually, and regulate soil transportation within development boundaries.

# **APPENDIX 1**

## **ALTA/NSPS LAND TITLE SURVEY**



# ALTA/NSPS LAND TITLE SURVEY

LOT 1, CERTIFIED SURVEY MAP No. 10663, LOCATED IN THE NORTHWEST QUARTER OF THE NORTHWEST QUARTER OF SECTION 31, TOWNSHIP 07 NORTH, RANGE 20 EAST, CITY OF WAUKESHA, WAUKESHA COUNTY, WISCONSIN.



CREATE THE VISION TELL THE STORY

MADISON | MILWAUKEE  
KENOSHA | APPLETON | WAUSAU


MADISON REGIONAL OFFICE  
161 HORIZON DRIVE, SUITE 101  
VERONA, WISCONSIN 53583  
P. 608.848.5060

CLIENT:  
**SUMMIT CREDIT UNION**

CLIENT ADDRESS:  
**4800 AMERICAN PARKWAY  
MADISON, WI 53718-8308**

PROJECT:  
**WAUKESHA**

PROJECT LOCATION:  
**CITY OF WAUKESHA  
WAUKESHA COUNTY, WISCONSIN**




PLAN MODIFICATIONS:

| #  | Date | Description |
|----|------|-------------|
| 1  |      |             |
| 2  |      |             |
| 3  |      |             |
| 4  |      |             |
| 5  |      |             |
| 6  |      |             |
| 7  |      |             |
| 8  |      |             |
| 9  |      |             |
| 10 |      |             |
| 11 |      |             |
| 12 |      |             |
| 13 |      |             |
| 14 |      |             |
| 15 |      |             |

SHEET TITLE:  
**ALTA/NSPS LAND  
TITLE SURVEY**

MAP No: E-#  
SHEET NUMBER:  
**1 OF 1**

JSD PROJECT NO: 18-8460



- LEGEND**
- GOVERNMENT CORNER
  - 1" IRON PIPE FOUND
  - CHISELED 'X' FOUND
  - COTTON SPINDLE SET
  - FINISHED FLOOR SHOT LOCATION
  - SDM
  - SANITARY MANHOLE
  - CLEAN OUT
  - HYDRANT
  - WATER VALVE
  - ROUND CASTED INLET
  - CURB INLET
  - GAS REGULATOR/METER
  - MANHOLE - GREASE TRAP
  - ELECTRIC MANHOLE
  - ELECTRIC PEDESTAL
  - POWER POLE W/GUY
  - LIGHT POLE
  - TELEPHONE PEDESTAL
  - TELEPHONE MANHOLE
  - DECIDUOUS TREE
  - CONIFEROUS TREE
  - BUSH
  - HANDICAP PARKING
  - PARCEL BOUNDARY
  - SECTION LINE
  - RIGHT-OF-WAY LINE
  - CENTERLINE
  - CHORD LINE
  - PLATTED LOT LINE
  - EASEMENT LINE
  - CONCRETE CURB & GUTTER
  - SANITARY SEWER
  - WATER LINE
  - STORM SEWER
  - NATURAL GAS
  - OVERHEAD ELECTRIC DISTRIBUTION
  - UNDERGROUND ELECTRIC
  - FIBER OPTIC
  - UNDERGROUND TELEPHONE
  - UNDERGROUND CABLE
  - EDGE OF WOODS OR BRUSH
  - BUILDING
  - WALL LINE
  - INDEX CONTOUR
  - INTERMEDIATE CONTOUR
  - SPOT ELEVATION
  - BITUMINOUS PAVEMENT
  - RETAINING WALL
  - CONCRETE PAVEMENT
  - NO ACCESS
  - PAVEMENT STRIPING
  - END OF FLAGGED UTILITIES
  - DENOTES RECORD DATA DECTION THE SAME LINE ON THE GROUND AS DETECTED BY THIS SURVEY
  - CANOPY COLUMN (TYP)
  - EDGE OF CANOPY

- NOTES**
- FIELD WORK PERFORMED BY JSD PROFESSIONAL SERVICES, INC. ON MARCH 29, 2018.
  - BEARINGS FOR THIS SURVEY AND MAP ARE BASED ON THE SOUTHEASTERN WISCONSIN REGIONAL PLANNING COMMISSION (SEWRPC), THE WEST LINE OF THE NORTHWEST QUARTER OF SECTION 31-07-20, BEARS 50073057"E.
  - ELEVATIONS ARE BASED ON THE NATIONAL GEODETIC VERTICAL DATUM OF 1929 (NGVD29). BENCHMARK IS A BRASS CAP IN CONCRETE MARKING THE NORTHWEST CORNER OF SECTION 31-07-20, ELEVATION = 931.30'
  - CONTOUR INTERVAL IS ONE FOOT.
  - SUBSURFACE UTILITIES AND FEATURES SHOWN ON THIS MAP HAVE BEEN APPROXIMATED BY LOCATING SURFICIAL FEATURES AND APPURTENANCES, LOCATING DIGGERS HOTLINE FIELD MARKINGS AND BY REFERENCE TO UTILITY RECORDS AND MAPS. BIGGER'S HOTLINE TICKET No.s 20181108335, 20181108347, 20181108366, 20181108372, 20181108416 AND 20181108425, WITH A CLEAR DATE OF MARCH 26, 2018.
  - UTILITY COMPANIES CONTACTED THRU DIGGERS HOTLINE: CITY OF DELAFIELD, DEPARTMENT OF PUBLIC WORKS WISCONSIN DOT-TS EQUIPMENT AT&T TRANSMISSION WE ENERGIES WISCONSIN DOT SOUTHEAST REGION LEVEL 3 COMMUNICATIONS TIME WARNER CABLE
  - BEFORE EXCAVATION, APPROPRIATE UTILITY COMPANIES SHOULD BE CONTACTED. FOR EXACT LOCATION OF UNDERGROUND UTILITIES, CONTACT DIGGERS HOTLINE, AT 1.800.242.8511.
  - JSD PROFESSIONAL SERVICES, INC. DOES NOT GUARANTEE THAT THE BENCHMARK ELEVATIONS LISTED ON THIS MAP HAVE NOT BEEN DISTURBED SINCE THE DATE OF THIS SURVEY AND SHOULD BE VERIFIED PRIOR TO CONSTRUCTION ACTIVITIES.
  - SET BACKS ARE BASED ON CHAPTER 22, 22.37(7). THERE ARE NO REFERENCES MADE TO CORNER LOTS. SET BACKS ALONG HERITAGE LANE MAY BE GREATER, CONTACT CITY OF WAUKESHA ZONING DEPARTMENT.
  - SANITARY SEWER AND WATER SERVICE LATERAL SIZE AND LOCATION ARE UNKNOWN.

- NOTES CORRESPONDING TO TABLE A REQUIREMENTS:**
- ITEM 3 THE SUBJECT PROPERTY LIES IN ZONE X (AREAS DETERMINED TO BE OUTSIDE THE 0.2% ANNUAL CHANCE FLOODPLAIN) PER FEMA MAP NUMBER 5504790186F, EFFECTIVE DATE OF NOVEMBER 19, 2008.
  - ITEM 6(b) CURRENT ZONING CLASSIFICATION IS B-5, COMMUNITY BUSINESS, FROM CITY WEB SITE.
  - ITEM 9 THERE ARE 10 REGULAR PARKING SPACES AND 1 HANDICAP SPACE FOR A TOTAL OF 11 PARKING SPACES.
  - ITEM 10(a) THERE ARE NO DIVISION OR PARTY WALLS WITH RESPECT TO ADJOINING PROPERTIES.
  - ITEM 11 SOURCE INFORMATION FROM PLANS AND MARKING WILL BE COMBINED WITH OBSERVED EVIDENCE OF UTILITIES PURSUANT TO SECTION 9.6.I.V. TO DEVELOP A VIEW OF THE UNDERGROUND UTILITIES. HOWEVER, THE EXACT LOCATION OF UNDERGROUND FEATURES CANNOT BE ACCURATELY, COMPLETELY AND RELIABLY DEPICTED. IN ADDITION, IN SOME JURISDICTIONS, 811 OR OTHER SIMILAR UTILITY LOCATE REQUESTS FROM SURVEYORS MAY BE IGNORED OR RESULT IN AN INCOMPLETE RESPONSE. IN WHICH CASE, THE SURVEYOR SHALL NOTE ON THE PLAT OR MAP HOW THIS AFFECTED THE SURVEYOR'S ASSESSMENT OF THE LOCATION OF THE UTILITIES. WHERE ADDITIONAL OR MORE DETAILED INFORMATION IS REQUIRED, THE CLIENT IS ADVISED THAT EXCAVATION AND/OR A PRIVATE UTILITY LOCATE REQUEST MAY BE NECESSARY.
  - ITEM 16 THERE IS NO OBSERVED EVIDENCE OF CURRENT EARTH MOVING WORK, BUILDING CONSTRUCTION OR BUILDING ADDITIONS AT THE TIME OF THIS SURVEY.
  - ITEM 17 THERE ARE NO PROPOSED CHANGES IN THE STREET RIGHT-OF-WAY LINES PER CITY OF DELAFIELD. THERE IS NO OBSERVED EVIDENCE OF RECENT STREET OR SIDEWALK CONSTRUCTION OR REPAIRS.
  - ITEM 18 THERE HAS BEEN NO FIELD DELINEATION OF WETLANDS CONDUCTED FOR THIS SITE.
  - ITEM 19 ANY OFFSITE EASEMENT FOR THE SUBJECT PROPERTY IS SHOWN IN ITS ENTIRETY.

- NOTES CORRESPONDING TO SCHEDULE B-SECTION TWO EXCEPTIONS**  
(CHICAGO TITLE INSURANCE COMPANY, COMMITMENT No.: CO-7333, COMMITMENT DATE: MARCH 6, 2018)
- (10) EASEMENT(S) FOR THE PURPOSE(S) AND RIGHTS INCIDENTAL THERETO, AS GRANTED IN A DOCUMENT, GRANTED TO WISCONSIN TELEPHONE COMPANY AND WISCONSIN ELECTRIC POWER COMPANY, FOR UTILITY PURPOSES, RECORDED ON APRIL 6, 1960, AS DOCUMENT No. 520795. THIS ITEM DOES NOT AFFECT THE SUBJECT PROPERTY AND IS NOT PLOTTED HEREON. (S IN CURRENT HIGHWAY RIGHT-OF-WAY).
  - (11) ACCESS LIMITATIONS AND DEVELOPMENT RESTRICTIONS SET FORTH IN INDENTURE RECORDED FEBRUARY 9, 1966 AS DOCUMENT No. 655271. THIS ITEM DOES AFFECT THE SUBJECT PROPERTY AND IS PLOTTED HEREON.
  - (12) EASEMENT(S) FOR THE PURPOSE(S) AND RIGHTS INCIDENTAL THERETO, AS GRANTED IN A DOCUMENT, GRANTED TO WISCONSIN ELECTRIC POWER COMPANY AND WISCONSIN TELEPHONE COMPANY, FOR UTILITY PURPOSES, RECORDED ON MARCH 13, 1976, AS DOCUMENT No. 756797. THIS ITEM DOES AFFECT THE SUBJECT PROPERTY AND IS PLOTTED HEREON.
  - (13) RECITALS AS SHOWN ON CERTIFIED SURVEY MAP No. 2681 RECORDED ON SEPTEMBER 1, 1976, AS DOCUMENT No. 965499, WHICH AMONG OTHER THINGS RECITES EASEMENT FOR INGRESS AND EGRESS, RESTRICTIONS AND NOTES. THIS ITEM DOES AFFECT THE SUBJECT PROPERTY AND IS PLOTTED HEREON.
  - (14) MEMORANDUM OF AGREEMENT RECORDED MARCH 8, 1977 AS DOCUMENT No. 987077. THIS ITEM DOES AFFECT THE SUBJECT PROPERTY AND IS NOT GRAPHIC IN NATURE, THEREFORE IT IS NOT PLOTTED HEREON.
  - (15) EASEMENT(S) FOR THE PURPOSE(S) AND RIGHTS INCIDENTAL THERETO, AS GRANTED IN A DOCUMENT, GRANTED TO THE CITY OF WAUKESHA, FOR SANITARY SEWER PURPOSES, RECORDED ON OCTOBER 25, 1977, AS DOCUMENT No. 1021809. THIS ITEM DOES AFFECT THE SUBJECT PROPERTY AND IS PLOTTED HEREON.
  - (16) EASEMENT(S) FOR THE PURPOSE(S) AND RIGHTS INCIDENTAL THERETO, AS GRANTED IN A DOCUMENT, GRANTED TO THE CITY OF WAUKESHA, FOR SANITARY SEWER PURPOSES, RECORDED ON NOVEMBER 2, 1977, AS DOCUMENT No. 1022917. THIS ITEM DOES AFFECT THE SUBJECT PROPERTY AND IS PLOTTED HEREON.
  - (17) EASEMENT(S) FOR THE PURPOSE(S) AND RIGHTS INCIDENTAL THERETO, AS GRANTED IN A DOCUMENT, GRANTED TO THE CITY OF WAUKESHA, FOR SANITARY SEWER PURPOSES, RECORDED ON JUNE 30, 1978, AS DOCUMENT No. 1054817. THIS ITEM DOES AFFECT THE SUBJECT PROPERTY AND IS PLOTTED HEREON.
  - (18) SANITARY SEWER EASEMENT RECORDED DECEMBER 7, 1978 AS DOCUMENT No. 1075472. THIS ITEM DOES AFFECT THE SUBJECT PROPERTY AND IS PLOTTED HEREON.
  - (19) RECITALS AS SHOWN ON CERTIFIED SURVEY MAP No. 10663 RECORDED ON MARCH 31, 2009, AS DOCUMENT No. 3641473, WHICH AMONG OTHER THINGS RECITES SIDEWALK EASEMENT, RESTRICTIONS, NOTES, INGRESS/EGRESS EASEMENT, CROSS ACCESS EASEMENT, TEMPORARY SLOPE EASEMENT FOR SIDEWALK CONSTRUCTION AND ACCESS LIMITATIONS. THIS ITEM MAY AFFECT THE SUBJECT PROPERTY AND IS PLOTTED HEREON.

**LEGAL DESCRIPTION (AS FURNISHED)**  
(CHICAGO TITLE INSURANCE COMPANY, COMMITMENT No.: CO-7333, COMMITMENT DATE: MARCH 6, 2018)


LOT 1 OF CERTIFIED SURVEY MAP No. 10663, RECORDED MARCH 31, 2009, IN VOLUME 102 OF CERTIFIED SURVEY MAPS ON PAGES 309 TO 313 AS DOCUMENT No. 3641473, A DIVISION OF PARCEL 6 OF CERTIFIED SURVEY MAP No. 2681 AND LANDS IN THE NORTHWEST 1/4 OF THE NORTHWEST 1/4 OF SECTION 31, TOWN 7 NORTH, RANGE 20 EAST, IN THE CITY OF WAUKESHA, COUNTY OF WAUKESHA, STATE OF WISCONSIN.

TAX KEY No.: WAC 1130.115.001  
ADDRESS: 2208 E. MORELAND BLVD.

**SURVEYOR'S CERTIFICATE**  
TO:  
1) PINNACLE WAUKESHA BURGERS, LLC, A WISCONSIN LIMITED LIABILITY COMPANY,  
2) BANK MUTUAL,  
3) CHICAGO TITLE INSURANCE COMPANY.

THIS IS TO CERTIFY THAT THIS MAP OR PLAT AND THE SURVEY ON WHICH IT IS BASED WERE MADE IN ACCORDANCE WITH THE 2016 MINIMUM STANDARD DETAIL REQUIREMENTS FOR ALTA/NSPS LAND TITLE SURVEYS, JOINTLY ESTABLISHED AND ADOPTED BY ALTA AND NSPS AND INCLUDES ITEMS 1, 2, 3, 4, 5, 6(a), 7(a), 7(b), 7(c), 8, 9, 10(c), 11, 13, 14, 16, 17, 18, 19 AND 20 OF TABLE A THEREOF. THE FIELD WORK WAS COMPLETED ON MARCH 28, 2018.

JOHN KREBS, S-1878  
PROFESSIONAL LAND SURVEYOR



**STORM SEWER MANHOLES**

| STRUCT. ID | RIM ELEVATION | INVERT | ELEVATION | PIPE SIZE | PIPE TYPE |
|------------|---------------|--------|-----------|-----------|-----------|
| STM-1      | 930.77        | NE     | 928.67    | 10"       | PVC       |
|            |               | SW     | 928.68    | 6"        | PVC       |
|            |               | NW     | 928.17    | 10"       | PVC       |
| STM-2      | 933.33        | SE     | 930.98    | 6"        | PVC       |
|            |               | NW     | 930.38    | 10"       | PVC       |
|            |               | SW     | 929.62    | 10"       | PVC       |
| STM-3      | 932.92        | SW     | 929.59    | 6"        | PVC       |
|            |               | NW     | 930.29    | 6"        | PVC       |
|            |               | NE     | 927.87    | 10"       | PVC       |

**STORM SEWER INLETS**

| INLET ID | RIM ELEVATION | INVERT | ELEVATION | PIPE SIZE | PIPE TYPE |
|----------|---------------|--------|-----------|-----------|-----------|
| INL-1    | 931.90        | SW     | 928.12    | 10"       | PVC       |
|          |               | SE     | 928.28    | 10"       | PVC       |
|          |               | NE     | 924.22    | 10"       | PVC       |
| INL-2    | 918.30        | SW     | 918.73    | 10"       | PVC       |
|          |               | NE     | 915.75    | 12"       | RCP       |
|          |               | SW     | 915.47    | 12"       | RCP       |
| INL-3    | 919.32        | SW     | 915.47    | 12"       | RCP       |
|          |               | NW     | 915.47    | 12"       | RCP       |
|          |               | NE     | 915.47    | 12"       | RCP       |

**SANITARY SEWER MANHOLES**

| STRUCT. ID | RIM ELEVATION | INVERT | ELEVATION | PIPE SIZE | PIPE TYPE |
|------------|---------------|--------|-----------|-----------|-----------|
| SAN-1      | 936.92        | SE     | 930.66    | 6"        | PVC       |
|            |               | SW     | 930.51    | 6"        | PVC       |
|            |               | NW     | 930.58    | 6"        | PVC       |
| SAN-2      | 927.79        | SE     | 922.65    | 8"        | PVC       |
|            |               | NE     | 922.55    | 8"        | PVC       |
|            |               | SW     | 913.99    | 8"        | PVC       |
| SAN-3      | 920.49        | NE     | 913.79    | 8"        | PVC       |
|            |               | SW     | 913.99    | 8"        | PVC       |
|            |               | NE     | 913.79    | 8"        | PVC       |

**WATER VALVES**


| VALVE No. | SIZE | RIM ELEVATION | INVERT | TOP NUT ELEVATION | PIPE INVERT |
|-----------|------|---------------|--------|-------------------|-------------|
| WV-1      | 10"  | 938.75        | TN     | 932.45            | 930.70      |

**BENCHMARKS**

| BENCH MARK | ELEVATION | DESCRIPTION                                       |
|------------|-----------|---|
| BM-1       | 938.42    | ARROW ON HYDRANT IN FRONT OF SITE                 |
| BM-2       | 935.18    | RR SPIKE IN UTILITY POLE NORTHWEST CORNER OF SITE |

**CURVE TABLE**

| CURVE | LENGTH  | RADIUS  | DELTA     | CHORD   | CHORD BEARING |
|-------|---------|---------|-----------|---------|---------------|
| C-1   | 120.51' | 286.55' | 24°05'43" | 119.62' | N78°24'32"E   |
| ( )   | 120.51' | 286.55' | 24°05'43" | 119.62' | N79°34'58"E   |
| C-2   | 90.85'  | 63.96'  | 81°22'52" | 83.40'  | S73°24'58"E   |
| ( )   | 90.80'  | 63.96'  | 81°20'08" | 83.36'  | S72°10'24"E   |



File: L:\2018\188463\DWG\188463\_Bosemap.dwg Layout: ALTA User: J. Plattner: Apr 04, 2018 12:03pm xref.s




## **APPENDIX 2**

### **SOILS INFORMATION**


#### **USDA NRCS WEB SOIL SURVEY**



Hydrologic Soil Group—Milwaukee and Waukesha Counties, Wisconsin



Map Scale: 1:1,620 if printed on A landscape (11" x 8.5") sheet.




Map projection: Web Mercator Corner coordinates: WGS84 Edge tics: UTM Zone 16N WGS84




## MAP LEGEND

### Area of Interest (AOI)









 Area of Interest (AOI)

### Soils

#### Soil Rating Polygons





 A  
 A/D  
 B  
 B/D  
 C  
 C/D  
 D  
 Not rated or not available

#### Soil Rating Lines


 A  
 A/D  
 B  
 B/D  
 C  
 C/D  
 D  
 Not rated or not available

#### Soil Rating Points






 A  
 A/D  
 B  
 B/D

 C  
 C/D  
 D  
 Not rated or not available

### Water Features

 Streams and Canals

### Transportation

 Rails  
 Interstate Highways  
 US Routes  
 Major Roads  
 Local Roads

### Background

 Aerial Photography

## MAP INFORMATION

The soil surveys that comprise your AOI were mapped at 1:15,800.

**Warning:** Soil Map may not be valid at this scale.

Enlargement of maps beyond the scale of mapping can cause misunderstanding of the detail of mapping and accuracy of soil line placement. The maps do not show the small areas of contrasting soils that could have been shown at a more detailed scale.

Please rely on the bar scale on each map sheet for map measurements.

Source of Map: Natural Resources Conservation Service  
 Web Soil Survey URL:  
 Coordinate System: Web Mercator (EPSG:3857)

Maps from the Web Soil Survey are based on the Web Mercator projection, which preserves direction and shape but distorts distance and area. A projection that preserves area, such as the Albers equal-area conic projection, should be used if more accurate calculations of distance or area are required.

This product is generated from the USDA-NRCS certified data as of the version date(s) listed below.

Soil Survey Area: Milwaukee and Waukesha Counties, Wisconsin  
 Survey Area Data: Version 13, Oct 6, 2017

Soil map units are labeled (as space allows) for map scales 1:50,000 or larger.

Date(s) aerial images were photographed: Sep 7, 2014—Sep 22, 2014

The orthophoto or other base map on which the soil lines were compiled and digitized probably differs from the background imagery displayed on these maps. As a result, some minor shifting of map unit boundaries may be evident.



## Hydrologic Soil Group

| Map unit symbol                    | Map unit name                                 | Rating | Acres in AOI | Percent of AOI |
|------------------------------------|---|--------|--------------|----------------|
| HmB                                | Hochheim loam, 2 to 6 percent slopes          | D      | 0.0          | 0.4%           |
| HmB2                               | Hochheim loam, 2 to 6 percent slopes, eroded  | D      | 0.9          | 8.0%           |
| HmC2                               | Hochheim loam, 6 to 12 percent slopes, eroded | D      | 9.0          | 84.2%          |
| ScB                                | St. Charles silt loam, 2 to 6 percent slopes  | B      | 0.8          | 7.4%           |
| <b>Totals for Area of Interest</b> |   |        | <b>10.7</b>  | <b>100.0%</b>  |



## Description

Hydrologic soil groups are based on estimates of runoff potential. Soils are assigned to one of four groups according to the rate of water infiltration when the soils are not protected by vegetation, are thoroughly wet, and receive precipitation from long-duration storms.

The soils in the United States are assigned to four groups (A, B, C, and D) and three dual classes (A/D, B/D, and C/D). The groups are defined as follows:

Group A. Soils having a high infiltration rate (low runoff potential) when thoroughly wet. These consist mainly of deep, well drained to excessively drained sands or gravelly sands. These soils have a high rate of water transmission.

Group B. Soils having a moderate infiltration rate when thoroughly wet. These consist chiefly of moderately deep or deep, moderately well drained or well drained soils that have moderately fine texture to moderately coarse texture. These soils have a moderate rate of water transmission.

Group C. Soils having a slow infiltration rate when thoroughly wet. These consist chiefly of soils having a layer that impedes the downward movement of water or soils of moderately fine texture or fine texture. These soils have a slow rate of water transmission.

Group D. Soils having a very slow infiltration rate (high runoff potential) when thoroughly wet. These consist chiefly of clays that have a high shrink-swell potential, soils that have a high water table, soils that have a claypan or clay layer at or near the surface, and soils that are shallow over nearly impervious material. These soils have a very slow rate of water transmission.

If a soil is assigned to a dual hydrologic group (A/D, B/D, or C/D), the first letter is for drained areas and the second is for undrained areas. Only the soils that in their natural condition are in group D are assigned to dual classes.

## Rating Options

*Aggregation Method:* Dominant Condition

*Component Percent Cutoff:* None Specified

*Tie-break Rule:* Higher



# **APPENDIX 3**

## **PRELIMINARY PLANS**




# **APPENDIX 4**

## **PRE-DEVELOPMENT HYDROLOGIC CALCULATIONS**

EXISTING WATERSHED MAP  
PRE-DEVELOPMENT HYDROCAD OUTPUT



File: I:\2018\185469\DWG\185469 SWMP.dwg Layout: EX1.0 User: chuhita Plotted: Apr 06, 2018 - 10:12am Xref's:



**LEGEND (PROPOSED)**

|  |                                       |
|--|---------------------------------------|
|  | PROPERTY LINE                         |
|  | SETBACK LINE                          |
|  | EASEMENT LINE                         |
|  | BUILDING LINE                         |
|  | BUILDING OVERHANG LINE                |
|  | EDGE OF CONCRETE                      |
|  | STANDARD CURB AND GUTTER              |
|  | REJECT CURB AND GUTTER                |
|  | PROPOSED CONCRETE PAVEMENT            |
|  | PROPOSED HEAVY DUTY CONCRETE PAVEMENT |
|  | PROPOSED ASPHALT PAVEMENT             |
|  | PROPOSED HEAVY DUTY ASPHALT PAVEMENT  |
|  | LIGHT POLE                            |
|  | BOLLARD                               |

**WATERSHED CHARACTERISTICS**

|              |                              |  |
|--------------|------------------------------|--|
| WATERSHED A  | 49,353 SF (66.4% IMPERVIOUS) | 6 MINUTE TIME OF CONCENTRATION (MINIMUM) |
| WATERSHED OS | 5663 SF (25.0% IMPERVIOUS)   | 6 MINUTE TIME OF CONCENTRATION (MINIMUM) |



CREATE THE VISION TELL THE STORY

MADISON | MILWAUKEE  
KENOSHA | APPLETON | WAUSAU

MADISON REGIONAL OFFICE  
161 HORIZON DRIVE, SUITE 101  
VERONA, WISCONSIN 53593  
P. 608.848.5060

CLIENT:  
**SUMMIT CREDIT UNION**

CLIENT ADDRESS:  
**4800 American Parkway  
MADISON, WI 53718**

PROJECT:  
**SUMMIT CREDIT UNION - WAUKESHA BRANCH**

PROJECT LOCATION:  
**2208 E MORELAND BOULEVARD  
WAUKESHA COUNTY**

PLAN MODIFICATIONS:



| #  | Date: | Description: |
|----|-------|--------------|
| 1  |       |              |
| 2  |       |              |
| 3  |       |              |
| 4  |       |              |
| 5  |       |              |
| 6  |       |              |
| 7  |       |              |
| 8  |       |              |
| 9  |       |              |
| 10 |       |              |
| 11 |       |              |
| 12 |       |              |
| 13 |       |              |
| 14 |       |              |
| 15 |       |              |

Design/Drawn: CLH  
Approved: WHD

SHEET TITLE:  
**EXISTING DRAINAGE AREA MAP**


SHEET NUMBER:  
**EX1.0**

JSD PROJECT NO: 18-8469




THESE PLANS AND DESIGNS ARE COPYRIGHT PROTECTED AND MAY NOT BE USED IN WHOLE OR IN PART WITHOUT THE WRITTEN CONSENT OF JSD PROFESSIONAL SERVICES, INC.








Off-site



Pre-Development Site



Pre-Development





**Predevelopment**

Prepared by Microsoft

Printed 4/6/2018

HydroCAD® 10.00-20 s/n 02918 © 2017 HydroCAD Software Solutions LLC

Page 2

**Area Listing (all nodes)**

| Area<br>(acres) | CN        | Description<br>(subcatchment-numbers) |
|-----------------|-----------|---------------------------------------|
| 0.849           | 98        | Impervious, HSG D (A, OS)             |
| 0.381           | 78        | Pervious, HSG D (A)                   |
| 0.033           | 78        | Pervious, HSG D (OS)                  |
| <b>1.263</b>    | <b>91</b> | <b>TOTAL AREA</b>                     |

**Predevelopment**

Prepared by Microsoft

Printed 4/6/2018

HydroCAD® 10.00-20 s/n 02918 © 2017 HydroCAD Software Solutions LLC

Page 3

**Soil Listing (all nodes)**

| Area<br>(acres) | Soil<br>Group | Subcatchment<br>Numbers |
|-----------------|---------------|-------------------------|
| 0.000           | HSG A         |                         |
| 0.000           | HSG B         |                         |
| 0.000           | HSG C         |                         |
| 1.263           | HSG D         | A, OS                   |
| 0.000           | Other         |                         |
| <b>1.263</b>    |               | <b>TOTAL AREA</b>       |



**Predevelopment**

Prepared by Microsoft

Printed 4/6/2018

HydroCAD® 10.00-20 s/n 02918 © 2017 HydroCAD Software Solutions LLC

Page 4

**Ground Covers (all nodes)**

| HSG-A<br>(acres) | HSG-B<br>(acres) | HSG-C<br>(acres) | HSG-D<br>(acres) | Other<br>(acres) | Total<br>(acres) | Ground<br>Cover       | Subcatchment<br>Numbers |
|------------------|------------------|------------------|------------------|------------------|------------------|-----------------------|-------------------------|
| 0.000            | 0.000            | 0.000            | 0.849            | 0.000            | 0.849            | Impervious            | A, OS                   |
| 0.000            | 0.000            | 0.000            | 0.381            | 0.000            | 0.381            | Pervious              | A                       |
| 0.000            | 0.000            | 0.000            | 0.033            | 0.000            | 0.033            | Pervious              | OS                      |
| <b>0.000</b>     | <b>0.000</b>     | <b>0.000</b>     | <b>1.263</b>     | <b>0.000</b>     | <b>1.263</b>     | <b>TOTAL<br/>AREA</b> |                         |

## Predevelopment

Prepared by Microsoft

HydroCAD® 10.00-20 s/n 02918 © 2017 HydroCAD Software Solutions LLC

Pre-Development

MSE 24-hr 3 2-year Rainfall=2.70"

Printed 4/6/2018

Page 5

Time span=5.00-20.00 hrs, dt=0.05 hrs, 301 points  
Runoff by SCS TR-20 method, UH=SCS, Weighted-CN  
Reach routing by Dyn-Stor-Ind method - Pond routing by Dyn-Stor-Ind method

### Link 1L: Pre-Development

Inflow=3.98 cfs 0.184 af  
Primary=3.98 cfs 0.184 af

### Subcatchment A: Pre-Development Site

Runoff Area=49,353 sf 66.36% Impervious Runoff Depth>1.73"  
Tc=6.0 min CN=91 Runoff=3.54 cfs 0.163 af

### Subcatchment OS: Off-site

Runoff Area=5,663 sf 75.00% Impervious Runoff Depth>1.90"  
Tc=6.0 min CN=93 Runoff=0.44 cfs 0.021 af

**Total Runoff Area = 1.263 ac Runoff Volume = 0.184 af Average Runoff Depth = 1.74"**  
**32.75% Pervious = 0.414 ac 67.25% Impervious = 0.849 ac**



# Predevelopment

Prepared by Microsoft

HydroCAD® 10.00-20 s/n 02918 © 2017 HydroCAD Software Solutions LLC

Pre-Development  
MSE 24-hr 3 2-year Rainfall=2.70"

Printed 4/6/2018

Page 6

## Summary for Link 1L: Pre-Development

Inflow Area = 1.263 ac, 67.25% Impervious, Inflow Depth > 1.74" for 2-year event  
 Inflow = 3.98 cfs @ 12.13 hrs, Volume= 0.184 af  
 Primary = 3.98 cfs @ 12.13 hrs, Volume= 0.184 af, Atten= 0%, Lag= 0.0 min

Primary outflow = Inflow, Time Span= 5.00-20.00 hrs, dt= 0.05 hrs

## Summary for Subcatchment A: Pre-Development Site

Runoff = 3.54 cfs @ 12.13 hrs, Volume= 0.163 af, Depth> 1.73"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 5.00-20.00 hrs, dt= 0.05 hrs  
MSE 24-hr 3 2-year Rainfall=2.70"

| Area (sf) | CN | Description            |
|-----------|----|------------------------|
| * 32,752  | 98 | Impervious, HSG D      |
| * 16,601  | 78 | Pervious, HSG D        |
| 49,353    | 91 | Weighted Average       |
| 16,601    |    | 33.64% Pervious Area   |
| 32,752    |    | 66.36% Impervious Area |

| Tc (min) | Length (feet) | Slope (ft/ft) | Velocity (ft/sec) | Capacity (cfs) | Description              |
|----------|---------------|---------------|-------------------|----------------|--------------------------|
| 6.0      |               |               |                   |                | Direct Entry, Minimum TC |

## Summary for Subcatchment OS: Off-site

Runoff = 0.44 cfs @ 12.13 hrs, Volume= 0.021 af, Depth> 1.90"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 5.00-20.00 hrs, dt= 0.05 hrs  
MSE 24-hr 3 2-year Rainfall=2.70"

| Area (sf) | CN | Description            |
|-----------|----|------------------------|
| * 4,247   | 98 | Impervious, HSG D      |
| * 1,416   | 78 | Pervious, HSG D        |
| 5,663     | 93 | Weighted Average       |
| 1,416     |    | 25.00% Pervious Area   |
| 4,247     |    | 75.00% Impervious Area |

| Tc (min) | Length (feet) | Slope (ft/ft) | Velocity (ft/sec) | Capacity (cfs) | Description              |
|----------|---------------|---------------|-------------------|----------------|--------------------------|
| 6.0      |               |               |                   |                | Direct Entry, Minimum TC |

## Predevelopment

Prepared by Microsoft

HydroCAD® 10.00-20 s/n 02918 © 2017 HydroCAD Software Solutions LLC

Pre-Development

MSE 24-hr 3 10-year Rainfall=3.81"

Printed 4/6/2018

Page 7

Time span=5.00-20.00 hrs, dt=0.05 hrs, 301 points  
Runoff by SCS TR-20 method, UH=SCS, Weighted-CN  
Reach routing by Dyn-Stor-Ind method - Pond routing by Dyn-Stor-Ind method

### Link 1L: Pre-Development

Inflow=6.11 cfs 0.290 af  
Primary=6.11 cfs 0.290 af

### Subcatchment A: Pre-Development Site

Runoff Area=49,353 sf 66.36% Impervious Runoff Depth>2.74"  
Tc=6.0 min CN=91 Runoff=5.45 cfs 0.259 af

### Subcatchment OS: Off-site

Runoff Area=5,663 sf 75.00% Impervious Runoff Depth>2.94"  
Tc=6.0 min CN=93 Runoff=0.66 cfs 0.032 af

**Total Runoff Area = 1.263 ac Runoff Volume = 0.290 af Average Runoff Depth = 2.76"**  
**32.75% Pervious = 0.414 ac 67.25% Impervious = 0.849 ac**



# Predevelopment

Prepared by Microsoft

HydroCAD® 10.00-20 s/n 02918 © 2017 HydroCAD Software Solutions LLC

Pre-Development

MSE 24-hr 3 10-year Rainfall=3.81"

Printed 4/6/2018

Page 8

## Summary for Link 1L: Pre-Development

Inflow Area = 1.263 ac, 67.25% Impervious, Inflow Depth > 2.76" for 10-year event  
 Inflow = 6.11 cfs @ 12.13 hrs, Volume= 0.290 af  
 Primary = 6.11 cfs @ 12.13 hrs, Volume= 0.290 af, Atten= 0%, Lag= 0.0 min

Primary outflow = Inflow, Time Span= 5.00-20.00 hrs, dt= 0.05 hrs

## Summary for Subcatchment A: Pre-Development Site

Runoff = 5.45 cfs @ 12.13 hrs, Volume= 0.259 af, Depth> 2.74"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 5.00-20.00 hrs, dt= 0.05 hrs  
MSE 24-hr 3 10-year Rainfall=3.81"

|   | Area (sf) | CN | Description            |
|---|-----------|----|------------------------|
| * | 32,752    | 98 | Impervious, HSG D      |
| * | 16,601    | 78 | Pervious, HSG D        |
|   | 49,353    | 91 | Weighted Average       |
|   | 16,601    |    | 33.64% Pervious Area   |
|   | 32,752    |    | 66.36% Impervious Area |

| Tc (min) | Length (feet) | Slope (ft/ft) | Velocity (ft/sec) | Capacity (cfs) | Description              |
|----------|---------------|---------------|-------------------|----------------|--------------------------|
| 6.0      |               |               |                   |                | Direct Entry, Minimum TC |

## Summary for Subcatchment OS: Off-site

Runoff = 0.66 cfs @ 12.13 hrs, Volume= 0.032 af, Depth> 2.94"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 5.00-20.00 hrs, dt= 0.05 hrs  
MSE 24-hr 3 10-year Rainfall=3.81"

|   | Area (sf) | CN | Description            |
|---|-----------|----|------------------------|
| * | 4,247     | 98 | Impervious, HSG D      |
| * | 1,416     | 78 | Pervious, HSG D        |
|   | 5,663     | 93 | Weighted Average       |
|   | 1,416     |    | 25.00% Pervious Area   |
|   | 4,247     |    | 75.00% Impervious Area |

| Tc (min) | Length (feet) | Slope (ft/ft) | Velocity (ft/sec) | Capacity (cfs) | Description              |
|----------|---------------|---------------|-------------------|----------------|--------------------------|
| 6.0      |               |               |                   |                | Direct Entry, Minimum TC |

**Predevelopment**

Prepared by Microsoft

HydroCAD® 10.00-20 s/n 02918 © 2017 HydroCAD Software Solutions LLC

Pre-Development

MSE 24-hr 3 100-year Rainfall=6.18"

Printed 4/6/2018

Page 9

Time span=5.00-20.00 hrs, dt=0.05 hrs, 301 points  
Runoff by SCS TR-20 method, UH=SCS, Weighted-CN  
Reach routing by Dyn-Stor-Ind method - Pond routing by Dyn-Stor-Ind method

**Link 1L: Pre-Development**

Inflow=10.61 cfs 0.526 af  
Primary=10.61 cfs 0.526 af

**Subcatchment A: Pre-Development Site**

Runoff Area=49,353 sf 66.36% Impervious Runoff Depth>4.97"  
Tc=6.0 min CN=91 Runoff=9.50 cfs 0.469 af

**Subcatchment OS: Off-site**

Runoff Area=5,663 sf 75.00% Impervious Runoff Depth>5.19"  
Tc=6.0 min CN=93 Runoff=1.11 cfs 0.056 af

**Total Runoff Area = 1.263 ac Runoff Volume = 0.526 af Average Runoff Depth = 4.99"**  
**32.75% Pervious = 0.414 ac 67.25% Impervious = 0.849 ac**



**Predevelopment**

Prepared by Microsoft

HydroCAD® 10.00-20 s/n 02918 © 2017 HydroCAD Software Solutions LLC

Pre-Development  
MSE 24-hr 3 100-year Rainfall=6.18"

Printed 4/6/2018

Page 10

**Summary for Link 1L: Pre-Development**

Inflow Area = 1.263 ac, 67.25% Impervious, Inflow Depth > 4.99" for 100-year event  
Inflow = 10.61 cfs @ 12.13 hrs, Volume= 0.526 af  
Primary = 10.61 cfs @ 12.13 hrs, Volume= 0.526 af, Atten= 0%, Lag= 0.0 min

Primary outflow = Inflow, Time Span= 5.00-20.00 hrs, dt= 0.05 hrs

**Summary for Subcatchment A: Pre-Development Site**

Runoff = 9.50 cfs @ 12.13 hrs, Volume= 0.469 af, Depth> 4.97"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 5.00-20.00 hrs, dt= 0.05 hrs  
MSE 24-hr 3 100-year Rainfall=6.18"

| Area (sf) | CN | Description            |
|-----------|----|------------------------|
| * 32,752  | 98 | Impervious, HSG D      |
| * 16,601  | 78 | Pervious, HSG D        |
| 49,353    | 91 | Weighted Average       |
| 16,601    |    | 33.64% Pervious Area   |
| 32,752    |    | 66.36% Impervious Area |

| Tc (min) | Length (feet) | Slope (ft/ft) | Velocity (ft/sec) | Capacity (cfs) | Description                     |
|----------|---------------|---------------|-------------------|----------------|---------------------------------|
| 6.0      |               |               |                   |                | <b>Direct Entry, Minimum TC</b> |

**Summary for Subcatchment OS: Off-site**

Runoff = 1.11 cfs @ 12.13 hrs, Volume= 0.056 af, Depth> 5.19"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 5.00-20.00 hrs, dt= 0.05 hrs  
MSE 24-hr 3 100-year Rainfall=6.18"

| Area (sf) | CN | Description            |
|-----------|----|------------------------|
| * 4,247   | 98 | Impervious, HSG D      |
| * 1,416   | 78 | Pervious, HSG D        |
| 5,663     | 93 | Weighted Average       |
| 1,416     |    | 25.00% Pervious Area   |
| 4,247     |    | 75.00% Impervious Area |


| Tc (min) | Length (feet) | Slope (ft/ft) | Velocity (ft/sec) | Capacity (cfs) | Description                     |
|----------|---------------|---------------|-------------------|----------------|---------------------------------|
| 6.0      |               |               |                   |                | <b>Direct Entry, Minimum TC</b> |

**APPENDIX 5**  
**POST-DEVELOPMENT HYDROLOGIC CALCULATIONS**

PROPOSED WATERSHED MAP  
POST-DEVELOPMENT HYDROCAD OUTPUT



File: I:\2018\188469\DWG\188469 SWMP.dwg Layout: EX2.0 User: chuihta Plotted: Apr 06, 2018 - 10:17am Xref's:



**LEGEND (PROPOSED)**

|           |                                       |
|-----------|---------------------------------------|
| ---       | PROPERTY LINE                         |
| - - -     | SETBACK LINE                          |
| - · - · - | EASEMENT LINE                         |
| ---       | BUILDING LINE                         |
| ---       | BUILDING OVERHANG LINE                |
| ---       | EDGE OF CONCRETE                      |
| ---       | STANDARD CURB AND GUTTER              |
| ---       | REJECT CURB AND GUTTER                |
| ▨         | PROPOSED CONCRETE PAVEMENT            |
| ▩         | PROPOSED HEAVY DUTY CONCRETE PAVEMENT |
| ▧         | PROPOSED ASPHALT PAVEMENT             |
| ▦         | PROPOSED HEAVY DUTY ASPHALT PAVEMENT  |
| □         | LIGHT POLE                            |
| ●         | BOLLARD                               |

**WATERSHED CHARACTERISTICS**

|              |                              |  |
|--------------|------------------------------|--|
| WATERSHED C  | 34,499 SF (57.0% IMPERVIOUS) | 6 MINUTE TIME OF CONCENTRATION (MINIMUM) |
| WATERSHED UT | 14,854 SF (57.0% IMPERVIOUS) | 6 MINUTE TIME OF CONCENTRATION (MINIMUM) |
| WATERSHED OS | 5663 SF (25.0% IMPERVIOUS)   | 6 MINUTE TIME OF CONCENTRATION (MINIMUM) |

**EAST MORELAND BOULEVARD  
(USH 18)**



CREATE THE VISION TELL THE STORY

MADISON | MILWAUKEE  
KENOSHA | APPLETON | WAUSAU

**MADISON REGIONAL OFFICE**  
161 HORIZON DRIVE, SUITE 101  
VERONA, WISCONSIN 53593  
P. 608.848.5060

CLIENT:  
**SUMMIT CREDIT UNION**

CLIENT ADDRESS:  
**4800 American Parkway  
MADISON, WI 53718**

PROJECT:  
**SUMMIT CREDIT UNION - WAUKESHA BRANCH**

PROJECT LOCATION:  
**2208 E MORELAND BOULEVARD  
WAUKESHA COUNTY**

**PLAN MODIFICATIONS:**


| #  | Date: | Description: |
|----|-------|--------------|
| 1  |       |              |
| 2  |       |              |
| 3  |       |              |
| 4  |       |              |
| 5  |       |              |
| 6  |       |              |
| 7  |       |              |
| 8  |       |              |
| 9  |       |              |
| 10 |       |              |
| 11 |       |              |
| 12 |       |              |
| 13 |       |              |
| 14 |       |              |
| 15 |       |              |

Design/Drawn: CLH  
Approved: WHD

SHEET TITLE:  
**PROPOSED DRAINAGE AREA MAP**





SHEET NUMBER:  
**EX2.0**

JSD PROJECT NO: 18-8469



THESE PLANS AND DESIGNS ARE COPYRIGHT PROTECTED AND MAY NOT BE USED IN WHOLE OR IN PART WITHOUT THE WRITTEN CONSENT OF JSD PROFESSIONAL SERVICES, INC.





**Routing Diagram for Post-Development**  
 Prepared by Microsoft, Printed 4/6/2018  
 HydroCAD® 10.00-20 s/n 02918 © 2017 HydroCAD Software Solutions LLC

**Post-Development**

Prepared by Microsoft

Printed 4/6/2018

HydroCAD® 10.00-20 s/n 02918 © 2017 HydroCAD Software Solutions LLC

Page 2

**Area Listing (all nodes)**

| Area<br>(acres) | CN        | Description<br>(subcatchment-numbers)  |
|-----------------|-----------|--|
| 1.439           | 98        | Impervious, HSG D (B, C, OS1, OS2, UT) |
| 1.022           | 78        | Pervious, HSG D (B, C, UT)             |
| 0.065           | 78        | Pervious, HSG D (OS1, OS2)             |
| <b>2.526</b>    | <b>89</b> | <b>TOTAL AREA</b>                      |



**Post-Development**

Prepared by Microsoft

HydroCAD® 10.00-20 s/n 02918 © 2017 HydroCAD Software Solutions LLC

Printed 4/6/2018

Page 3

**Soil Listing (all nodes)**

| Area<br>(acres) | Soil<br>Group | Subcatchment<br>Numbers |
|-----------------|---------------|-------------------------|
| 0.000           | HSG A         |                         |
| 0.000           | HSG B         |                         |
| 0.000           | HSG C         |                         |
| 2.526           | HSG D         | B, C, OS1, OS2, UT      |
| 0.000           | Other         |                         |
| <b>2.526</b>    |               | <b>TOTAL AREA</b>       |

**Post-Development**

Prepared by Microsoft

Printed 4/6/2018

HydroCAD® 10.00-20 s/n 02918 © 2017 HydroCAD Software Solutions LLC

Page 4

**Ground Covers (all nodes)**

| HSG-A<br>(acres) | HSG-B<br>(acres) | HSG-C<br>(acres) | HSG-D<br>(acres) | Other<br>(acres) | Total<br>(acres) | Ground<br>Cover       | Subcatchment<br>Numbers |
|------------------|------------------|------------------|------------------|------------------|------------------|-----------------------|-------------------------|
| 0.000            | 0.000            | 0.000            | 1.439            | 0.000            | 1.439            | Impervious            | B, C, OS1, OS2, UT      |
| 0.000            | 0.000            | 0.000            | 1.022            | 0.000            | 1.022            | Pervious              | B, C, UT                |
| 0.000            | 0.000            | 0.000            | 0.065            | 0.000            | 0.065            | Pervious              | OS1, OS2                |
| <b>0.000</b>     | <b>0.000</b>     | <b>0.000</b>     | <b>2.526</b>     | <b>0.000</b>     | <b>2.526</b>     | <b>TOTAL<br/>AREA</b> |                         |

**Post-Development**

Prepared by Microsoft

HydroCAD® 10.00-20 s/n 02918 © 2017 HydroCAD Software Solutions LLC

Post-Development

MSE 24-hr 3 2-year Rainfall=2.70"

Printed 4/6/2018

Page 5

Time span=5.00-20.00 hrs, dt=0.05 hrs, 301 points  
Runoff by SCS TR-20 method, UH=SCS, Weighted-CN  
Reach routing by Dyn-Stor-Ind method - Pond routing by Dyn-Stor-Ind method

**Link 2L: Uncontrolled**

Inflow=3.84 cfs 0.176 af  
Primary=3.84 cfs 0.176 af

**Link 3L: Post-Development**

Inflow=3.16 cfs 0.154 af  
Primary=3.16 cfs 0.154 af

**Pond 6P: WQ Chamber**

Peak Elev=927.42' Storage=0.031 af Inflow=2.72 cfs 0.124 af  
12.0" Round Culvert n=0.011 L=8.0' S=0.0100 '/' Outflow=2.45 cfs 0.121 af

**Subcatchment B: UnControlled Site**

Runoff Area=49,353 sf 62.45% Impervious Runoff Depth>1.65"  
Tc=6.0 min CN=90 Runoff=3.40 cfs 0.155 af

**Subcatchment C: Untreated Site**

Runoff Area=34,499 sf 57.01% Impervious Runoff Depth>1.57"  
Tc=6.0 min CN=89 Runoff=2.28 cfs 0.103 af

**Subcatchment OS1: Off-site**

Runoff Area=5,663 sf 75.00% Impervious Runoff Depth>1.90"  
Tc=6.0 min CN=93 Runoff=0.44 cfs 0.021 af

**Subcatchment OS2: Off-site**

Runoff Area=5,663 sf 75.00% Impervious Runoff Depth>1.90"  
Tc=6.0 min CN=93 Runoff=0.44 cfs 0.021 af

**Subcatchment UT: Untreated Site Bypass**

Runoff Area=0.341 ac 24.93% Impervious Runoff Depth>1.15"  
Tc=6.0 min CN=83 Runoff=0.74 cfs 0.033 af

**Total Runoff Area = 2.526 ac Runoff Volume = 0.333 af Average Runoff Depth = 1.58"**  
**43.03% Pervious = 1.087 ac 56.97% Impervious = 1.439 ac**



## Post-Development

Prepared by Microsoft

HydroCAD® 10.00-20 s/n 02918 © 2017 HydroCAD Software Solutions LLC

Post-Development

MSE 24-hr 3 2-year Rainfall=2.70"

Printed 4/6/2018

Page 6

### Summary for Link 2L: Uncontrolled

Inflow Area = 1.263 ac, 63.74% Impervious, Inflow Depth > 1.67" for 2-year event  
Inflow = 3.84 cfs @ 12.13 hrs, Volume= 0.176 af  
Primary = 3.84 cfs @ 12.13 hrs, Volume= 0.176 af, Atten= 0%, Lag= 0.0 min

Primary outflow = Inflow, Time Span= 5.00-20.00 hrs, dt= 0.05 hrs

### Summary for Link 3L: Post-Development

Inflow Area = 1.263 ac, 50.20% Impervious, Inflow Depth > 1.46" for 2-year event  
Inflow = 3.16 cfs @ 12.15 hrs, Volume= 0.154 af  
Primary = 3.16 cfs @ 12.15 hrs, Volume= 0.154 af, Atten= 0%, Lag= 0.0 min

Primary outflow = Inflow, Time Span= 5.00-20.00 hrs, dt= 0.05 hrs

### Summary for Pond 6P: WQ Chamber

Inflow Area = 0.922 ac, 59.55% Impervious, Inflow Depth > 1.61" for 2-year event  
Inflow = 2.72 cfs @ 12.13 hrs, Volume= 0.124 af  
Outflow = 2.45 cfs @ 12.16 hrs, Volume= 0.121 af, Atten= 10%, Lag= 1.9 min  
Primary = 2.45 cfs @ 12.16 hrs, Volume= 0.121 af

Routing by Dyn-Stor-Ind method, Time Span= 5.00-20.00 hrs, dt= 0.05 hrs

Starting Elev= 926.00' Surf.Area= 0.009 ac Storage= 0.019 af

Peak Elev= 927.42' @ 12.16 hrs Surf.Area= 0.008 ac Storage= 0.031 af (0.012 af above start)

Plug-Flow detention time= 66.7 min calculated for 0.102 af (82% of inflow)

Center-of-Mass det. time= 8.2 min ( 782.6 - 774.4 )

| Volume | Invert  | Avail.Storage | Storage Description                         |
|--------|---------|---------------|---|
| #1     | 923.25' | 0.042 af      | <b>72.0" Round Pipe Storage</b><br>L= 65.0' |

| Device | Routing | Invert  | Outlet Devices  |
|--------|---------|---------|---|
| #1     | Primary | 926.25' | <b>12.0" Round Culvert</b><br>L= 8.0' CPP, projecting, no headwall, Ke= 0.900<br>Inlet / Outlet Invert= 926.25' / 926.17' S= 0.0100 '/' Cc= 0.900<br>n= 0.011, Flow Area= 0.79 sf |

**Primary OutFlow** Max=2.39 cfs @ 12.16 hrs HW=927.39' TW=0.00' (Dynamic Tailwater)

←1=Culvert (Inlet Controls 2.39 cfs @ 3.05 fps)

### Summary for Subcatchment B: UnControlled Site

Runoff = 3.40 cfs @ 12.13 hrs, Volume= 0.155 af, Depth> 1.65"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 5.00-20.00 hrs, dt= 0.05 hrs  
MSE 24-hr 3 2-year Rainfall=2.70"

**Post-Development**

Prepared by Microsoft

HydroCAD® 10.00-20 s/n 02918 © 2017 HydroCAD Software Solutions LLC

Post-Development

MSE 24-hr 3 2-year Rainfall=2.70"

Printed 4/6/2018

Page 7

|   | Area (sf) | CN | Description            |
|---|-----------|----|------------------------|
| * | 30,820    | 98 | Impervious, HSG D      |
| * | 18,533    | 78 | Pervious, HSG D        |
|   | 49,353    | 90 | Weighted Average       |
|   | 18,533    |    | 37.55% Pervious Area   |
|   | 30,820    |    | 62.45% Impervious Area |

| Tc (min) | Length (feet) | Slope (ft/ft) | Velocity (ft/sec) | Capacity (cfs) | Description                     |
|----------|---------------|---------------|-------------------|----------------|---------------------------------|
| 6.0      |               |               |                   |                | <b>Direct Entry, Minimum TC</b> |

**Summary for Subcatchment C: Untreated Site**

Runoff = 2.28 cfs @ 12.13 hrs, Volume= 0.103 af, Depth&gt; 1.57"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 5.00-20.00 hrs, dt= 0.05 hrs  
MSE 24-hr 3 2-year Rainfall=2.70"

|   | Area (sf) | CN | Description            |
|---|-----------|----|------------------------|
| * | 19,669    | 98 | Impervious, HSG D      |
| * | 14,830    | 78 | Pervious, HSG D        |
|   | 34,499    | 89 | Weighted Average       |
|   | 14,830    |    | 42.99% Pervious Area   |
|   | 19,669    |    | 57.01% Impervious Area |

| Tc (min) | Length (feet) | Slope (ft/ft) | Velocity (ft/sec) | Capacity (cfs) | Description                     |
|----------|---------------|---------------|-------------------|----------------|---------------------------------|
| 6.0      |               |               |                   |                | <b>Direct Entry, Minimum TC</b> |

**Summary for Subcatchment OS1: Off-site**

Runoff = 0.44 cfs @ 12.13 hrs, Volume= 0.021 af, Depth&gt; 1.90"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 5.00-20.00 hrs, dt= 0.05 hrs  
MSE 24-hr 3 2-year Rainfall=2.70"

|   | Area (sf) | CN | Description            |
|---|-----------|----|------------------------|
| * | 4,247     | 98 | Impervious, HSG D      |
| * | 1,416     | 78 | Pervious, HSG D        |
|   | 5,663     | 93 | Weighted Average       |
|   | 1,416     |    | 25.00% Pervious Area   |
|   | 4,247     |    | 75.00% Impervious Area |

| Tc (min) | Length (feet) | Slope (ft/ft) | Velocity (ft/sec) | Capacity (cfs) | Description                     |
|----------|---------------|---------------|-------------------|----------------|---------------------------------|
| 6.0      |               |               |                   |                | <b>Direct Entry, Minimum TC</b> |

## Post-Development

Prepared by Microsoft

HydroCAD® 10.00-20 s/n 02918 © 2017 HydroCAD Software Solutions LLC

Post-Development

MSE 24-hr 3 2-year Rainfall=2.70"

Printed 4/6/2018

Page 8

### Summary for Subcatchment OS2: Off-site

Runoff = 0.44 cfs @ 12.13 hrs, Volume= 0.021 af, Depth> 1.90"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 5.00-20.00 hrs, dt= 0.05 hrs  
MSE 24-hr 3 2-year Rainfall=2.70"

|   | Area (sf) | CN | Description            |
|---|-----------|----|------------------------|
| * | 4,247     | 98 | Impervious, HSG D      |
| * | 1,416     | 78 | Pervsious, HSG D       |
|   | 5,663     | 93 | Weighted Average       |
|   | 1,416     |    | 25.00% Pervious Area   |
|   | 4,247     |    | 75.00% Impervious Area |

| Tc (min) | Length (feet) | Slope (ft/ft) | Velocity (ft/sec) | Capacity (cfs) | Description              |
|----------|---------------|---------------|-------------------|----------------|--------------------------|
| 6.0      |               |               |                   |                | Direct Entry, Minimum TC |

### Summary for Subcatchment UT: Untreated Site Bypass

Runoff = 0.74 cfs @ 12.14 hrs, Volume= 0.033 af, Depth> 1.15"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 5.00-20.00 hrs, dt= 0.05 hrs  
MSE 24-hr 3 2-year Rainfall=2.70"

|   | Area (ac) | CN | Description            |
|---|-----------|----|------------------------|
| * | 0.256     | 78 | Pervious, HSG D        |
| * | 0.085     | 98 | Impervious, HSG D      |
|   | 0.341     | 83 | Weighted Average       |
|   | 0.256     |    | 75.07% Pervious Area   |
|   | 0.085     |    | 24.93% Impervious Area |

| Tc (min) | Length (feet) | Slope (ft/ft) | Velocity (ft/sec) | Capacity (cfs) | Description              |
|----------|---------------|---------------|-------------------|----------------|--------------------------|
| 6.0      |               |               |                   |                | Direct Entry, Minimum TC |



**Post-Development**

Prepared by Microsoft

HydroCAD® 10.00-20 s/n 02918 © 2017 HydroCAD Software Solutions LLC

Post-Development

MSE 24-hr 3 10-year Rainfall=3.81"

Printed 4/6/2018

Page 9

Time span=5.00-20.00 hrs, dt=0.05 hrs, 301 points  
Runoff by SCS TR-20 method, UH=SCS, Weighted-CN  
Reach routing by Dyn-Stor-Ind method - Pond routing by Dyn-Stor-Ind method

**Link 2L: Uncontrolled**

Inflow=5.97 cfs 0.281 af  
Primary=5.97 cfs 0.281 af

**Link 3L: Post-Development**

Inflow=4.83 cfs 0.255 af  
Primary=4.83 cfs 0.255 af

**Pond 6P: WQ Chamber**

Peak Elev=928.21' Storage=0.037 af Inflow=4.27 cfs 0.200 af  
12.0" Round Culvert n=0.011 L=8.0' S=0.0100 '/' Outflow=3.62 cfs 0.197 af

**Subcatchment B: UnControlled Site**

Runoff Area=49,353 sf 62.45% Impervious Runoff Depth>2.64"  
Tc=6.0 min CN=90 Runoff=5.32 cfs 0.250 af

**Subcatchment C: Untreated Site**

Runoff Area=34,499 sf 57.01% Impervious Runoff Depth>2.55"  
Tc=6.0 min CN=89 Runoff=3.62 cfs 0.168 af

**Subcatchment OS1: Off-site**

Runoff Area=5,663 sf 75.00% Impervious Runoff Depth>2.94"  
Tc=6.0 min CN=93 Runoff=0.66 cfs 0.032 af

**Subcatchment OS2: Off-site**

Runoff Area=5,663 sf 75.00% Impervious Runoff Depth>2.94"  
Tc=6.0 min CN=93 Runoff=0.66 cfs 0.032 af

**Subcatchment UT: Untreated Site Bypass**

Runoff Area=0.341 ac 24.93% Impervious Runoff Depth>2.03"  
Tc=6.0 min CN=83 Runoff=1.29 cfs 0.058 af

**Total Runoff Area = 2.526 ac Runoff Volume = 0.539 af Average Runoff Depth = 2.56"**  
**43.03% Pervious = 1.087 ac 56.97% Impervious = 1.439 ac**

## Post-Development

Prepared by Microsoft

HydroCAD® 10.00-20 s/n 02918 © 2017 HydroCAD Software Solutions LLC

Post-Development

MSE 24-hr 3 10-year Rainfall=3.81"

Printed 4/6/2018

Page 10

### Summary for Link 2L: Uncontrolled

Inflow Area = 1.263 ac, 63.74% Impervious, Inflow Depth > 2.67" for 10-year event  
Inflow = 5.97 cfs @ 12.13 hrs, Volume= 0.281 af  
Primary = 5.97 cfs @ 12.13 hrs, Volume= 0.281 af, Atten= 0%, Lag= 0.0 min

Primary outflow = Inflow, Time Span= 5.00-20.00 hrs, dt= 0.05 hrs

### Summary for Link 3L: Post-Development

Inflow Area = 1.263 ac, 50.20% Impervious, Inflow Depth > 2.42" for 10-year event  
Inflow = 4.83 cfs @ 12.15 hrs, Volume= 0.255 af  
Primary = 4.83 cfs @ 12.15 hrs, Volume= 0.255 af, Atten= 0%, Lag= 0.0 min

Primary outflow = Inflow, Time Span= 5.00-20.00 hrs, dt= 0.05 hrs

### Summary for Pond 6P: WQ Chamber

Inflow Area = 0.922 ac, 59.55% Impervious, Inflow Depth > 2.60" for 10-year event  
Inflow = 4.27 cfs @ 12.13 hrs, Volume= 0.200 af  
Outflow = 3.62 cfs @ 12.17 hrs, Volume= 0.197 af, Atten= 15%, Lag= 2.4 min  
Primary = 3.62 cfs @ 12.17 hrs, Volume= 0.197 af

Routing by Dyn-Stor-Ind method, Time Span= 5.00-20.00 hrs, dt= 0.05 hrs

Starting Elev= 926.00' Surf.Area= 0.009 ac Storage= 0.019 af

Peak Elev= 928.21' @ 12.17 hrs Surf.Area= 0.007 ac Storage= 0.037 af (0.018 af above start)

Plug-Flow detention time= 51.8 min calculated for 0.178 af (89% of inflow)

Center-of-Mass det. time= 7.3 min ( 773.7 - 766.4 )

| Volume | Invert  | Avail.Storage | Storage Description                         |
|--------|---------|---------------|---|
| #1     | 923.25' | 0.042 af      | <b>72.0" Round Pipe Storage</b><br>L= 65.0' |

| Device | Routing | Invert  | Outlet Devices  |
|--------|---------|---------|---|
| #1     | Primary | 926.25' | <b>12.0" Round Culvert</b><br>L= 8.0' CPP, projecting, no headwall, Ke= 0.900<br>Inlet / Outlet Invert= 926.25' / 926.17' S= 0.0100 '/' Cc= 0.900<br>n= 0.011, Flow Area= 0.79 sf |

**Primary OutFlow** Max=3.54 cfs @ 12.17 hrs HW=928.15' TW=0.00' (Dynamic Tailwater)

↑1=Culvert (Inlet Controls 3.54 cfs @ 4.50 fps)

### Summary for Subcatchment B: UnControlled Site

Runoff = 5.32 cfs @ 12.13 hrs, Volume= 0.250 af, Depth> 2.64"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 5.00-20.00 hrs, dt= 0.05 hrs  
MSE 24-hr 3 10-year Rainfall=3.81"

**Post-Development**

Prepared by Microsoft

HydroCAD® 10.00-20 s/n 02918 © 2017 HydroCAD Software Solutions LLC

Post-Development

MSE 24-hr 3 10-year Rainfall=3.81"

Printed 4/6/2018

Page 11

|   | Area (sf) | CN | Description            |
|---|-----------|----|------------------------|
| * | 30,820    | 98 | Impervious, HSG D      |
| * | 18,533    | 78 | Pervious, HSG D        |
|   | 49,353    | 90 | Weighted Average       |
|   | 18,533    |    | 37.55% Pervious Area   |
|   | 30,820    |    | 62.45% Impervious Area |

| Tc (min) | Length (feet) | Slope (ft/ft) | Velocity (ft/sec) | Capacity (cfs) | Description                     |
|----------|---------------|---------------|-------------------|----------------|---------------------------------|
| 6.0      |               |               |                   |                | <b>Direct Entry, Minimum TC</b> |

**Summary for Subcatchment C: Untreated Site**

Runoff = 3.62 cfs @ 12.13 hrs, Volume= 0.168 af, Depth&gt; 2.55"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 5.00-20.00 hrs, dt= 0.05 hrs  
MSE 24-hr 3 10-year Rainfall=3.81"

|   | Area (sf) | CN | Description            |
|---|-----------|----|------------------------|
| * | 19,669    | 98 | Impervious, HSG D      |
| * | 14,830    | 78 | Pervious, HSG D        |
|   | 34,499    | 89 | Weighted Average       |
|   | 14,830    |    | 42.99% Pervious Area   |
|   | 19,669    |    | 57.01% Impervious Area |

| Tc (min) | Length (feet) | Slope (ft/ft) | Velocity (ft/sec) | Capacity (cfs) | Description                     |
|----------|---------------|---------------|-------------------|----------------|---------------------------------|
| 6.0      |               |               |                   |                | <b>Direct Entry, Minimum TC</b> |

**Summary for Subcatchment OS1: Off-site**

Runoff = 0.66 cfs @ 12.13 hrs, Volume= 0.032 af, Depth&gt; 2.94"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 5.00-20.00 hrs, dt= 0.05 hrs  
MSE 24-hr 3 10-year Rainfall=3.81"

|   | Area (sf) | CN | Description            |
|---|-----------|----|------------------------|
| * | 4,247     | 98 | Impervious, HSG D      |
| * | 1,416     | 78 | Pervious, HSG D        |
|   | 5,663     | 93 | Weighted Average       |
|   | 1,416     |    | 25.00% Pervious Area   |
|   | 4,247     |    | 75.00% Impervious Area |

| Tc (min) | Length (feet) | Slope (ft/ft) | Velocity (ft/sec) | Capacity (cfs) | Description                     |
|----------|---------------|---------------|-------------------|----------------|---------------------------------|
| 6.0      |               |               |                   |                | <b>Direct Entry, Minimum TC</b> |



**Post-Development**

Prepared by Microsoft

HydroCAD® 10.00-20 s/n 02918 © 2017 HydroCAD Software Solutions LLC

Post-Development

MSE 24-hr 3 10-year Rainfall=3.81"

Printed 4/6/2018

Page 12

**Summary for Subcatchment OS2: Off-site**

Runoff = 0.66 cfs @ 12.13 hrs, Volume= 0.032 af, Depth> 2.94"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 5.00-20.00 hrs, dt= 0.05 hrs  
MSE 24-hr 3 10-year Rainfall=3.81"

|   | Area (sf) | CN | Description            |
|---|-----------|----|------------------------|
| * | 4,247     | 98 | Impervious, HSG D      |
| * | 1,416     | 78 | Pervsious, HSG D       |
|   | 5,663     | 93 | Weighted Average       |
|   | 1,416     |    | 25.00% Pervious Area   |
|   | 4,247     |    | 75.00% Impervious Area |

| Tc (min) | Length (feet) | Slope (ft/ft) | Velocity (ft/sec) | Capacity (cfs) | Description                     |
|----------|---------------|---------------|-------------------|----------------|---------------------------------|
| 6.0      |               |               |                   |                | <b>Direct Entry, Minimum TC</b> |

**Summary for Subcatchment UT: Untreated Site Bypass**

Runoff = 1.29 cfs @ 12.13 hrs, Volume= 0.058 af, Depth> 2.03"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 5.00-20.00 hrs, dt= 0.05 hrs  
MSE 24-hr 3 10-year Rainfall=3.81"

|   | Area (ac) | CN | Description            |
|---|-----------|----|------------------------|
| * | 0.256     | 78 | Pervious, HSG D        |
| * | 0.085     | 98 | Impervious, HSG D      |
|   | 0.341     | 83 | Weighted Average       |
|   | 0.256     |    | 75.07% Pervious Area   |
|   | 0.085     |    | 24.93% Impervious Area |

| Tc (min) | Length (feet) | Slope (ft/ft) | Velocity (ft/sec) | Capacity (cfs) | Description                     |
|----------|---------------|---------------|-------------------|----------------|---------------------------------|
| 6.0      |               |               |                   |                | <b>Direct Entry, Minimum TC</b> |

**Post-Development**

Prepared by Microsoft

HydroCAD® 10.00-20 s/n 02918 © 2017 HydroCAD Software Solutions LLC

Post-Development

MSE 24-hr 3 100-year Rainfall=6.18"

Printed 4/6/2018

Page 13

Time span=5.00-20.00 hrs, dt=0.05 hrs, 301 points  
Runoff by SCS TR-20 method, UH=SCS, Weighted-CN  
Reach routing by Dyn-Stor-Ind method - Pond routing by Dyn-Stor-Ind method

**Link 2L: Uncontrolled**

Inflow=10.49 cfs 0.515 af  
Primary=10.49 cfs 0.515 af

**Link 3L: Post-Development**

Inflow=10.71 cfs 0.483 af  
Primary=10.71 cfs 0.483 af

**Pond 6P: WQ Chamber**

Peak Elev=934.26' Storage=0.042 af Inflow=7.58 cfs 0.370 af  
12.0" Round Culvert n=0.011 L=8.0' S=0.0100 '/' Outflow=8.22 cfs 0.366 af

**Subcatchment B: UnControlled Site**

Runoff Area=49,353 sf 62.45% Impervious Runoff Depth>4.86"  
Tc=6.0 min CN=90 Runoff=9.38 cfs 0.459 af

**Subcatchment C: Untreated Site**

Runoff Area=34,499 sf 57.01% Impervious Runoff Depth>4.75"  
Tc=6.0 min CN=89 Runoff=6.46 cfs 0.313 af

**Subcatchment OS1: Off-site**

Runoff Area=5,663 sf 75.00% Impervious Runoff Depth>5.19"  
Tc=6.0 min CN=93 Runoff=1.11 cfs 0.056 af

**Subcatchment OS2: Off-site**

Runoff Area=5,663 sf 75.00% Impervious Runoff Depth>5.19"  
Tc=6.0 min CN=93 Runoff=1.11 cfs 0.056 af

**Subcatchment UT: Untreated Site Bypass**

Runoff Area=0.341 ac 24.93% Impervious Runoff Depth>4.10"  
Tc=6.0 min CN=83 Runoff=2.51 cfs 0.117 af

**Total Runoff Area = 2.526 ac Runoff Volume = 1.001 af Average Runoff Depth = 4.76"**  
**43.03% Pervious = 1.087 ac 56.97% Impervious = 1.439 ac**

## Post-Development

Prepared by Microsoft

HydroCAD® 10.00-20 s/n 02918 © 2017 HydroCAD Software Solutions LLC

Post-Development

MSE 24-hr 3 100-year Rainfall=6.18"

Printed 4/6/2018

Page 14

### Summary for Link 2L: Uncontrolled

Inflow Area = 1.263 ac, 63.74% Impervious, Inflow Depth > 4.89" for 100-year event  
Inflow = 10.49 cfs @ 12.13 hrs, Volume= 0.515 af  
Primary = 10.49 cfs @ 12.13 hrs, Volume= 0.515 af, Atten= 0%, Lag= 0.0 min

Primary outflow = Inflow, Time Span= 5.00-20.00 hrs, dt= 0.05 hrs

### Summary for Link 3L: Post-Development

Inflow Area = 1.263 ac, 50.20% Impervious, Inflow Depth > 4.59" for 100-year event  
Inflow = 10.71 cfs @ 12.14 hrs, Volume= 0.483 af  
Primary = 10.71 cfs @ 12.14 hrs, Volume= 0.483 af, Atten= 0%, Lag= 0.0 min

Primary outflow = Inflow, Time Span= 5.00-20.00 hrs, dt= 0.05 hrs

### Summary for Pond 6P: WQ Chamber

Inflow Area = 0.922 ac, 59.55% Impervious, Inflow Depth > 4.81" for 100-year event  
Inflow = 7.58 cfs @ 12.13 hrs, Volume= 0.370 af  
Outflow = 8.22 cfs @ 12.14 hrs, Volume= 0.366 af, Atten= 0%, Lag= 0.8 min  
Primary = 8.22 cfs @ 12.14 hrs, Volume= 0.366 af

Routing by Dyn-Stor-Ind method, Time Span= 5.00-20.00 hrs, dt= 0.05 hrs

Starting Elev= 926.00' Surf.Area= 0.009 ac Storage= 0.019 af

Peak Elev= 934.26' @ 12.14 hrs Surf.Area= 0.000 ac Storage= 0.042 af (0.023 af above start)

Plug-Flow detention time= 37.7 min calculated for 0.347 af (94% of inflow)

Center-of-Mass det. time= 6.0 min ( 761.9 - 755.8 )

| Volume | Invert  | Avail.Storage | Storage Description                         |
|--------|---------|---------------|---|
| #1     | 923.25' | 0.042 af      | <b>72.0" Round Pipe Storage</b><br>L= 65.0' |

| Device | Routing | Invert  | Outlet Devices  |
|--------|---------|---------|---|
| #1     | Primary | 926.25' | <b>12.0" Round Culvert</b><br>L= 8.0' CPP, projecting, no headwall, Ke= 0.900<br>Inlet / Outlet Invert= 926.25' / 926.17' S= 0.0100 '/' Cc= 0.900<br>n= 0.011, Flow Area= 0.79 sf |

**Primary OutFlow** Max=7.85 cfs @ 12.14 hrs HW=933.67' TW=0.00' (Dynamic Tailwater)

↑1=Culvert (Inlet Controls 7.85 cfs @ 10.00 fps)

### Summary for Subcatchment B: UnControlled Site

Runoff = 9.38 cfs @ 12.13 hrs, Volume= 0.459 af, Depth> 4.86"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 5.00-20.00 hrs, dt= 0.05 hrs  
MSE 24-hr 3 100-year Rainfall=6.18"

**Post-Development**

Prepared by Microsoft

HydroCAD® 10.00-20 s/n 02918 © 2017 HydroCAD Software Solutions LLC

Post-Development

MSE 24-hr 3 100-year Rainfall=6.18"

Printed 4/6/2018

Page 15

|   | Area (sf) | CN | Description            |
|---|-----------|----|------------------------|
| * | 30,820    | 98 | Impervious, HSG D      |
| * | 18,533    | 78 | Pervious, HSG D        |
|   | 49,353    | 90 | Weighted Average       |
|   | 18,533    |    | 37.55% Pervious Area   |
|   | 30,820    |    | 62.45% Impervious Area |

| Tc (min) | Length (feet) | Slope (ft/ft) | Velocity (ft/sec) | Capacity (cfs) | Description                     |
|----------|---------------|---------------|-------------------|----------------|---------------------------------|
| 6.0      |               |               |                   |                | <b>Direct Entry, Minimum TC</b> |

**Summary for Subcatchment C: Untreated Site**

Runoff = 6.46 cfs @ 12.13 hrs, Volume= 0.313 af, Depth&gt; 4.75"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 5.00-20.00 hrs, dt= 0.05 hrs  
MSE 24-hr 3 100-year Rainfall=6.18"

|   | Area (sf) | CN | Description            |
|---|-----------|----|------------------------|
| * | 19,669    | 98 | Impervious, HSG D      |
| * | 14,830    | 78 | Pervious, HSG D        |
|   | 34,499    | 89 | Weighted Average       |
|   | 14,830    |    | 42.99% Pervious Area   |
|   | 19,669    |    | 57.01% Impervious Area |

| Tc (min) | Length (feet) | Slope (ft/ft) | Velocity (ft/sec) | Capacity (cfs) | Description                     |
|----------|---------------|---------------|-------------------|----------------|---------------------------------|
| 6.0      |               |               |                   |                | <b>Direct Entry, Minimum TC</b> |

**Summary for Subcatchment OS1: Off-site**

Runoff = 1.11 cfs @ 12.13 hrs, Volume= 0.056 af, Depth&gt; 5.19"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 5.00-20.00 hrs, dt= 0.05 hrs  
MSE 24-hr 3 100-year Rainfall=6.18"

|   | Area (sf) | CN | Description            |
|---|-----------|----|------------------------|
| * | 4,247     | 98 | Impervious, HSG D      |
| * | 1,416     | 78 | Pervious, HSG D        |
|   | 5,663     | 93 | Weighted Average       |
|   | 1,416     |    | 25.00% Pervious Area   |
|   | 4,247     |    | 75.00% Impervious Area |

| Tc (min) | Length (feet) | Slope (ft/ft) | Velocity (ft/sec) | Capacity (cfs) | Description                     |
|----------|---------------|---------------|-------------------|----------------|---------------------------------|
| 6.0      |               |               |                   |                | <b>Direct Entry, Minimum TC</b> |



**Post-Development**

Prepared by Microsoft

HydroCAD® 10.00-20 s/n 02918 © 2017 HydroCAD Software Solutions LLC

Post-Development

MSE 24-hr 3 100-year Rainfall=6.18"

Printed 4/6/2018

Page 16

**Summary for Subcatchment OS2: Off-site**

Runoff = 1.11 cfs @ 12.13 hrs, Volume= 0.056 af, Depth> 5.19"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 5.00-20.00 hrs, dt= 0.05 hrs  
MSE 24-hr 3 100-year Rainfall=6.18"

|   | Area (sf) | CN | Description            |
|---|-----------|----|------------------------|
| * | 4,247     | 98 | Impervious, HSG D      |
| * | 1,416     | 78 | Pervsious, HSG D       |
|   | 5,663     | 93 | Weighted Average       |
|   | 1,416     |    | 25.00% Pervious Area   |
|   | 4,247     |    | 75.00% Impervious Area |

| Tc (min) | Length (feet) | Slope (ft/ft) | Velocity (ft/sec) | Capacity (cfs) | Description                     |
|----------|---------------|---------------|-------------------|----------------|---------------------------------|
| 6.0      |               |               |                   |                | <b>Direct Entry, Minimum TC</b> |

**Summary for Subcatchment UT: Untreated Site Bypass**

Runoff = 2.51 cfs @ 12.13 hrs, Volume= 0.117 af, Depth> 4.10"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 5.00-20.00 hrs, dt= 0.05 hrs  
MSE 24-hr 3 100-year Rainfall=6.18"

|   | Area (ac) | CN | Description            |
|---|-----------|----|------------------------|
| * | 0.256     | 78 | Pervious, HSG D        |
| * | 0.085     | 98 | Impervious, HSG D      |
|   | 0.341     | 83 | Weighted Average       |
|   | 0.256     |    | 75.07% Pervious Area   |
|   | 0.085     |    | 24.93% Impervious Area |

| Tc (min) | Length (feet) | Slope (ft/ft) | Velocity (ft/sec) | Capacity (cfs) | Description                     |
|----------|---------------|---------------|-------------------|----------------|---------------------------------|
| 6.0      |               |               |                   |                | <b>Direct Entry, Minimum TC</b> |


# **APPENDIX 6**

## **SEDIMENT CALCULATIONS**

WINSLAMM DIAGRAM

WINSLAMM INPUT

WINSLAMM OUTPUT



TSS Calculations - InputData.txt

Data file name: I:\2018\188469\Civil\SWMP\Modeling\Slamm\TSS Calculations.mdb  
WinSLAMM Version 10.3.4  
Rain file name: C:\WinSLAMM Files\Rain Files\wisReg - Madison WI 1981.RAN  
Particulate Solids Concentration file name: C:\winSLAMM Files\v10.1 WI\_AVG01.pscx  
Runoff Coefficient file name: C:\winSLAMM Files\WI\_SL06 Dec06.rsvx  
Residential Street Delivery file name: C:\winSLAMM Files\WI\_Res and Other Urban Dec06.std  
Institutional Street Delivery file name: C:\winSLAMM Files\WI\_Com Inst Indust Dec06.std  
Commercial Street Delivery file name: C:\winSLAMM Files\WI\_Com Inst Indust Dec06.std  
Industrial Street Delivery file name: C:\winSLAMM Files\WI\_Com Inst Indust Dec06.std  
Other Urban Street Delivery file name: C:\winSLAMM Files\WI\_Res and Other Urban Dec06.std  
Freeway Street Delivery file name: C:\winSLAMM Files\Freeway Dec06.std  
Apply Street Delivery Files to Adjust the After Event Load Street Dirt Mass Balance: False  
Pollutant Relative Concentration file name: C:\winSLAMM Files\WI\_GEO03.ppd  
Source Area PSD and Peak to Average Flow Ratio File: C:\winSLAMM Files\NURP Source Area PSD Files.csv  
Cost Data file name:  
Seed for random number generator: -42  
Study period starting date: 01/01/81 Study period ending date: 12/31/81  
Start of Winter Season: 12/02 End of Winter Season: 03/12  
Date: 04-06-2018 Time: 10:44:20  
Site information:

LU# 1 - Commercial: Primary Total area (ac): 0.340  
13 - Paved Parking 1: 0.082 ac. Connected Source Area PSD File:  
C:\winSLAMM Files\NURP.cpz  
25 - Driveways 1: 0.126 ac. Connected Source Area PSD File: C:\winSLAMM Files\NURP.cpz  
26 - Driveways 2: 0.018 ac. Connected Source Area PSD File: C:\winSLAMM Files\NURP.cpz  
31 - Sidewalks 1: 0.007 ac. Connected Source Area PSD File: C:\winSLAMM Files\NURP.cpz  
32 - Sidewalks 2: 0.003 ac. Connected Source Area PSD File: C:\winSLAMM Files\NURP.cpz  
51 - Small Landscaped Areas 1: 0.093 ac. Normal Clayey Low Density  
Source Area PSD File: C:\winSLAMM Files\NURP.cpz  
52 - Small Landscaped Areas 2: 0.011 ac. Normal Clayey Low Density  
Source Area PSD File: C:\winSLAMM Files\NURP.cpz

LU# 2 - Commercial: Offsite Total area (ac): 0.341  
13 - Paved Parking 1: 0.008 ac. Connected Source Area PSD File:  
C:\winSLAMM Files\NURP.cpz  
25 - Driveways 1: 0.044 ac. Connected Source Area PSD File: C:\winSLAMM Files\NURP.cpz  
26 - Driveways 2: 0.022 ac. Connected Source Area PSD File: C:\winSLAMM Files\NURP.cpz  
31 - Sidewalks 1: 0.008 ac. Connected Source Area PSD File: C:\winSLAMM Files\NURP.cpz  
32 - Sidewalks 2: 0.003 ac. Connected Source Area PSD File: C:\winSLAMM Files\NURP.cpz  
51 - Small Landscaped Areas 1: 0.250 ac. Normal Clayey Low Density  
Source Area PSD File: C:\winSLAMM Files\NURP.cpz  
52 - Small Landscaped Areas 2: 0.006 ac. Normal Clayey Low Density  
Source Area PSD File: C:\winSLAMM Files\NURP.cpz

LU# 3 - Commercial: Secondary Total area (ac): 0.317  
Page 1



TSS Calculations - InputData.txt

1 - Roofs 1: 0.078 ac. Flat Connected Source Area PSD File:  
C:\winSLAMM Files\NURP.cpz  
13 - Paved Parking 1: 0.067 ac. Connected Source Area PSD File:  
C:\winSLAMM Files\NURP.cpz  
25 - Driveways 1: 0.107 ac. Connected Source Area PSD File: C:\winSLAMM  
Files\NURP.cpz  
31 - Sidewalks 1: 0.010 ac. Connected Source Area PSD File: C:\winSLAMM  
Files\NURP.cpz  
51 - Small Landscaped Areas 1: 0.055 ac. Normal Clayey Low Density  
Source Area PSD File: C:\winSLAMM Files\NURP.cpz

LU# 4 - Commercial: Tertiary Total area (ac): 0.135  
13 - Paved Parking 1: 0.108 ac. Connected Source Area PSD File:  
C:\winSLAMM Files\NURP.cpz  
31 - Sidewalks 1: 0.010 ac. Connected Source Area PSD File: C:\winSLAMM  
Files\NURP.cpz  
51 - Small Landscaped Areas 1: 0.017 ac. Normal Clayey Low Density  
Source Area PSD File: C:\winSLAMM Files\NURP.cpz

Control Practice 1: Catchbasin Cleaning CP# 1 (DS) - DS Catchbasins # 1

1. Fraction of area served by catchbasins = 1.00
  2. Number of catchbasins = 1
  3. Average sump depth below catchbasin outlet invert (feet) = 3
  4. Depth of sediment in catchbasin sump at beginning of study period (ft)
- = 0
5. Typical outlet pipe diameter (ft) = 1
  6. Typical outlet pipe Mannings n = 0.012
  7. Typical outlet pipe slope (ft/ft) = 0.01
  8. Typical catchbasin sump surface area (square feet) = 390
  9. Total catchbasin depth (feet) = 8
  10. Inflow hydrograph peak to average flow ratio = 3.8
  11. Leakage rate through sump bottom (in/hr) = 0
  12. Catchbasin Critical Particle Size File Name: Not needed - calculated  
by program

TSS Calculations - Output Summary.txt

SLAMM for windows Version 10.3.4  
 (c) Copyright Robert Pitt and John Voorhees 2012  
 All Rights Reserved

Data file name: I:\2018\188469\Civil\SWMP\Modeling\Slamm\TSS Calculations.mdb  
 Data file description:  
 Rain file name: C:\winSLAMM Files\Rain Files\wisReg - Madison WI 1981.RAN  
 Particulate Solids Concentration file name: C:\winSLAMM Files\v10.1 WI\_AVG01.pscx  
 Runoff Coefficient file name: C:\winSLAMM Files\WI\_SL06 Dec06.rsvx  
 Residential Street Delivery file name: C:\winSLAMM Files\WI\_Res and Other Urban Dec06.std  
 Institutional Street Delivery file name: C:\winSLAMM Files\WI\_Com Inst Indust Dec06.std  
 Commercial Street Delivery file name: C:\winSLAMM Files\WI\_Com Inst Indust Dec06.std  
 Industrial Street Delivery file name: C:\winSLAMM Files\WI\_Com Inst Indust Dec06.std  
 Other Urban Street Delivery file name: C:\winSLAMM Files\WI\_Res and Other Urban Dec06.std  
 Freeway Street Delivery file name: C:\winSLAMM Files\Freeway Dec06.std  
 Pollutant Relative Concentration file name: C:\winSLAMM Files\WI\_GEO03.ppd  
 Start of Winter Season: 12/02 End of Winter Season: 03/12  
 Model Run Start Date: 01/01/81 Model Run End Date: 12/31/81  
 Date of run: 04-06-2018 Time of run: 10:43:12  
 Total Area Modeled (acres): 1.133  
 Years in Model Run: 1.00

| Particulate                              | Percent     | Runoff  | Percent   | Particulate |
|--|-------------|---------|-----------|-------------|
| Solids                                   | Particulate | Volume  | Runoff    | Solids      |
| Yield                                    | Solids      | (cu ft) | Volume    | Conc.       |
| (lbs)                                    | Reduction   |         | Reduction | (mg/L)      |
| Total of all Land Uses without Controls: |             | 56938   | -         | 132.3       |
| 470.1                                    | -           |         |           |             |
| Outfall Total with Controls:             |             | 56937   | 0.00%     | 78.65       |
| 279.6                                    | 40.52%      |         |           |             |
| Annualized Total After Outfall Controls: |             | 57093   |           |             |
| 280.3                                    |             |         |           |             |

# **APPENDIX 7**

## **STORM SEWER SIZING CALCULATIONS**

### **STORM SEWER SYSTEM CALCULATIONS**

STORM SEWER SIZING CALCULATIONS - 10 YEAR STORM

| PIPE | Pipe Run   |            | Manhole Size (in.) | Length (ft.) | Pipe Diameter (inches) | Slope (%) | Pipe Material | Mannings (n) | Pipe Area (sq. ft.) | Hydraulic Radius (ft.) | DA             | Drainage Areas |               |               | Runoff Coef. C | Upstream End (Y/N) | Area x C  |       | Time of Conc.       |             | Rainfall Intensity (in/hr) | Design Storm Event | Total Runoff (cfs) | Design Capacity (cfs) | Percent Full (%) | Velocity Full (ft/sec) | Downstream I.E. (ft.) | Upstream I.E. (ft.) | Upstream T/P Elev. (ft.) | Pipe Cover (ft.) | Upstream Rim Elev. (ft.) | Upstream HGL Cover (ft) | Comments |
|------|------------|------------|--------------------|--------------|------------------------|-----------|---------------|--------------|---------------------|------------------------|----------------|----------------|---------------|---------------|----------------|--------------------|-----------|-------|---------------------|-------------|----------------------------|--------------------|--------------------|-----------------------|------------------|------------------------|-----------------------|---------------------|--------------------------|------------------|--------------------------|-------------------------|----------|
|      | From       | To         |                    |              |                        |           |               |              |                     |                        |                | Imp. (acres)   | Perv. (acres) | Total (acres) |                |                    | Increment | Total | To Structure (min.) | Pipe (min.) |                            |                    |                    |                       |                  |                        |                       |                     |                          |                  |                          |                         |          |
| P-1  | STO INL-1  | STO INL-2  | 2x3                | 23           | 10                     | 0.25      | PVC           | 0.010        | 0.55                | 0.21                   | P-1            | 0.155          | 0.166         | 0.321         | 0.59           | Y                  | 0.19      | 0.19  | 6.0                 | 0.15        | 6.68                       | 10                 | 1.26               | 1.43                  | 88.5%            | 2.62                   | 927.88                | 927.94              | 928.85                   | 1.92             | 930.77                   |                         |          |
| P-2  | STO INL-2  | STO MH 1   | 2x3                | 20           | 12                     | 0.40      | PVC           | 0.010        | 0.79                | 0.25                   | INL 2          | 0.092          | 0.024         | 0.116         | 0.80           | N                  | 0.09      | 0.28  | 6.1                 | 0.09        | 6.68                       | 10                 | 1.89               | 2.94                  | 64.3%            | 3.74                   | 927.70                | 927.78              | 928.86                   | 1.19             | 930.05                   |                         |          |
| P-3  | STO MH 1   | WQ Chamber | 36                 | 137          | 12                     | 0.98      | PVC           | 0.010        | 0.79                | 0.25                   |                |                |               |               | N              | 0.00               | 0.28      | 6.2   | 0.39                | 6.68        | 10                         | 1.89               | 4.61               | 41.0%                 | 5.87             | 926.25                 | 927.60                | 928.68              | 3.27                     | 931.95           |                          |                         |          |
| P-4  | STO INL-3  | WQ Chamber | 2x3                | 19           | 6                      | 5.00      | PVC           | 0.010        | 0.20                | 0.13                   | INL 3          | 0.079          | 0.011         | 0.090         | 0.86           | Y                  | 0.08      | 0.08  | 6.0                 | 0.04        | 6.68                       | 10                 | 0.52               | 1.64                  | 31.9%            | 8.33                   | 928.75                | 929.70              | 930.28                   | 3.27             | 933.55                   |                         |          |
| P-5  | STO INL-4  | WQ Chamber | 2x3                | 15           | 6                      | 5.00      | PVC           | 0.010        | 0.20                | 0.13                   | INL 4          | 0.098          | 0.024         | 0.122         | 0.81           | Y                  | 0.10      | 0.10  | 6.0                 | 0.03        | 6.68                       | 10                 | 0.66               | 1.64                  | 40.4%            | 8.33                   | 928.75                | 929.50              | 930.08                   | 3.96             | 934.04                   |                         |          |
| P-8  | RD         | STO INL-6  | -                  | 37           | 6                      | 5.00      | PVC           | 0.010        | 0.20                | 0.13                   | RD             | 0.000          | 0.090         | 0.090         | 0.25           | Y                  | 0.02      | 0.02  | 6.0                 | 0.07        | 6.68                       | 10                 | 0.15               | 1.64                  | 9.2%             | 8.33                   | 931.05                | 932.90              | 933.48                   | 3.72             | 937.20                   |                         |          |
| P-7  | STO INL-6  | STO INL-5  | 2x3                | 10           | 6                      | 5.00      | PVC           | 0.010        | 0.20                | 0.13                   |                |                |               |               | N              | 0.00               | 0.02      | 6.0   | 0.02                | 6.68        | 10                         | 0.15               | 1.64               | 9.2%                  | 8.33             | 930.45                 | 930.95                | 931.53              | 2.49                     | 934.02           |                          |                         |          |
| P-6  | STO INL-5  | WQ Chamber | 2x3                | 32           | 6                      | 5.00      | PVC           | 0.010        | 0.20                | 0.13                   | INL 5          | 0.153          | 0.029         | 0.182         | 0.84           | N                  | 0.15      | 0.18  | 6.0                 | 0.06        | 6.68                       | 10                 | 1.17               | 1.64                  | 71.7%            | 8.33                   | 928.75                | 930.35              | 930.93                   | 3.50             | 934.43                   |                         |          |
| P-9  | WQ Chamber | STO MH 2   | -                  | 8            | 12                     | 1.00      | PVC           | 0.010        | 0.79                | 0.25                   | HYDROCAD MODEL |                |               |               |                |                    |           |       |                     |             |                            |                    |                    |                       |                  | 926.17                 | 926.25                | 927.33              | 7.27                     | 934.60           |                          |                         |          |

# **APPENDIX 7**

## **USLE INFORMATION**





# Soil Loss & Sediment Discharge Calculation Tool

for use on Construction Sites in the State of Wisconsin

WDNR Official Version 1.0 (05-15-2015)



YEAR 1

Developer: Summit Credit Union

Project: Summit Credit Union - Waukesha Branch

Date: 4/6/2018

County: Waukesha

Version 1.0

| Activity             | Begin Date | End Date   | Period % R | Annual R Factor | Sub Soil Texture | Soil Erodibility K Factor | Slope (%) | Slope Length (feet) | LS Factor | Land Cover C Factor | Soil loss A (tons/acre) | Sediment Control Practice | Sediment Discharge (tons/acre) |
|----------------------|------------|------------|------------|-----------------|------------------|---------------------------|-----------|---------------------|-----------|---------------------|-------------------------|---------------------------|--------------------------------|
| Bare Ground          | 4/29/2019  | 5/10/2019  | 3.6%       | 130             | Clay             | 0.32                      | 40.0%     | 32                  | 8.20      | 1.00                | 12.2                    | Silt Fence                | 4.3                            |
| Mulch or Erosion Mat | 5/10/2019  | 10/15/2019 | 81.8%      | 130             | Clay             | 0.32                      | 40.0%     | 95                  | 14.13     | 0.20                | 96.2                    | Sediment Basin            | 0.0                            |
| End                  | 10/15/2019 | ----       | ----       | ----            | -----            | ----                      |           |                     | ----      | ----                | ----                    |                           | 0.0                            |
|                      |            | ----       | ----       | ----            | -----            | ----                      |           |                     | ----      | ----                | ----                    |                           | 0.0                            |
|                      |            | ----       | ----       | ----            | -----            | ----                      |           |                     | ----      | ----                | ----                    |                           | 0.0                            |
|                      |            | ----       | ----       | ----            | -----            | ----                      |           |                     | ----      | ----                | ----                    |                           | 0.0                            |
|                      |            | ----       | ----       | ----            | -----            | ----                      |           |                     | ----      | ----                | ----                    |                           | 0.0                            |
| <b>TOTAL</b>         |            |            |            |                 |                  |                           |           |                     |           |                     | <b>108.4</b>            | <b>TOTAL</b>              | <b>4.3</b>                     |

SLOPE > 20% USE PRESCRIPTIVE COMPLIANCE

|                             |             |
|-----------------------------|-------------|
| <b>% Reduction Required</b> | <b>NONE</b> |
|-----------------------------|-------------|

**Notes:**  
 See Help Page for further descriptions of variables and items in drop-down boxes.  
 The last land disturbing activity on each sheet must be 'End'. This is either 12 months from the start of construction or final stabilization.  
 For periods of construction that exceed 12 months, please demonstrate that 5 tons/acre/year is not exceeded in any given 12 month period.

NOTE: THIS TOOL ONLY ADDRESSED SOIL EROSION DUE TO SHEET FLOW. MEASURES TO CONTROL CHANNEL EROSION MAY ALSO BE REQUIRED TO MEET SEDIMENT DISCHARGE REQUIREMENTS.

**Recommended Permanent Seeding Dates:**  
 4/1-5/15 and 8/7-8/29 Turf, introduced grasses and legumes  
 Thaw-6/30 Native Grasses, forbs, and legumes

|              |          |
|--------------|----------|
| Designed By: | CLH      |
| Date         | 4/6/2018 |

## **APPENDIX 9**

### **MAINTAINENCE AGREEMENT**

**AGREEMENT FOR MAINTENANCE OF STORMWATER MANAGEMENT MEASURES**

**RECITALS:**

- A. Summit Credit Union \_\_\_\_\_  
is(are) the owner(s) of property in the  
City of Waukesha \_\_\_\_\_,  
County of Waukesha, State of Wisconsin, more particularly described  
on Exhibit A attached hereto (“Property”).
- B. The County requires Owner to record this Agreement regarding maintenance  
of stormwater management measures to be located on the Property. Owner  
agrees to maintain the stormwater management measures and to grant to the  
County the rights set forth below.

NOW, THEREFORE, in consideration of the agreement herein and other good and  
valuable consideration, the receipt and sufficiency of which are hereby acknowledged,  
the owner agrees as follows:

- 1. Maintenance. Owner and its successors and assigns shall be responsible to  
repair and maintain the stormwater management measures located on the  
Property in good condition and in working order and such that the measures  
comply with approved plans on file with Waukesha County. Said  
maintenance shall be at the Owner’s sole cost and expense. Owner will  
conduct such

maintenance or repair work in accordance with all applicable laws, codes,  
regulations, and similar requirements. Specific maintenance task are more  
particularly described on Exhibit A.

- 2. Easement to County. If Owner fails to maintain the stormwater management  
measures as required in Section 1, then County shall have the right, after providing Owner with written notice of the  
maintenance issue (“Maintenance Notice”) and thirty (30) days to comply with the County’s maintenance request, to  
enter the Property in order to conduct the maintenance specified in the Maintenance Notice. County will conduct such  
maintenance work in accordance with all applicable laws, codes, regulations, and similar requirements and will not  
unreasonably interfere with Owner’s use of the Property. All costs and expenses incurred by the County in conducting  
such maintenance may be charged to the owner of the Property by placing the amount on the tax roll for the Property as  
a special assessment in accordance with Section 66.0703, Wis. Stats. and applicable portions of the Waukesha County  
Ordinances.

- 3. Term/Termination. The term of this Agreement shall commence on the date that this Agreement is recorded with the  
Register of Deeds Office for Waukesha County, Wisconsin, and except as otherwise herein specifically provided, shall  
continue in perpetuity. Notwithstanding the foregoing, this Agreement may be terminated by recording with the Register  
of Deeds Office for Waukesha County, Wisconsin, a written instrument of termination signed by the County and all of  
the then-owners of the Property.

- 4. Miscellaneous.
  - (a) Notices. Any notice, request or demand required or permitted under this Agreement shall be in writing and  
shall be deemed given when personally served or three (3) days after the same has been deposited with the  
United States Post Office, registered or certified mail, return receipt requested, postage prepaid and addressed  
as follows:

If to Owner: \_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_

This space is reserved for recording data

Return to:  
Waukesha County Register of Deeds  
515 W Moreland Blvd Rm AC110  
Waukesha, Wisconsin 53188

Parcel Number(s):

WAKC113015001

If to County: Waukesha County Land & Water Resources  
515 W Moreland Blvd Rm AC110  
Waukesha, Wisconsin 53188

Any party may change its address for the receipt of notice by written notice to the other.

- (b) Governing Law. This Agreement shall be governed and construed in accordance with the laws of the State of Wisconsin.
- (c) Amendments or Further Agreements to be in Writing. This Agreement may not be modified in whole or in part unless such agreement is in writing and signed by all parties bound hereby.
- (d) Covenants Running with the Land. All of the easements, restrictions, covenants and agreements set forth in this Agreement are intended to be and shall be construed as covenants running with the land, binding upon, inuring to the benefit of, and enforceable by the parties hereto and their respective successors and assigns.
- (e) Partial Invalidity. If any provisions, or portions thereof, of this Agreement or the application thereof to any person or circumstance shall, to any extent, be invalid or unenforceable, the remainder of this Agreement, or the application of such provision, or portion thereof, to any other persons or circumstances shall not be affected thereby and each provision of this Agreement shall be valid and enforceable to the fullest extent permitted by law.

X \_\_\_\_\_  
Land Records Staff Signature

\_\_\_\_\_  
Print or type name

**State of WI**, County of \_\_\_\_\_; Subscribed and sworn  
before me on \_\_\_\_\_ by  
the above named person(s).

\_\_\_\_\_  
Notary Public

Print or type name: \_\_\_\_\_

My Commission Expires: \_\_\_\_\_

---

X \_\_\_\_\_  
Owner Signature

\_\_\_\_\_  
Print or type name

**State of WI**, County of \_\_\_\_\_; Subscribed and sworn  
before me on \_\_\_\_\_ by  
the above named person(s).

\_\_\_\_\_  
Notary Public

Print or type name: \_\_\_\_\_

My Commission Expires: \_\_\_\_\_

**DRAFTED BY:** \_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_

## **EXHIBIT A**

Lot 1 of CSM #10663

## **EXHIBIT B**

### Maintenance Provisions:

#### Storm Sewer System

The owner shall maintain all components of the storm sewer system located onsite. Installation and maintenance shall be in accordance with the manufacturer's guidelines. At a minimum the storm sewer system shall be inspected annually and cleaned as needed to maintain functionality and design capacity. The sumps located in the storm sewer system shall be inspected a minimum of three (3) times per year. Sediment should be removed from the sumps when sediment depth is greater than 1.5'. Owner shall maintain records of inspections, cleaning and replacement of the system or components of the system all in accordance with City of Waukesha Ordinances.

#### Underground Water Quality System

The owner shall install and maintain an underground storage chamber system as distributed by StormTech or approved equivalent. Said system is installed for detention and infiltration purposes to infiltrate roof water runoff. Installation and maintenance shall be in accordance with the manufacturer's guidelines. Inspect the StormTech system immediately following construction completion. Inspection of the underground storage structure shall be done a minimum of two (2) times per year or as needed until an understanding of the site characteristics is developed. More specifically, the StormTech rows shall be visually inspected via the inspection port and is to be JetVac cleaned any time sediment has accumulated to an average depth exceeding three (3) inches. Owner shall maintain records of inspections and cleaning of the rows in accordance with the City of Waukesha Ordinances.

Detailed information regarding installation and maintenance can be found on the Internet at [www.stormtech.com](http://www.stormtech.com) or by calling StormTech at 888-892-2694.