



## LED DECORATIVE WALL SCONCE—UP AND DOWN, LARGE 34-WATT LED E-S23 SERIES

**Applications** – Ideal for illumination along steps, walkways and entry ways

**Typical Mounting Height:** 8 to 15 feet **Typical Spacing:** 1 to 2 times the mounting height

GOOD HARVEST FOODS  
TYPE OE



7-1/4" L x 6" W x 7-3/16" H

| Catalog #  | Description                         | Input Voltage         | Delivered Lumen Output | CCT   | CRI | Estimated Lifetime (L70) | Weight  |
|--|-------------------------------------|-----------------------|------------------------|-------|-----|--------------------------|---------|
| <b>E-S23L033UW (White)</b><br><b>E-S23L033UK (Black)</b> | 34W (Total)<br>LED<br>Warm White    | Universal<br>120-277V | 2500 Lumens (Total)    | 3000K | 80  | 100,000+ Hours           | 6.2 lbs |
| <b>E-S23L034UW (White)</b><br><b>E-S23L034UK (Black)</b> | 34W (Total)<br>LED<br>Neutral White | Universal<br>120-277V | 2500 Lumens (Total)    | 4000K | 80  | 100,000+ Hours           | 6.2 lbs |

### Features

- Estimated 100,000+ hours of maintenance-free operation to L70
- Up and down fixture creates gorgeous hourglass lighting effect
- Dimmable with most 0-10V dimmers
- Die-cast aluminum mounting box with extruded aluminum housing—mounting box measures 5" square (5-3/8" square with gasket)
- Supplied with back mounting plate to mount over a 4" square or 4" octagonal junction box
- 25-degree beam spread
- Silicon gasket provides a water tight seal
- Polyester powder-coat black or white finish
- Tempered glass lens, thermal shock and impact resistant
- Universal voltage (120V through 277V)
- ETL Listed for wet locations
- Cree® LEDs inside
- 3-year warranty

### Accessories

None Available