



MEMORANDUM

TO: Josh Pudelko
FROM: Jayme Sisel
DATE: January 25, 2021
SUBJECT: Skyline Subdivision Stormwater Management

The following is a summary of preliminary stormwater assumptions and calculations for the proposed Skyline Subdivision project. This preliminary stormwater management plan meets the City of Waukesha's requirements for stormwater management.

Design Requirements:

Chapter 32 of the City of Waukesha's Code of Ordinance includes criteria for peak discharge, water quality, and infiltration practices.

- The Ordinance requires post-development peak discharge rates to be no greater than pre-development discharge rates for the 1, 2, 10 and 100-year, 24-hour design storms.
- The Ordinance requires best management practices (BMPs) to be designed to control total suspended solids (TSS) carried by runoff from redevelopment sites by 40 percent and from new development sites by 80 percent, based on an average annual rainfall, as compared to no runoff management controls.
- The Ordinance requires medium density residential developments to infiltrate sufficient runoff volume so that the post-development infiltration volume is at least 75 percent of pre-development infiltration volume, based on an average annual rainfall. However, no more than 2 percent of the post-construction site is required as an effective infiltration area.

Analysis Overview:

Peak runoff rates and volumes were computed using NRCS's TR-55 and TR-20 methodologies, as implemented by HydroCAD Version 10.00 software by HydroCAD Software Solutions.

Soil types for the site were determined from soil boring logs and from the NRCS Soil Survey for Waukesha County. Soils at the site are predominantly hydrologic soil group D soils. Maximum predevelopment runoff curve numbers (CN) were taken from Chapter 32 of Waukesha's City Ordinance.

Rainfall values were taken from Table 3 of Chapter 32 of Waukesha's City Ordinance. MSE3 rainfall distributions were used for peak flow calculations.

SOUND STORMWATER DESIGN LLC

Existing Conditions:

The project site is approximately 80-acres in size and is occupied by a farmstead and two residential properties. The site is mostly cropland with some areas of woodlands and wetlands. Peak flow rates for existing conditions are as follows:

$$\begin{aligned} Q(1\text{yr}) &= 60.68 \text{ cfs} \\ Q(2\text{yr}) &= 76.17 \text{ cfs} \\ Q(10\text{yr}) &= 137.92 \text{ cfs} \\ Q(100\text{yr}) &= 279.59 \text{ cfs} \end{aligned}$$

Proposed Conditions:

The proposed development includes the construction of a new residential subdivision including new roadways, a public park, stormwater management ponds and infiltration basins. The proposed plan will disturb approximately 75 acres and will result in a net increase in impervious area of approximately 22.8 acres. Development assumptions are as follows:

- 1/3-acre residential lots ~ assumed 30 percent impervious
- New road cross-section to match neighboring subdivision
 - 5-foot sidewalk, both sides
 - 5½-foot landscape, both sides
 - 39-foot road, curb to curb

Overall peak flow rates for proposed conditions are shown as follows:

$$\begin{aligned} Q(1\text{yr}) &= 20.23 \text{ cfs} \\ Q(2\text{yr}) &= 25.60 \text{ cfs} \\ Q(10\text{yr}) &= 64.38 \text{ cfs} \\ Q(100\text{yr}) &= 187.44 \text{ cfs} \end{aligned}$$

Stormwater Quality:

Stormwater quality will be accomplished by six stormwater management ponds and three infiltration basins. The stormwater management ponds and infiltration basins are designed in accordance with WDNR's Technical Standard 1001 (Wet Detention Basin) and 1003 (Infiltration Basin), respectively.

Stormwater quality was analyzed using SLAMM Version 10.4.1 software, developed by Robert Pitt and John Voorhees. The results of the SLAMM analysis indicate that approximately 80 percent of TSS will be removed from stormwater as a result of the proposed stormwater management ponds and infiltration basins. Detailed computations are included.

Infiltration:

The soil boring logs indicate soils at the site as generally 3 to 8 feet of clay underlain by silt, loam or sand with varying amounts of gravel. Based on this, infiltration will be

SOUND STORMWATER DESIGN LLC

incorporated into areas of the site where groundwater is not a limiting factor and unsuitable surficial clays can be excavated to access soils suitable for infiltration.

FIGURES



SOUND STORMWATER DESIGN

Copper Oaks Ct.
Muskego, WI 53150
414.286.4739
jayme.sisell@soundstormwater.com

CLIENT:
BIELINSKI HOMES
1830 MEADOW LANE, SUITE A
PEWAUKEE, WISCONSIN 53072


PROJECT TITLE:
SKYLINE SUBDIVISION
SUMMIT AVENUE (USH 18)
WAUKESHA, WISCONSIN

DATE: 01-25-21

JOB NO: 2019-006

SHEET TITLE:
EXISTING CONDITIONS PLAN


FIGURE:








SOUND STORMWATER DESIGN

Copper Oaks Ct.
Muskego, WI 53150
414.286.4739
jayme.sisell@soundstormwater.com



**HYDROLOGIC ANALYSIS
EXISTING CONDITIONS**



Routing Diagram for Existing_006
 Prepared by HP Inc., Printed 1/24/2021
 HydroCAD® 10.00-25 s/n 11025 © 2019 HydroCAD Software Solutions LLC

Existing_006

Prepared by HP Inc.

HydroCAD® 10.00-25 s/n 11025 © 2019 HydroCAD Software Solutions LLC

Printed 1/24/2021

Page 2

Area Listing (all nodes)

Area (acres)	CN	Description (subcatchment-numbers)
54.390	83	cropland - D soils (10N, 20E, 30E, 40E, 50E, 60W, 70W, 80W, 90W)
3.690	80	grass - D soils (50E, 80W, 90W)
0.250	96	gravel (50E, 90W)
0.470	98	impervious (50E, 90W)
6.600	78	meadow - D soils (80W)
2.080	78	wetland - D soils (10N, 20E, 80W)
12.420	77	woodland - D soils (10N, 20E, 30E, 40E, 50E, 60W, 70W, 80W, 90W)
79.900	82	TOTAL AREA

Time span=0.00-24.00 hrs, dt=0.05 hrs, 481 points
Runoff by SCS TR-20 method, UH=SCS, Weighted-CN
Reach routing by Stor-Ind+Trans method - Pond routing by Stor-Ind method

Subcatchment10N: Subarea Runoff Area=14.600 ac 0.00% Impervious Runoff Depth>0.92"
Flow Length=590' Slope=0.0700 '/' Tc=19.2 min CN=82 Runoff=15.07 cfs 1.124 af

Subcatchment20E: Subarea Runoff Area=18.960 ac 0.00% Impervious Runoff Depth>0.92"
Flow Length=1,495' Tc=26.7 min CN=82 Runoff=16.34 cfs 1.459 af

Subcatchment30E: Subarea Runoff Area=2.160 ac 0.00% Impervious Runoff Depth>0.98"
Flow Length=390' Slope=0.0500 '/' Tc=20.4 min CN=83 Runoff=2.31 cfs 0.176 af

Subcatchment40E: Subarea Runoff Area=4.460 ac 0.00% Impervious Runoff Depth>0.98"
Flow Length=550' Slope=0.0500 '/' Tc=21.8 min CN=83 Runoff=4.59 cfs 0.364 af

Subcatchment50E: Subarea Runoff Area=4.910 ac 6.31% Impervious Runoff Depth>0.98"
Flow Length=545' Slope=0.0800 '/' Tc=17.2 min CN=83 Runoff=5.73 cfs 0.401 af

Subcatchment60W: Subarea Runoff Area=2.410 ac 0.00% Impervious Runoff Depth>0.98"
Flow Length=445' Tc=18.5 min CN=83 Runoff=2.70 cfs 0.197 af

Subcatchment70W: Subarea Runoff Area=3.760 ac 0.00% Impervious Runoff Depth>0.98"
Flow Length=430' Tc=16.0 min CN=83 Runoff=4.54 cfs 0.307 af

Subcatchment80W: Subarea Runoff Area=20.770 ac 0.00% Impervious Runoff Depth>0.77"
Flow Length=1,275' Tc=56.1 min CN=79 Runoff=9.08 cfs 1.326 af

Subcatchment90W: Subarea Runoff Area=7.870 ac 2.03% Impervious Runoff Depth>0.98"
Flow Length=445' Slope=0.0800 '/' Tc=17.2 min CN=83 Runoff=9.19 cfs 0.643 af

Link 15: North Drainage Inflow=15.07 cfs 1.124 af
Primary=15.07 cfs 1.124 af

Link 35: East to White Oak Way Inflow=18.41 cfs 1.635 af
Primary=18.41 cfs 1.635 af

Link 45: East to Hawthorn Hill Drive Inflow=4.59 cfs 0.364 af
Primary=4.59 cfs 0.364 af

Link 55: East to Summit Avenue Inflow=5.73 cfs 0.401 af
Primary=5.73 cfs 0.401 af

Link 95: West Drainage Inflow=18.47 cfs 2.473 af
Primary=18.47 cfs 2.473 af

Link 99: Total Existing Flow Inflow=60.68 cfs 5.997 af
Primary=60.68 cfs 5.997 af

Total Runoff Area = 79.900 ac Runoff Volume = 5.997 af Average Runoff Depth = 0.90"
99.41% Pervious = 79.430 ac 0.59% Impervious = 0.470 ac

Existing_006

MSE 24-hr 3 2-yr Rainfall=2.70"

Prepared by HP Inc.

Printed 1/24/2021

HydroCAD® 10.00-25 s/n 11025 © 2019 HydroCAD Software Solutions LLC

Page 20

Time span=0.00-24.00 hrs, dt=0.05 hrs, 481 points
 Runoff by SCS TR-20 method, UH=SCS, Weighted-CN
 Reach routing by Stor-Ind+Trans method - Pond routing by Stor-Ind method

Subcatchment10N: Subarea Runoff Area=14.600 ac 0.00% Impervious Runoff Depth>1.15"
 Flow Length=590' Slope=0.0700 '/' Tc=19.2 min CN=82 Runoff=18.87 cfs 1.394 af

Subcatchment20E: Subarea Runoff Area=18.960 ac 0.00% Impervious Runoff Depth>1.14"
 Flow Length=1,495' Tc=26.7 min CN=82 Runoff=20.48 cfs 1.809 af

Subcatchment30E: Subarea Runoff Area=2.160 ac 0.00% Impervious Runoff Depth>1.21"
 Flow Length=390' Slope=0.0500 '/' Tc=20.4 min CN=83 Runoff=2.87 cfs 0.217 af

Subcatchment40E: Subarea Runoff Area=4.460 ac 0.00% Impervious Runoff Depth>1.21"
 Flow Length=550' Slope=0.0500 '/' Tc=21.8 min CN=83 Runoff=5.70 cfs 0.449 af

Subcatchment50E: Subarea Runoff Area=4.910 ac 6.31% Impervious Runoff Depth>1.21"
 Flow Length=545' Slope=0.0800 '/' Tc=17.2 min CN=83 Runoff=7.12 cfs 0.494 af

Subcatchment60W: Subarea Runoff Area=2.410 ac 0.00% Impervious Runoff Depth>1.21"
 Flow Length=445' Tc=18.5 min CN=83 Runoff=3.35 cfs 0.243 af

Subcatchment70W: Subarea Runoff Area=3.760 ac 0.00% Impervious Runoff Depth>1.21"
 Flow Length=430' Tc=16.0 min CN=83 Runoff=5.64 cfs 0.378 af

Subcatchment80W: Subarea Runoff Area=20.770 ac 0.00% Impervious Runoff Depth>0.97"
 Flow Length=1,275' Tc=56.1 min CN=79 Runoff=11.72 cfs 1.676 af

Subcatchment90W: Subarea Runoff Area=7.870 ac 2.03% Impervious Runoff Depth>1.21"
 Flow Length=445' Slope=0.0800 '/' Tc=17.2 min CN=83 Runoff=11.41 cfs 0.792 af

Link 15: North Drainage Inflow=18.87 cfs 1.394 af
 Primary=18.87 cfs 1.394 af

Link 35: East to White Oak Way Inflow=23.07 cfs 2.026 af
 Primary=23.07 cfs 2.026 af

Link 45: East to Hawthorn Hill Drive Inflow=5.70 cfs 0.449 af
 Primary=5.70 cfs 0.449 af

Link 55: East to Summit Avenue Inflow=7.12 cfs 0.494 af
 Primary=7.12 cfs 0.494 af

Link 95: West Drainage Inflow=23.33 cfs 3.089 af
 Primary=23.33 cfs 3.089 af

Link 99: Total Existing Flow Inflow=76.17 cfs 7.452 af
 Primary=76.17 cfs 7.452 af

Total Runoff Area = 79.900 ac Runoff Volume = 7.452 af Average Runoff Depth = 1.12"
99.41% Pervious = 79.430 ac 0.59% Impervious = 0.470 ac

Time span=0.00-24.00 hrs, dt=0.05 hrs, 481 points
Runoff by SCS TR-20 method, UH=SCS, Weighted-CN
Reach routing by Stor-Ind+Trans method - Pond routing by Stor-Ind method

Subcatchment10N: Subarea Runoff Area=14.600 ac 0.00% Impervious Runoff Depth>2.04"
Flow Length=590' Slope=0.0700 '/' Tc=19.2 min CN=82 Runoff=33.92 cfs 2.481 af

Subcatchment20E: Subarea Runoff Area=18.960 ac 0.00% Impervious Runoff Depth>2.04"
Flow Length=1,495' Tc=26.7 min CN=82 Runoff=36.96 cfs 3.220 af

Subcatchment30E: Subarea Runoff Area=2.160 ac 0.00% Impervious Runoff Depth>2.12"
Flow Length=390' Slope=0.0500 '/' Tc=20.4 min CN=83 Runoff=5.07 cfs 0.381 af

Subcatchment40E: Subarea Runoff Area=4.460 ac 0.00% Impervious Runoff Depth>2.12"
Flow Length=550' Slope=0.0500 '/' Tc=21.8 min CN=83 Runoff=10.11 cfs 0.788 af

Subcatchment50E: Subarea Runoff Area=4.910 ac 6.31% Impervious Runoff Depth>2.12"
Flow Length=545' Slope=0.0800 '/' Tc=17.2 min CN=83 Runoff=12.56 cfs 0.867 af

Subcatchment60W: Subarea Runoff Area=2.410 ac 0.00% Impervious Runoff Depth>2.12"
Flow Length=445' Tc=18.5 min CN=83 Runoff=5.92 cfs 0.426 af

Subcatchment70W: Subarea Runoff Area=3.760 ac 0.00% Impervious Runoff Depth>2.12"
Flow Length=430' Tc=16.0 min CN=83 Runoff=9.93 cfs 0.664 af

Subcatchment80W: Subarea Runoff Area=20.770 ac 0.00% Impervious Runoff Depth>1.80"
Flow Length=1,275' Tc=56.1 min CN=79 Runoff=22.57 cfs 3.117 af

Subcatchment90W: Subarea Runoff Area=7.870 ac 2.03% Impervious Runoff Depth>2.12"
Flow Length=445' Slope=0.0800 '/' Tc=17.2 min CN=83 Runoff=20.13 cfs 1.390 af

Link 15: North Drainage Inflow=33.92 cfs 2.481 af
Primary=33.92 cfs 2.481 af

Link 35: East to White Oak Way Inflow=41.66 cfs 3.601 af
Primary=41.66 cfs 3.601 af

Link 45: East to Hawthorn Hill Drive Inflow=10.11 cfs 0.788 af
Primary=10.11 cfs 0.788 af

Link 55: East to Summit Avenue Inflow=12.56 cfs 0.867 af
Primary=12.56 cfs 0.867 af

Link 95: West Drainage Inflow=42.94 cfs 5.598 af
Primary=42.94 cfs 5.598 af

Link 99: Total Existing Flow Inflow=137.92 cfs 13.335 af
Primary=137.92 cfs 13.335 af

Total Runoff Area = 79.900 ac Runoff Volume = 13.335 af Average Runoff Depth = 2.00"
99.41% Pervious = 79.430 ac 0.59% Impervious = 0.470 ac

Time span=0.00-24.00 hrs, dt=0.05 hrs, 481 points

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN

Reach routing by Stor-Ind+Trans method - Pond routing by Stor-Ind method

Subcatchment10N: Subarea Runoff Area=14.600 ac 0.00% Impervious Runoff Depth>4.15"
Flow Length=590' Slope=0.0700 '/' Tc=19.2 min CN=82 Runoff=68.24 cfs 5.047 af

Subcatchment20E: Subarea Runoff Area=18.960 ac 0.00% Impervious Runoff Depth>4.15"
Flow Length=1,495' Tc=26.7 min CN=82 Runoff=74.84 cfs 6.551 af

Subcatchment30E: Subarea Runoff Area=2.160 ac 0.00% Impervious Runoff Depth>4.25"
Flow Length=390' Slope=0.0500 '/' Tc=20.4 min CN=83 Runoff=10.05 cfs 0.766 af

Subcatchment40E: Subarea Runoff Area=4.460 ac 0.00% Impervious Runoff Depth>4.25"
Flow Length=550' Slope=0.0500 '/' Tc=21.8 min CN=83 Runoff=20.04 cfs 1.581 af

Subcatchment50E: Subarea Runoff Area=4.910 ac 6.31% Impervious Runoff Depth>4.25"
Flow Length=545' Slope=0.0800 '/' Tc=17.2 min CN=83 Runoff=24.83 cfs 1.741 af

Subcatchment60W: Subarea Runoff Area=2.410 ac 0.00% Impervious Runoff Depth>4.25"
Flow Length=445' Tc=18.5 min CN=83 Runoff=11.75 cfs 0.854 af

Subcatchment70W: Subarea Runoff Area=3.760 ac 0.00% Impervious Runoff Depth>4.26"
Flow Length=430' Tc=16.0 min CN=83 Runoff=19.61 cfs 1.333 af

Subcatchment80W: Subarea Runoff Area=20.770 ac 0.00% Impervious Runoff Depth>3.82"
Flow Length=1,275' Tc=56.1 min CN=79 Runoff=48.41 cfs 6.619 af

Subcatchment90W: Subarea Runoff Area=7.870 ac 2.03% Impervious Runoff Depth>4.25"
Flow Length=445' Slope=0.0800 '/' Tc=17.2 min CN=83 Runoff=39.79 cfs 2.790 af

Link 15: North Drainage Inflow=68.24 cfs 5.047 af
Primary=68.24 cfs 5.047 af

Link 35: East to White Oak Way Inflow=84.05 cfs 7.317 af
Primary=84.05 cfs 7.317 af

Link 45: East to Hawthorn Hill Drive Inflow=20.04 cfs 1.581 af
Primary=20.04 cfs 1.581 af

Link 55: East to Summit Avenue Inflow=24.83 cfs 1.741 af
Primary=24.83 cfs 1.741 af

Link 95: West Drainage Inflow=88.56 cfs 11.597 af
Primary=88.56 cfs 11.597 af

Link 99: Total Existing Flow Inflow=279.59 cfs 27.282 af
Primary=279.59 cfs 27.282 af

Total Runoff Area = 79.900 ac Runoff Volume = 27.282 af Average Runoff Depth = 4.10"
99.41% Pervious = 79.430 ac 0.59% Impervious = 0.470 ac

Existing_006

Prepared by HP Inc.

HydroCAD® 10.00-25 s/n 11025 © 2019 HydroCAD Software Solutions LLC

MSE 24-hr 3 100-yr Rainfall=6.18"

Printed 1/24/2021

Page 55


Summary for Subcatchment 10N: Subarea

Runoff = 68.24 cfs @ 12.28 hrs, Volume= 5.047 af, Depth> 4.15"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.05 hrs
MSE 24-hr 3 100-yr Rainfall=6.18"

Area (ac)	CN	Description
* 12.830	83	cropland - D soils
* 1.200	77	woodland - D soils
* 0.570	78	wetland - D soils
14.600	82	Weighted Average
14.600		100.00% Pervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
17.2	300	0.0700	0.29		Sheet Flow, Cultivated: Residue>20% n= 0.170 P2= 2.70"
2.0	290	0.0700	2.38		Shallow Concentrated Flow, Cultivated Straight Rows Kv= 9.0 fps
19.2	590	Total			

Subcatchment 10N: Subarea

Existing_006

Prepared by HP Inc.

HydroCAD® 10.00-25 s/n 11025 © 2019 HydroCAD Software Solutions LLC

MSE 24-hr 3 100-yr Rainfall=6.18"

Printed 1/24/2021


Page 56

Summary for Subcatchment 20E: Subarea

Runoff = 74.84 cfs @ 12.37 hrs, Volume= 6.551 af, Depth> 4.15"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.05 hrs
MSE 24-hr 3 100-yr Rainfall=6.18"

Area (ac)	CN	Description		
* 16.870	83	cropland - D soils		
* 0.780	77	woodland - D soils		
* 1.310	78	wetland - D soils		
18.960	82	Weighted Average		
18.960		100.00% Pervious Area		
Tc (min)	Length (feet)	Slope (ft/ft) Velocity (ft/sec) Capacity (cfs) Description		
13.4	250	0.0900	0.31	Sheet Flow, Cultivated: Residue>20% n= 0.170 P2= 2.70"
13.3	1,245	0.0300	1.56	Shallow Concentrated Flow, Cultivated Straight Rows Kv= 9.0 fps
26.7	1,495	Total		

Subcatchment 20E: Subarea

Summary for Subcatchment 30E: Subarea

Runoff = 10.05 cfs @ 12.30 hrs, Volume= 0.766 af, Depth> 4.25"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.05 hrs
 MSE 24-hr 3 100-yr Rainfall=6.18"


Area (ac)	CN	Description
* 1.980	83	cropland - D soils
* 0.180	77	woodland - D soils

2.160	83	Weighted Average
2.160		100.00% Pervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
19.7	300	0.0500	0.25		Sheet Flow, Cultivated: Residue>20% n= 0.170 P2= 2.70"
0.7	90	0.0500	2.01		Shallow Concentrated Flow, Cultivated Straight Rows Kv= 9.0 fps
20.4	390	Total			

Subcatchment 30E: Subarea

Hydrograph



Summary for Subcatchment 40E: Subarea

Runoff = 20.04 cfs @ 12.31 hrs, Volume= 1.581 af, Depth> 4.25"


Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.05 hrs
 MSE 24-hr 3 100-yr Rainfall=6.18"

Area (ac)	CN	Description
* 4.170	83	cropland - D soils
* 0.290	77	woodland - D soils

4.460	83	Weighted Average
4.460		100.00% Pervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
19.7	300	0.0500	0.25		Sheet Flow, Cultivated: Residue>20% n= 0.170 P2= 2.70"
2.1	250	0.0500	2.01		Shallow Concentrated Flow, Cultivated Straight Rows Kv= 9.0 fps
21.8	550	Total			

Subcatchment 40E: Subarea



Existing_006

Prepared by HP Inc.

HydroCAD® 10.00-25 s/n 11025 © 2019 HydroCAD Software Solutions LLC

MSE 24-hr 3 100-yr Rainfall=6.18"

Printed 1/24/2021

Page 59


Summary for Subcatchment 50E: Subarea

Runoff = 24.83 cfs @ 12.26 hrs, Volume= 1.741 af, Depth> 4.25"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.05 hrs
MSE 24-hr 3 100-yr Rainfall=6.18"

Area (ac)	CN	Description
*	1.710	83 cropland - D soils
*	0.470	77 woodland - D soils
*	2.220	80 grass - D soils
*	0.200	96 gravel
*	0.310	98 impervious
4.910	83	Weighted Average
4.600		93.69% Pervious Area
0.310		6.31% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
16.3	300	0.0800	0.31		Sheet Flow, Cultivated: Residue>20% n= 0.170 P2= 2.70"
0.9	245	0.0800	4.55		Shallow Concentrated Flow, Unpaved Kv= 16.1 fps
17.2	545	Total			

Subcatchment 50E: Subarea

Summary for Subcatchment 60W: Subarea

Runoff = 11.75 cfs @ 12.27 hrs, Volume= 0.854 af, Depth> 4.25"


Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.05 hrs
 MSE 24-hr 3 100-yr Rainfall=6.18"

Area (ac)	CN	Description
* 2.350	83	cropland - D soils
* 0.060	77	woodland - D soils

2.410	83	Weighted Average
2.410		100.00% Pervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
15.4	280	0.0800	0.30		Sheet Flow, Cultivated: Residue>20% n= 0.170 P2= 2.70"
3.1	165	0.0100	0.90		Shallow Concentrated Flow, Cultivated Straight Rows Kv= 9.0 fps
18.5	445	Total			

Subcatchment 60W: Subarea



Summary for Subcatchment 70W: Subarea

Runoff = 19.61 cfs @ 12.25 hrs, Volume= 1.333 af, Depth> 4.26"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.05 hrs
 MSE 24-hr 3 100-yr Rainfall=6.18"


Area (ac)	CN	Description
* 3.630	83	cropland - D soils
* 0.130	77	woodland - D soils

3.760	83	Weighted Average
		100.00% Pervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
13.9	300	0.1200	0.36		Sheet Flow, Cultivated: Residue>20% n= 0.170 P2= 2.70"
0.1	20	0.1200	3.12		Shallow Concentrated Flow, Cultivated Straight Rows Kv= 9.0 fps
2.0	110	0.0100	0.90		Shallow Concentrated Flow, Cultivated Straight Rows Kv= 9.0 fps
16.0	430	Total			

Subcatchment 70W: Subarea

Hydrograph



Existing_006

Prepared by HP Inc.

HydroCAD® 10.00-25 s/n 11025 © 2019 HydroCAD Software Solutions LLC

MSE 24-hr 3 100-yr Rainfall=6.18"

Printed 1/24/2021

Page 62


Summary for Subcatchment 80W: Subarea

Runoff = 48.41 cfs @ 12.76 hrs, Volume= 6.619 af, Depth> 3.82"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.05 hrs
MSE 24-hr 3 100-yr Rainfall=6.18"

Area (ac)	CN	Description
*	4.430	83 cropland - D soils
*	9.200	77 woodland - D soils
*	0.200	78 wetland - D soils
*	6.600	78 meadow - D soils
*	0.340	80 grass - D soils
20.770	79	Weighted Average
20.770		100.00% Pervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
5.1	80	0.0600	0.26		Sheet Flow, Range n= 0.130 P2= 2.70"
28.3	220	0.0600	0.13		Sheet Flow, Woods: Light underbrush n= 0.400 P2= 2.70"
6.7	495	0.0600	1.22		Shallow Concentrated Flow, Woodland Kv= 5.0 fps
16.0	480	0.0100	0.50		Shallow Concentrated Flow, Woodland Kv= 5.0 fps
56.1	1,275	Total			

Subcatchment 80W: Subarea

Summary for Subcatchment 90W: Subarea


Runoff = 39.79 cfs @ 12.26 hrs, Volume= 2.790 af, Depth> 4.25"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.05 hrs
 MSE 24-hr 3 100-yr Rainfall=6.18"

Area (ac)	CN	Description
*	6.420	83 cropland - D soils
*	0.110	77 woodland - D soils
*	1.130	80 grass - D soils
*	0.050	96 gravel
*	0.160	98 impervious
7.870	83	Weighted Average
7.710		97.97% Pervious Area
0.160		2.03% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
16.3	300	0.0800	0.31		Sheet Flow, Cultivated: Residue>20% n= 0.170 P2= 2.70"
0.9	145	0.0800	2.55		Shallow Concentrated Flow, Cultivated Straight Rows Kv= 9.0 fps
17.2	445	Total			

Subcatchment 90W: Subarea




Summary for Link 15: North Drainage

Inflow Area = 14.600 ac, 0.00% Impervious, Inflow Depth > 4.15" for 100-yr event
Inflow = 68.24 cfs @ 12.28 hrs, Volume= 5.047 af
Primary = 68.24 cfs @ 12.28 hrs, Volume= 5.047 af, Atten= 0%, Lag= 0.0 min

Primary outflow = Inflow, Time Span= 0.00-24.00 hrs, dt= 0.05 hrs

Link 15: North Drainage




Summary for Link 35: East to White Oak Way

Inflow Area = 21.120 ac, 0.00% Impervious, Inflow Depth > 4.16" for 100-yr event

Inflow = 84.05 cfs @ 12.36 hrs, Volume= 7.317 af

Primary = 84.05 cfs @ 12.36 hrs, Volume= 7.317 af, Atten= 0%, Lag= 0.0 min

Primary outflow = Inflow, Time Span= 0.00-24.00 hrs, dt= 0.05 hrs

Link 35: East to White Oak Way**Hydrograph**


Summary for Link 45: East to Hawthorn Hill Drive

Inflow Area = 4.460 ac, 0.00% Impervious, Inflow Depth > 4.25" for 100-yr event

Inflow = 20.04 cfs @ 12.31 hrs, Volume= 1.581 af

Primary = 20.04 cfs @ 12.31 hrs, Volume= 1.581 af, Atten= 0%, Lag= 0.0 min

Primary outflow = Inflow, Time Span= 0.00-24.00 hrs, dt= 0.05 hrs

Link 45: East to Hawthorn Hill Drive**Hydrograph**


Summary for Link 55: East to Summit Avenue

Inflow Area = 4.910 ac, 6.31% Impervious, Inflow Depth > 4.25" for 100-yr event

Inflow = 24.83 cfs @ 12.26 hrs, Volume= 1.741 af

Primary = 24.83 cfs @ 12.26 hrs, Volume= 1.741 af, Atten= 0%, Lag= 0.0 min


Primary outflow = Inflow, Time Span= 0.00-24.00 hrs, dt= 0.05 hrs

Link 55: East to Summit Avenue**Hydrograph**

Summary for Link 95: West Drainage

Inflow Area = 34.810 ac, 0.46% Impervious, Inflow Depth > 4.00" for 100-yr event
Inflow = 88.56 cfs @ 12.28 hrs, Volume= 11.597 af
Primary = 88.56 cfs @ 12.28 hrs, Volume= 11.597 af, Atten= 0%, Lag= 0.0 min

Primary outflow = Inflow, Time Span= 0.00-24.00 hrs, dt= 0.05 hrs

Link 95: West Drainage**Hydrograph**


Summary for Link 99: Total Existing Flow

Inflow Area = 79.900 ac, 0.59% Impervious, Inflow Depth > 4.10" for 100-yr event




Inflow = 279.59 cfs @ 12.30 hrs, Volume= 27.282 af

Primary = 279.59 cfs @ 12.30 hrs, Volume= 27.282 af, Atten= 0%, Lag= 0.0 min

Primary outflow = Inflow, Time Span= 0.00-24.00 hrs, dt= 0.05 hrs

Link 99: Total Existing Flow**Hydrograph**

**HYDROLOGIC ANALYSIS
PROPOSED CONDITIONS**



Routing Diagram for Proposed_006_REVISED

Prepared by HP Inc., Printed 1/24/2021

HydroCAD® 10.00-25 s/n 11025 © 2019 HydroCAD Software Solutions LLC

Proposed_006_REVISED

Prepared by HP Inc.

HydroCAD® 10.00-25 s/n 11025 © 2019 HydroCAD Software Solutions LLC

Printed 1/24/2021

Page 2

Area Listing (all nodes)

Area (acres)	CN	Description (subcatchment-numbers)
50.480	86	1/3 acre lots, 30% imp, HSG D (5N, 10N, 20E, 25E, 30E, 40E, 50E, 60W, 70W, 80W)
14.180	80	grass - D soils (5N, 10N, 20E, 25E, 30E, 50E, 60W, 70W, 80W, 90W)
8.070	98	road (5N, 10N, 20E, 30E, 40E, 70W, 80W)
0.280	98	sidewalk (10N, 30E, 50E, 60W, 70W, 80W)
1.610	98	water (5N, 20E, 30E, 70W, 80W)
2.070	78	wetland - D soils (10N, 25E, 90W)
3.210	77	woodland - D soils (5N, 10N, 20E, 25E, 30E, 80W, 90W)
79.900	86	TOTAL AREA

Time span=0.00-24.00 hrs, dt=0.01 hrs, 2401 points
Runoff by SCS TR-20 method, UH=SCS, Weighted-CN
Reach routing by Sim-Route method - Pond routing by Sim-Route method

Subcatchment5N: Subarea	Runoff Area=17.500 ac 35.06% Impervious Runoff Depth>1.23" Flow Length=185' Slope=0.0300 '/' Tc=21.6 min CN=87 Runoff=23.21 cfs 1.788 af
Subcatchment10N: Subarea - North	Runoff Area=4.960 ac 12.94% Impervious Runoff Depth>0.92" Flow Length=185' Slope=0.0700 '/' Tc=15.4 min CN=82 Runoff=5.75 cfs 0.382 af
Subcatchment20E: Subarea	Runoff Area=5.400 ac 35.15% Impervious Runoff Depth>1.23" Flow Length=240' Slope=0.0500 '/' Tc=21.7 min CN=87 Runoff=7.15 cfs 0.552 af
Subcatchment25E: Subarea - East to	Runoff Area=3.510 ac 11.03% Impervious Runoff Depth>0.87" Flow Length=645' Slope=0.0300 '/' Tc=33.9 min CN=81 Runoff=2.46 cfs 0.254 af
Subcatchment30E: Subarea	Runoff Area=9.140 ac 36.70% Impervious Runoff Depth>1.23" Flow Length=85' Slope=0.0600 '/' Tc=8.8 min CN=87 Runoff=18.41 cfs 0.935 af
Subcatchment40E: Subarea - East to	Runoff Area=1.690 ac 37.04% Impervious Runoff Depth>1.23" Flow Length=300' Slope=0.0700 '/' Tc=22.7 min CN=87 Runoff=2.18 cfs 0.173 af
Subcatchment50E: Subarea - East to	Runoff Area=2.510 ac 20.72% Impervious Runoff Depth>1.04" Flow Length=160' Slope=0.1000 '/' Tc=11.9 min CN=84 Runoff=3.75 cfs 0.217 af
Subcatchment60W: Subarea - West to	Runoff Area=1.780 ac 20.11% Impervious Runoff Depth>1.04" Flow Length=165' Slope=0.0800 '/' Tc=13.3 min CN=84 Runoff=2.52 cfs 0.154 af
Subcatchment70W: Subarea	Runoff Area=16.300 ac 37.82% Impervious Runoff Depth>1.23" Flow Length=140' Slope=0.0600 '/' Tc=13.1 min CN=87 Runoff=27.67 cfs 1.666 af
Subcatchment80W: Subarea	Runoff Area=14.390 ac 34.89% Impervious Runoff Depth>1.23" Flow Length=190' Slope=0.0900 '/' Tc=14.2 min CN=87 Runoff=23.49 cfs 1.471 af
Subcatchment90W: Subarea	Runoff Area=2.720 ac 0.00% Impervious Runoff Depth>0.72" Flow Length=495' Slope=0.0100 '/' Tc=39.9 min CN=78 Runoff=1.38 cfs 0.163 af
Pond 5P: Pond	Peak Elev=216.88' Storage=1.201 af Inflow=23.21 cfs 1.788 af Outflow=1.21 cfs 1.072 af
Pond 20B: Pond/Basin	Peak Elev=214.60' Storage=0.548 af Inflow=18.41 cfs 0.935 af Discarded=0.10 cfs 0.096 af Primary=1.10 cfs 0.751 af Outflow=1.20 cfs 0.847 af
Pond 20P: Pond	Peak Elev=222.24' Storage=0.226 af Inflow=7.15 cfs 0.552 af Outflow=3.23 cfs 0.528 af
Pond 70B: Pond/Basin	Peak Elev=213.46' Storage=0.861 af Inflow=27.67 cfs 1.666 af Discarded=0.14 cfs 0.124 af Primary=3.70 cfs 1.357 af Outflow=3.84 cfs 1.482 af
Pond 80B: Pond/Basin	Peak Elev=212.76' Storage=0.860 af Inflow=23.49 cfs 1.471 af Discarded=0.25 cfs 0.249 af Primary=1.89 cfs 0.849 af Outflow=2.14 cfs 1.098 af

Proposed_006_REVISED

Prepared by HP Inc.

HydroCAD® 10.00-25 s/n 11025 © 2019 HydroCAD Software Solutions LLC

MSE 24-hr 3 1-yr Rainfall=2.40"

Printed 1/24/2021

Page 4

Link 15L: North DrainageInflow=6.31 cfs 1.453 af
Primary=6.31 cfs 1.453 af**Link 35L: East to White Oak Way**Inflow=6.55 cfs 1.533 af
Primary=6.55 cfs 1.533 af**Link 45L: East to Hawthorn Hill Drive**Inflow=2.18 cfs 0.173 af
Primary=2.18 cfs 0.173 af**Link 55: East to Summit Avenue**Inflow=3.75 cfs 0.217 af
Primary=3.75 cfs 0.217 af**Link 95: West Drainage**Inflow=7.24 cfs 2.524 af
Primary=7.24 cfs 2.524 af**Link 99: Total Existing Flow**Inflow=20.23 cfs 5.898 af
Primary=20.23 cfs 5.898 af**Total Runoff Area = 79.900 ac Runoff Volume = 7.755 af Average Runoff Depth = 1.16"**
68.58% Pervious = 54.796 ac 31.42% Impervious = 25.104 ac

Time span=0.00-24.00 hrs, dt=0.01 hrs, 2401 points
Runoff by SCS TR-20 method, UH=SCS, Weighted-CN
Reach routing by Sim-Route method - Pond routing by Sim-Route method

Subcatchment5N: Subarea	Runoff Area=17.500 ac 35.06% Impervious Runoff Depth>1.48" Flow Length=185' Slope=0.0300 '/' Tc=21.6 min CN=87 Runoff=28.02 cfs 2.155 af
Subcatchment10N: Subarea - North	Runoff Area=4.960 ac 12.94% Impervious Runoff Depth>1.15" Flow Length=185' Slope=0.0700 '/' Tc=15.4 min CN=82 Runoff=7.20 cfs 0.474 af
Subcatchment20E: Subarea	Runoff Area=5.400 ac 35.15% Impervious Runoff Depth>1.48" Flow Length=240' Slope=0.0500 '/' Tc=21.7 min CN=87 Runoff=8.62 cfs 0.665 af
Subcatchment25E: Subarea - East to	Runoff Area=3.510 ac 11.03% Impervious Runoff Depth>1.08" Flow Length=645' Slope=0.0300 '/' Tc=33.9 min CN=81 Runoff=3.11 cfs 0.317 af
Subcatchment30E: Subarea	Runoff Area=9.140 ac 36.70% Impervious Runoff Depth>1.48" Flow Length=85' Slope=0.0600 '/' Tc=8.8 min CN=87 Runoff=22.13 cfs 1.127 af
Subcatchment40E: Subarea - East to	Runoff Area=1.690 ac 37.04% Impervious Runoff Depth>1.48" Flow Length=300' Slope=0.0700 '/' Tc=22.7 min CN=87 Runoff=2.63 cfs 0.208 af
Subcatchment50E: Subarea - East to	Runoff Area=2.510 ac 20.72% Impervious Runoff Depth>1.27" Flow Length=160' Slope=0.1000 '/' Tc=11.9 min CN=84 Runoff=4.61 cfs 0.266 af
Subcatchment60W: Subarea - West to	Runoff Area=1.780 ac 20.11% Impervious Runoff Depth>1.27" Flow Length=165' Slope=0.0800 '/' Tc=13.3 min CN=84 Runoff=3.11 cfs 0.189 af
Subcatchment70W: Subarea	Runoff Area=16.300 ac 37.82% Impervious Runoff Depth>1.48" Flow Length=140' Slope=0.0600 '/' Tc=13.1 min CN=87 Runoff=33.33 cfs 2.009 af
Subcatchment80W: Subarea	Runoff Area=14.390 ac 34.89% Impervious Runoff Depth>1.48" Flow Length=190' Slope=0.0900 '/' Tc=14.2 min CN=87 Runoff=28.30 cfs 1.773 af
Subcatchment90W: Subarea	Runoff Area=2.720 ac 0.00% Impervious Runoff Depth>0.92" Flow Length=495' Slope=0.0100 '/' Tc=39.9 min CN=78 Runoff=1.80 cfs 0.208 af
Pond 5P: Pond	Peak Elev=217.16' Storage=1.402 af Inflow=28.02 cfs 2.155 af Outflow=2.59 cfs 1.320 af
Pond 20B: Pond/Basin	Peak Elev=214.91' Storage=0.680 af Inflow=22.13 cfs 1.127 af Discarded=0.11 cfs 0.104 af Primary=1.22 cfs 0.909 af Outflow=1.33 cfs 1.013 af
Pond 20P: Pond	Peak Elev=222.34' Storage=0.248 af Inflow=8.62 cfs 0.665 af Outflow=4.82 cfs 0.640 af
Pond 70B: Pond/Basin	Peak Elev=213.77' Storage=1.059 af Inflow=33.33 cfs 2.009 af Discarded=0.15 cfs 0.132 af Primary=4.30 cfs 1.683 af Outflow=4.45 cfs 1.814 af
Pond 80B: Pond/Basin	Peak Elev=212.93' Storage=1.028 af Inflow=28.30 cfs 1.773 af Discarded=0.26 cfs 0.260 af Primary=2.51 cfs 1.118 af Outflow=2.76 cfs 1.378 af

Proposed_006_REVISED

Prepared by HP Inc.

HydroCAD® 10.00-25 s/n 11025 © 2019 HydroCAD Software Solutions LLC

MSE 24-hr 3 2-yr Rainfall=2.70"

Printed 1/24/2021

Page 33

Link 15L: North DrainageInflow=7.87 cfs 1.793 af
Primary=7.87 cfs 1.793 af**Link 35L: East to White Oak Way**Inflow=9.03 cfs 1.865 af
Primary=9.03 cfs 1.865 af**Link 45L: East to Hawthorn Hill Drive**Inflow=2.63 cfs 0.208 af
Primary=2.63 cfs 0.208 af**Link 55: East to Summit Avenue**Inflow=4.61 cfs 0.266 af
Primary=4.61 cfs 0.266 af**Link 95: West Drainage**Inflow=9.03 cfs 3.196 af
Primary=9.03 cfs 3.196 af**Link 99: Total Existing Flow**Inflow=25.60 cfs 7.326 af
Primary=25.60 cfs 7.326 af**Total Runoff Area = 79.900 ac Runoff Volume = 9.390 af Average Runoff Depth = 1.41"**
68.58% Pervious = 54.796 ac 31.42% Impervious = 25.104 ac

Time span=0.00-24.00 hrs, dt=0.01 hrs, 2401 points
Runoff by SCS TR-20 method, UH=SCS, Weighted-CN
Reach routing by Sim-Route method - Pond routing by Sim-Route method

Subcatchment5N: Subarea	Runoff Area=17.500 ac 35.06% Impervious Runoff Depth>2.46" Flow Length=185' Slope=0.0300 '/' Tc=21.6 min CN=87 Runoff=46.38 cfs 3.587 af
Subcatchment10N: Subarea - North	Runoff Area=4.960 ac 12.94% Impervious Runoff Depth>2.04" Flow Length=185' Slope=0.0700 '/' Tc=15.4 min CN=82 Runoff=12.93 cfs 0.843 af
Subcatchment20E: Subarea	Runoff Area=5.400 ac 35.15% Impervious Runoff Depth>2.46" Flow Length=240' Slope=0.0500 '/' Tc=21.7 min CN=87 Runoff=14.26 cfs 1.107 af
Subcatchment25E: Subarea - East to	Runoff Area=3.510 ac 11.03% Impervious Runoff Depth>1.96" Flow Length=645' Slope=0.0300 '/' Tc=33.9 min CN=81 Runoff=5.75 cfs 0.573 af
Subcatchment30E: Subarea	Runoff Area=9.140 ac 36.70% Impervious Runoff Depth>2.46" Flow Length=85' Slope=0.0600 '/' Tc=8.8 min CN=87 Runoff=36.28 cfs 1.875 af
Subcatchment40E: Subarea - East to	Runoff Area=1.690 ac 37.04% Impervious Runoff Depth>2.46" Flow Length=300' Slope=0.0700 '/' Tc=22.7 min CN=87 Runoff=4.36 cfs 0.346 af
Subcatchment50E: Subarea - East to	Runoff Area=2.510 ac 20.72% Impervious Runoff Depth>2.20" Flow Length=160' Slope=0.1000 '/' Tc=11.9 min CN=84 Runoff=7.96 cfs 0.461 af
Subcatchment60W: Subarea - West to	Runoff Area=1.780 ac 20.11% Impervious Runoff Depth>2.20" Flow Length=165' Slope=0.0800 '/' Tc=13.3 min CN=84 Runoff=5.37 cfs 0.327 af
Subcatchment70W: Subarea	Runoff Area=16.300 ac 37.82% Impervious Runoff Depth>2.46" Flow Length=140' Slope=0.0600 '/' Tc=13.1 min CN=87 Runoff=54.90 cfs 3.343 af
Subcatchment80W: Subarea	Runoff Area=14.390 ac 34.89% Impervious Runoff Depth>2.46" Flow Length=190' Slope=0.0900 '/' Tc=14.2 min CN=87 Runoff=46.60 cfs 2.951 af
Subcatchment90W: Subarea	Runoff Area=2.720 ac 0.00% Impervious Runoff Depth>1.73" Flow Length=495' Slope=0.0100 '/' Tc=39.9 min CN=78 Runoff=3.53 cfs 0.392 af
Pond 5P: Pond	Peak Elev=217.76' Storage=1.859 af Inflow=46.38 cfs 3.587 af Outflow=14.48 cfs 2.614 af
Pond 20B: Pond/Basin	Peak Elev=215.59' Storage=1.002 af Inflow=36.28 cfs 1.875 af Discarded=0.13 cfs 0.120 af Primary=5.84 cfs 1.546 af Outflow=5.96 cfs 1.666 af
Pond 20P: Pond	Peak Elev=222.63' Storage=0.320 af Inflow=14.26 cfs 1.107 af Outflow=11.02 cfs 1.076 af
Pond 70B: Pond/Basin	Peak Elev=214.62' Storage=1.644 af Inflow=54.90 cfs 3.343 af Discarded=0.18 cfs 0.151 af Primary=13.45 cfs 2.969 af Outflow=13.63 cfs 3.120 af
Pond 80B: Pond/Basin	Peak Elev=213.65' Storage=1.761 af Inflow=46.60 cfs 2.951 af Discarded=0.30 cfs 0.301 af Primary=4.05 cfs 2.168 af Outflow=4.35 cfs 2.469 af

Proposed_006_REVISED

Prepared by HP Inc.

HydroCAD® 10.00-25 s/n 11025 © 2019 HydroCAD Software Solutions LLC

MSE 24-hr 3 10-yr Rainfall=3.81"

Printed 1/24/2021

Page 62

Link 15L: North DrainageInflow=17.21 cfs 3.456 af
Primary=17.21 cfs 3.456 af**Link 35L: East to White Oak Way**Inflow=22.37 cfs 3.193 af
Primary=22.37 cfs 3.193 af**Link 45L: East to Hawthorn Hill Drive**Inflow=4.36 cfs 0.346 af
Primary=4.36 cfs 0.346 af**Link 55: East to Summit Avenue**Inflow=7.96 cfs 0.461 af
Primary=7.96 cfs 0.461 af**Link 95: West Drainage**Inflow=22.26 cfs 5.855 af
Primary=22.26 cfs 5.855 af**Link 99: Total Existing Flow**Inflow=64.38 cfs 13.310 af
Primary=64.38 cfs 13.310 af

Total Runoff Area = 79.900 ac Runoff Volume = 15.804 af Average Runoff Depth = 2.37"
68.58% Pervious = 54.796 ac 31.42% Impervious = 25.104 ac

Time span=0.00-24.00 hrs, dt=0.01 hrs, 2401 points
Runoff by SCS TR-20 method, UH=SCS, Weighted-CN
Reach routing by Sim-Route method - Pond routing by Sim-Route method

Subcatchment5N: Subarea	Runoff Area=17.500 ac 35.06% Impervious Runoff Depth>4.68" Flow Length=185' Slope=0.0300 '/' Tc=21.6 min CN=87 Runoff=86.37 cfs 6.831 af
Subcatchment10N: Subarea - North	Runoff Area=4.960 ac 12.94% Impervious Runoff Depth>4.15" Flow Length=185' Slope=0.0700 '/' Tc=15.4 min CN=82 Runoff=25.97 cfs 1.715 af
Subcatchment20E: Subarea	Runoff Area=5.400 ac 35.15% Impervious Runoff Depth>4.68" Flow Length=240' Slope=0.0500 '/' Tc=21.7 min CN=87 Runoff=26.51 cfs 2.108 af
Subcatchment25E: Subarea - East to	Runoff Area=3.510 ac 11.03% Impervious Runoff Depth>4.04" Flow Length=645' Slope=0.0300 '/' Tc=33.9 min CN=81 Runoff=11.85 cfs 1.181 af
Subcatchment30E: Subarea	Runoff Area=9.140 ac 36.70% Impervious Runoff Depth>4.69" Flow Length=85' Slope=0.0600 '/' Tc=8.8 min CN=87 Runoff=66.90 cfs 3.570 af
Subcatchment40E: Subarea - East to	Runoff Area=1.690 ac 37.04% Impervious Runoff Depth>4.68" Flow Length=300' Slope=0.0700 '/' Tc=22.7 min CN=87 Runoff=8.11 cfs 0.660 af
Subcatchment50E: Subarea - East to	Runoff Area=2.510 ac 20.72% Impervious Runoff Depth>4.36" Flow Length=160' Slope=0.1000 '/' Tc=11.9 min CN=84 Runoff=15.41 cfs 0.912 af
Subcatchment60W: Subarea - West to	Runoff Area=1.780 ac 20.11% Impervious Runoff Depth>4.36" Flow Length=165' Slope=0.0800 '/' Tc=13.3 min CN=84 Runoff=10.41 cfs 0.647 af
Subcatchment70W: Subarea	Runoff Area=16.300 ac 37.82% Impervious Runoff Depth>4.69" Flow Length=140' Slope=0.0600 '/' Tc=13.1 min CN=87 Runoff=101.68 cfs 6.366 af
Subcatchment80W: Subarea	Runoff Area=14.390 ac 34.89% Impervious Runoff Depth>4.69" Flow Length=190' Slope=0.0900 '/' Tc=14.2 min CN=87 Runoff=86.38 cfs 5.619 af
Subcatchment90W: Subarea	Runoff Area=2.720 ac 0.00% Impervious Runoff Depth>3.73" Flow Length=495' Slope=0.0100 '/' Tc=39.9 min CN=78 Runoff=7.70 cfs 0.845 af
Pond 5P: Pond	Peak Elev=218.82' Storage=2.760 af Inflow=86.37 cfs 6.830 af Outflow=49.85 cfs 5.685 af
Pond 20B: Pond/Basin	Peak Elev=216.68' Storage=1.620 af Inflow=66.90 cfs 3.570 af Discarded=0.16 cfs 0.141 af Primary=23.18 cfs 3.094 af Outflow=23.34 cfs 3.235 af
Pond 20P: Pond	Peak Elev=223.07' Storage=0.438 af Inflow=26.51 cfs 2.108 af Outflow=23.06 cfs 2.064 af
Pond 70B: Pond/Basin	Peak Elev=215.95' Storage=2.738 af Inflow=101.68 cfs 6.365 af Discarded=0.24 cfs 0.181 af Primary=39.10 cfs 5.915 af Outflow=39.34 cfs 6.096 af
Pond 80B: Pond/Basin	Peak Elev=214.95' Storage=3.297 af Inflow=86.38 cfs 5.619 af Discarded=0.36 cfs 0.378 af Primary=11.61 cfs 4.552 af Outflow=11.97 cfs 4.930 af

Proposed_006_REVISED

Prepared by HP Inc.

HydroCAD® 10.00-25 s/n 11025 © 2019 HydroCAD Software Solutions LLC

MSE 24-hr 3 100-yr Rainfall=6.18"

Printed 1/24/2021

Page 91

Link 15L: North DrainageInflow=60.01 cfs 7.399 af
Primary=60.01 cfs 7.399 af**Link 35L: East to White Oak Way**Inflow=57.33 cfs 6.338 af
Primary=57.33 cfs 6.338 af**Link 45L: East to Hawthorn Hill Drive**Inflow=8.11 cfs 0.660 af
Primary=8.11 cfs 0.660 af**Link 55: East to Summit Avenue**Inflow=15.41 cfs 0.912 af
Primary=15.41 cfs 0.912 af**Link 95: West Drainage**Inflow=59.30 cfs 11.958 af
Primary=59.30 cfs 11.958 af**Link 99: Total Existing Flow**Inflow=187.44 cfs 27.263 af
Primary=187.44 cfs 27.263 af

Total Runoff Area = 79.900 ac Runoff Volume = 30.454 af Average Runoff Depth = 4.57"
68.58% Pervious = 54.796 ac 31.42% Impervious = 25.104 ac

Proposed_006_REVISED

Prepared by HP Inc.

HydroCAD® 10.00-25 s/n 11025 © 2019 HydroCAD Software Solutions LLC

MSE 24-hr 3 100-yr Rainfall=6.18"

Printed 1/24/2021

Page 92

Summary for Subcatchment 5N: Subarea

Runoff = 86.37 cfs @ 12.31 hrs, Volume= 6.831 af, Depth> 4.68"


Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs
MSE 24-hr 3 100-yr Rainfall=6.18"

Area (ac)	CN	Description
* 0.200	77	woodland - D soils
* 0.570	98	water
* 1.800	98	road
12.550	86	1/3 acre lots, 30% imp, HSG D
* 2.380	80	grass - D soils
17.500	87	Weighted Average
11.365		64.94% Pervious Area
6.135		35.06% Impervious Area

Tc	Length	Slope	Velocity	Capacity	Description
(min)	(feet)	(ft/ft)	(ft/sec)	(cfs)	
21.6	185	0.0300	0.14		Sheet Flow, Grass: Dense n= 0.240 P2= 2.70"

Subcatchment 5N: Subarea

Hydrograph



Proposed_006_REVISED

Prepared by HP Inc.

HydroCAD® 10.00-25 s/n 11025 © 2019 HydroCAD Software Solutions LLC

MSE 24-hr 3 100-yr Rainfall=6.18"

Printed 1/24/2021

Page 93

Summary for Subcatchment 10N: Subarea - North Drainage

Runoff = 25.97 cfs @ 12.24 hrs, Volume= 1.715 af, Depth> 4.15"


Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs
MSE 24-hr 3 100-yr Rainfall=6.18"

Area (ac)	CN	Description
*	0.940	77 woodland - D soils
*	0.570	78 wetland - D soils
*	1.380	80 grass - D soils
	2.040	86 1/3 acre lots, 30% imp, HSG D
*	0.020	road
*	0.010	sidewalk
	4.960	Weighted Average
	4.318	87.06% Pervious Area
	0.642	12.94% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
15.4	185	0.0700	0.20		Sheet Flow, Grass: Dense n= 0.240 P2= 2.70"

Subcatchment 10N: Subarea - North Drainage

Hydrograph



Proposed_006_REVISED

Prepared by HP Inc.

HydroCAD® 10.00-25 s/n 11025 © 2019 HydroCAD Software Solutions LLC

MSE 24-hr 3 100-yr Rainfall=6.18"

Printed 1/24/2021

Page 94

Summary for Subcatchment 20E: Subarea

Runoff = 26.51 cfs @ 12.31 hrs, Volume= 2.108 af, Depth> 4.68"


Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs
MSE 24-hr 3 100-yr Rainfall=6.18"

Area (ac)	CN	Description
*	0.570	98 road
	3.960	1/3 acre lots, 30% imp, HSG D
*	0.690	80 grass - D soils
*	0.140	98 water
*	0.040	77 woodland - D soils
	5.400	Weighted Average
	3.502	64.85% Pervious Area
	1.898	35.15% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
21.7	240	0.0500	0.18		Sheet Flow, Grass: Dense n= 0.240 P2= 2.70"

Subcatchment 20E: Subarea

Hydrograph



Proposed_006_REVISED

Prepared by HP Inc.

HydroCAD® 10.00-25 s/n 11025 © 2019 HydroCAD Software Solutions LLC

MSE 24-hr 3 100-yr Rainfall=6.18"

Printed 1/24/2021

Page 95


Summary for Subcatchment 25E: Subarea - East to White Oak Way

Runoff = 11.85 cfs @ 12.47 hrs, Volume= 1.181 af, Depth> 4.04"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs
MSE 24-hr 3 100-yr Rainfall=6.18"

Area (ac)	CN	Description
* 0.110	77	woodland - D soils
* 1.310	78	wetland - D soils
1.290	86	1/3 acre lots, 30% imp, HSG D
* 0.800	80	grass - D soils
3.510	81	Weighted Average
3.123		88.97% Pervious Area
0.387		11.03% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
31.8	300	0.0300	0.16		Sheet Flow, Grass: Dense n= 0.240 P2= 2.70"
2.1	345	0.0300	2.79		Shallow Concentrated Flow, Unpaved Kv= 16.1 fps
33.9	645	Total			

Subcatchment 25E: Subarea - East to White Oak Way

Proposed_006_REVISED

Prepared by HP Inc.

HydroCAD® 10.00-25 s/n 11025 © 2019 HydroCAD Software Solutions LLC

MSE 24-hr 3 100-yr Rainfall=6.18"

Printed 1/24/2021

Page 96

Summary for Subcatchment 30E: Subarea

Runoff = 66.90 cfs @ 12.16 hrs, Volume= 3.570 af, Depth> 4.69"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs
MSE 24-hr 3 100-yr Rainfall=6.18"

Area (ac)	CN	Description
* 0.250	77	woodland - D soils
* 0.190	98	water
* 1.450	98	road
5.480	86	1/3 acre lots, 30% imp, HSG D
* 1.700	80	grass - D soils
* 0.070	98	sidewalk

9.140 87 Weighted Average


5.786 63.30% Pervious Area

3.354 36.70% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
8.8	85	0.0600	0.16		Sheet Flow, Grass: Dense n= 0.240 P2= 2.70"

Subcatchment 30E: Subarea

Hydrograph



Summary for Subcatchment 40E: Subarea - East to Hawthorn Hill Drive


Runoff = 8.11 cfs @ 12.33 hrs, Volume= 0.660 af, Depth> 4.68"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs
MSE 24-hr 3 100-yr Rainfall=6.18"

Area (ac)	CN	Description
* 0.170	98	road
1.520	86	1/3 acre lots, 30% imp, HSG D

1.690	87	Weighted Average
1.064		62.96% Pervious Area
0.626		37.04% Impervious Area

Tc	Length	Slope	Velocity	Capacity	Description
(min)	(feet)	(ft/ft)	(ft/sec)	(cfs)	
22.7	300	0.0700	0.22		Sheet Flow, Grass: Dense n= 0.240 P2= 2.70"

Subcatchment 40E: Subarea - East to Hawthorn Hill Drive


Summary for Subcatchment 50E: Subarea - East to Summit Avenue

Runoff = 15.41 cfs @ 12.20 hrs, Volume= 0.912 af, Depth> 4.36"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs
MSE 24-hr 3 100-yr Rainfall=6.18"

Area (ac)	CN	Description
1.500	86	1/3 acre lots, 30% imp, HSG D
*	0.940	grass - D soils
*	0.070	sidewalk
2.510	84	Weighted Average
1.990		79.28% Pervious Area
0.520		20.72% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
11.9	160	0.1000	0.22		Sheet Flow, Grass: Dense n= 0.240 P2= 2.70"

Subcatchment 50E: Subarea - East to Summit Avenue**Hydrograph**


Summary for Subcatchment 60W: Subarea - West to Summit Avenue

Runoff = 10.41 cfs @ 12.21 hrs, Volume= 0.647 af, Depth> 4.36"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs
MSE 24-hr 3 100-yr Rainfall=6.18"

Area (ac)	CN	Description
0.960	86	1/3 acre lots, 30% imp, HSG D
*	0.750	grass - D soils
*	0.070	sidewalk
1.780	84	Weighted Average
1.422		79.89% Pervious Area
0.358		20.11% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
13.3	165	0.0800	0.21		Sheet Flow, Grass: Dense n= 0.240 P2= 2.70"

Subcatchment 60W: Subarea - West to Summit Avenue**Hydrograph**

Proposed_006_REVISED

Prepared by HP Inc.

HydroCAD® 10.00-25 s/n 11025 © 2019 HydroCAD Software Solutions LLC

MSE 24-hr 3 100-yr Rainfall=6.18"

Printed 1/24/2021

Page 100

Summary for Subcatchment 70W: Subarea

Runoff = 101.68 cfs @ 12.21 hrs, Volume= 6.366 af, Depth> 4.69"


Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs
MSE 24-hr 3 100-yr Rainfall=6.18"

Area (ac)	CN	Description
*	2.340	98 road
11.680	86	1/3 acre lots, 30% imp, HSG D
*	1.960	80 grass - D soils
*	0.280	98 water
*	0.040	98 sidewalk
16.300	87	Weighted Average
10.136		62.18% Pervious Area
6.164		37.82% Impervious Area

Tc	Length	Slope	Velocity	Capacity	Description
(min)	(feet)	(ft/ft)	(ft/sec)	(cfs)	
13.1	140	0.0600	0.18		Sheet Flow, Grass: Dense n= 0.240 P2= 2.70"

Subcatchment 70W: Subarea

Hydrograph



Summary for Subcatchment 80W: Subarea

Runoff = 86.38 cfs @ 12.22 hrs, Volume= 5.619 af, Depth> 4.69"

Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs
MSE 24-hr 3 100-yr Rainfall=6.18"


Area (ac)	CN	Description
*	0.040	77 woodland - D soils
*	0.430	98 water
*	1.720	98 road
	9.500	1/3 acre lots, 30% imp, HSG D
*	2.680	80 grass - D soils
*	0.020	sidewalk

14.390 87 Weighted Average

9.370 65.11% Pervious Area

5.020 34.89% Impervious Area

Tc	Length	Slope	Velocity	Capacity	Description
(min)	(feet)	(ft/ft)	(ft/sec)	(cfs)	
14.2	190	0.0900	0.22		Sheet Flow, Grass: Dense n= 0.240 P2= 2.70"

Subcatchment 80W: Subarea**Hydrograph**

Proposed_006_REVISED

Prepared by HP Inc.

HydroCAD® 10.00-25 s/n 11025 © 2019 HydroCAD Software Solutions LLC

MSE 24-hr 3 100-yr Rainfall=6.18"

Printed 1/24/2021

Page 102

Summary for Subcatchment 90W: Subarea

Runoff = 7.70 cfs @ 12.55 hrs, Volume= 0.845 af, Depth> 3.73"


Runoff by SCS TR-20 method, UH=SCS, Weighted-CN, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs
MSE 24-hr 3 100-yr Rainfall=6.18"

Area (ac)	CN	Description
* 1.630	77	woodland - D soils
* 0.190	78	wetland - D soils
* 0.900	80	grass - D soils
2.720	78	Weighted Average
2.720		100.00% Pervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
28.4	150	0.0100	0.09		Sheet Flow, Grass: Dense n= 0.240 P2= 2.70"
11.5	345	0.0100	0.50		Shallow Concentrated Flow, Woodland Kv= 5.0 fps
39.9	495	Total			

Subcatchment 90W: Subarea

Hydrograph



Proposed_006_REVISED

Prepared by HP Inc.

HydroCAD® 10.00-25 s/n 11025 © 2019 HydroCAD Software Solutions LLC

MSE 24-hr 3 100-yr Rainfall=6.18"

Printed 1/24/2021

Page 103

Summary for Pond 5P: Pond

Inflow Area = 17.500 ac, 35.06% Impervious, Inflow Depth > 4.68" for 100-yr event
 Inflow = 86.37 cfs @ 12.31 hrs, Volume= 6.830 af
 Outflow = 49.85 cfs @ 12.54 hrs, Volume= 5.685 af, Atten= 42%, Lag= 13.7 min
 Primary = 49.85 cfs @ 12.54 hrs, Volume= 5.685 af

Routing by Sim-Route method, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs
 Peak Elev= 218.82' @ 12.54 hrs Surf.Area= 0.909 ac Storage= 2.760 af


Plug-Flow detention time= 119.0 min calculated for 5.683 af (83% of inflow)
 Center-of-Mass det. time= 64.5 min (857.7 - 793.3)


Volume	Invert	Avail.Storage	Storage Description
#1	215.00'	3.913 af	Pond (Conic) Listed below (Recalc)

Elevation (feet)	Surf.Area (acres)	Inc.Store (acre-feet)	Cum.Store (acre-feet)	Wet.Area (acres)
215.00	0.570	0.000	0.000	0.570
216.00	0.640	0.605	0.605	0.641
217.00	0.720	0.680	1.284	0.722
218.00	0.820	0.769	2.054	0.824
219.00	0.930	0.874	2.928	0.935
220.00	1.040	0.984	3.913	1.046

Device	Routing	Invert	Outlet Devices
#1	Primary	214.25'	24.0" Round Culvert X 2.00 L= 30.0' RCP, square edge headwall, Ke= 0.500 Inlet / Outlet Invert= 214.25' / 214.00' S= 0.0083 '/' Cc= 0.900 n= 0.013, Flow Area= 3.14 sf
#2	Device 1	215.00'	6.0" Vert. Orifice/Grate C= 0.600
#3	Device 1	217.00'	3.0' long Sharp-Crested Rectangular Weir X 2.00 0 End Contraction(s)
#4	Primary	219.00'	10.0' long x 10.0' breadth Broad-Crested Rectangular Weir Head (feet) 0.20 0.40 0.60 0.80 1.00 1.20 1.40 1.60 Coef. (English) 2.49 2.56 2.70 2.69 2.68 2.69 2.67 2.64

Primary OutFlow Max=49.85 cfs @ 12.54 hrs HW=218.82' TW=0.00' (Dynamic Tailwater)



Pond 5P: Pond**Hydrograph**

Proposed_006_REVISED

Prepared by HP Inc.

HydroCAD® 10.00-25 s/n 11025 © 2019 HydroCAD Software Solutions LLC

MSE 24-hr 3 100-yr Rainfall=6.18"

Printed 1/24/2021

Page 105

Summary for Pond 20B: Pond/Basin

Inflow Area = 9.140 ac, 36.70% Impervious, Inflow Depth > 4.69" for 100-yr event
 Inflow = 66.90 cfs @ 12.16 hrs, Volume= 3.570 af
 Outflow = 23.34 cfs @ 12.35 hrs, Volume= 3.235 af, Atten= 65%, Lag= 11.6 min
 Discarded = 0.16 cfs @ 12.35 hrs, Volume= 0.141 af
 Primary = 23.18 cfs @ 12.35 hrs, Volume= 3.094 af

Routing by Sim-Route method, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs
 Peak Elev= 216.68' @ 12.35 hrs Surf.Area= 0.264 ac Storage= 1.620 af

Plug-Flow detention time= 140.3 min calculated for 3.235 af (91% of inflow)
 Center-of-Mass det. time= 100.5 min (882.4 - 781.9)

Volume	Invert	Avail.Storage	Storage Description
#1	213.50'	1.371 af	Pond (Conic) Listed below (Recalc) -Impervious
#2	212.50'	1.139 af	Infiltration Basin (Conic) Listed below (Recalc)
2.510 af Total Available Storage			

Elevation (feet)	Surf.Area (acres)	Inc.Store (acre-feet)	Cum.Store (acre-feet)	Wet.Area (acres)
213.50	0.190	0.000	0.000	0.190
214.00	0.220	0.102	0.102	0.220
215.00	0.260	0.240	0.342	0.261
216.00	0.320	0.289	0.632	0.322
217.00	0.370	0.345	0.976	0.373
218.00	0.420	0.395	1.371	0.424

Elevation (feet)	Surf.Area (acres)	Inc.Store (acre-feet)	Cum.Store (acre-feet)	Wet.Area (acres)
212.50	0.110	0.000	0.000	0.110
213.00	0.130	0.060	0.060	0.130
214.00	0.160	0.145	0.205	0.161
215.00	0.190	0.175	0.379	0.192
216.00	0.230	0.210	0.589	0.232
217.00	0.280	0.255	0.844	0.283
218.00	0.310	0.295	1.139	0.315


Device	Routing	Invert	Outlet Devices
#1	Discarded	212.50'	0.500 in/hr Exfiltration over Surface area Conductivity to Groundwater Elevation = 200.00' Phase-In= 0.01'
#2	Primary	210.00'	18.0" Round Culvert L= 50.0' RCP, rounded edge headwall, Ke= 0.100 Inlet / Outlet Invert= 210.00' / 204.00' S= 0.1200 '/' Cc= 0.900 n= 0.013, Flow Area= 1.77 sf
#3	Device 2	213.00'	6.0" Vert. Orifice/Grate C= 0.600
#4	Device 2	215.00'	3.0' long Sharp-Crested Rectangular Weir 0 End Contraction(s)

Discarded OutFlow Max=0.16 cfs @ 12.35 hrs HW=216.68' (Free Discharge)
1=Exfiltration (Controls 0.16 cfs)

Primary OutFlow Max=23.18 cfs @ 12.35 hrs HW=216.68' TW=0.00' (Dynamic Tailwater)
2=Culvert (Passes 23.18 cfs of 28.26 cfs potential flow)
3=Orifice/Grate (Orifice Controls 1.75 cfs @ 8.92 fps)
4=Sharp-Crested Rectangular Weir(Weir Controls 21.43 cfs @ 4.24 fps)

Pond 20B: Pond/Basin

Hydrograph



Proposed_006_REVISED

Prepared by HP Inc.

HydroCAD® 10.00-25 s/n 11025 © 2019 HydroCAD Software Solutions LLC

MSE 24-hr 3 100-yr Rainfall=6.18"

Printed 1/24/2021

Page 107

Summary for Pond 20P: Pond

Inflow Area = 5.400 ac, 35.15% Impervious, Inflow Depth > 4.68" for 100-yr event
 Inflow = 26.51 cfs @ 12.31 hrs, Volume= 2.108 af
 Outflow = 23.06 cfs @ 12.41 hrs, Volume= 2.064 af, Atten= 13%, Lag= 5.9 min
 Primary = 23.06 cfs @ 12.41 hrs, Volume= 2.064 af

Routing by Sim-Route method, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs
 Peak Elev= 223.07' @ 12.41 hrs Surf.Area= 0.286 ac Storage= 0.438 af

Plug-Flow detention time= 55.8 min calculated for 2.064 af (98% of inflow)
 Center-of-Mass det. time= 44.2 min (837.5 - 793.3)


Volume	Invert	Avail.Storage	Storage Description
#1	221.00'	0.742 af	Pond (Conic) Listed below (Recalc)

Elevation (feet)	Surf.Area (acres)	Inc.Store (acre-feet)	Cum.Store (acre-feet)	Wet.Area (acres)
221.00	0.140	0.000	0.000	0.140
222.00	0.210	0.174	0.174	0.210
223.00	0.280	0.244	0.418	0.281
224.00	0.370	0.324	0.742	0.371

Device	Routing	Invert	Outlet Devices
#1	Primary	218.00'	15.0" Round Culvert X 2.00 L= 30.0' RCP, square edge headwall, Ke= 0.500 Inlet / Outlet Invert= 218.00' / 217.00' S= 0.0333 '/' Cc= 0.900 n= 0.013, Flow Area= 1.23 sf
#2	Device 1	221.00'	6.0" Vert. Orifice/Grate C= 0.600
#3	Device 1	222.00'	3.0' long Sharp-Crested Rectangular Weir X 2.00 0 End Contraction(s)
#4	Primary	223.30'	10.0' long x 10.0' breadth Broad-Crested Rectangular Weir Head (feet) 0.20 0.40 0.60 0.80 1.00 1.20 1.40 1.60 Coef. (English) 2.49 2.56 2.70 2.69 2.68 2.69 2.67 2.64

Primary OutFlow Max=23.06 cfs @ 12.41 hrs HW=223.07' TW=0.00' (Dynamic Tailwater)

- ↑ 1=Culvert (Passes 23.06 cfs of 24.92 cfs potential flow)
- ↑ 2=Orifice/Grate (Orifice Controls 1.28 cfs @ 6.50 fps)
- ↑ 3=Sharp-Crested Rectangular Weir (Weir Controls 21.78 cfs @ 3.39 fps)
- ↑ 4=Broad-Crested Rectangular Weir (Controls 0.00 cfs)

Pond 20P: Pond**Hydrograph**

Proposed_006_REVISED

Prepared by HP Inc.

HydroCAD® 10.00-25 s/n 11025 © 2019 HydroCAD Software Solutions LLC

MSE 24-hr 3 100-yr Rainfall=6.18"

Printed 1/24/2021

Page 109

Summary for Pond 70B: Pond/Basin

Inflow Area = 16.300 ac, 37.82% Impervious, Inflow Depth > 4.69" for 100-yr event
 Inflow = 101.68 cfs @ 12.21 hrs, Volume= 6.365 af
 Outflow = 39.34 cfs @ 12.45 hrs, Volume= 6.096 af, Atten= 61%, Lag= 14.4 min
 Discarded = 0.24 cfs @ 12.45 hrs, Volume= 0.181 af
 Primary = 39.10 cfs @ 12.45 hrs, Volume= 5.915 af

Routing by Sim-Route method, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs
 Peak Elev= 215.95' @ 12.45 hrs Surf.Area= 0.377 ac Storage= 2.738 af

Plug-Flow detention time= 102.1 min calculated for 6.094 af (96% of inflow)
 Center-of-Mass det. time= 80.4 min (866.1 - 785.7)

Volume	Invert	Avail.Storage	Storage Description
#1	212.00'	2.250 af	Pond (Conic) Listed below (Recalc) -Impervious
#2	211.50'	1.583 af	Infiltration Basin (Conic) Listed below (Recalc)
3.833 af Total Available Storage			

Elevation (feet)	Surf.Area (acres)	Inc.Store (acre-feet)	Cum.Store (acre-feet)	Wet.Area (acres)
212.00	0.280	0.000	0.000	0.280
213.00	0.340	0.310	0.310	0.341
214.00	0.400	0.370	0.679	0.402
215.00	0.460	0.430	1.109	0.463
216.00	0.540	0.499	1.608	0.544
217.00	0.750	0.642	2.250	0.754

Elevation (feet)	Surf.Area (acres)	Inc.Store (acre-feet)	Cum.Store (acre-feet)	Wet.Area (acres)
211.50	0.160	0.000	0.000	0.160
212.00	0.180	0.085	0.085	0.180
213.00	0.220	0.200	0.285	0.221
214.00	0.270	0.245	0.529	0.272
215.00	0.320	0.295	0.824	0.323
216.00	0.380	0.350	1.173	0.383
217.00	0.440	0.410	1.583	0.444


Device	Routing	Invert	Outlet Devices
#1	Discarded	211.50'	0.500 in/hr Exfiltration over Wetted area Conductivity to Groundwater Elevation = 200.00' Phase-In= 0.01'
#2	Primary	209.75'	27.0" Round Culvert L= 40.0' RCP, square edge headwall, Ke= 0.500 Inlet / Outlet Invert= 209.75' / 209.00' S= 0.0187 '/' Cc= 0.900 n= 0.013, Flow Area= 3.98 sf
#3	Device 2	212.00'	12.0" Vert. Orifice/Grate C= 0.600
#4	Device 2	213.75'	3.0' long Sharp-Crested Rectangular Weir 0 End Contraction(s)

Discarded OutFlow Max=0.24 cfs @ 12.45 hrs HW=215.95' (Free Discharge)
1=Exfiltration (Controls 0.24 cfs)

Primary OutFlow Max=39.10 cfs @ 12.45 hrs HW=215.95' TW=0.00' (Dynamic Tailwater)
2=Culvert (Passes 39.10 cfs of 43.14 cfs potential flow)
3=Orifice/Grate (Orifice Controls 7.03 cfs @ 8.95 fps)
4=Sharp-Crested Rectangular Weir(Weir Controls 32.07 cfs @ 4.85 fps)

Pond 70B: Pond/Basin

Hydrograph



Proposed_006_REVISED

Prepared by HP Inc.

HydroCAD® 10.00-25 s/n 11025 © 2019 HydroCAD Software Solutions LLC

MSE 24-hr 3 100-yr Rainfall=6.18"

Printed 1/24/2021

Page 111

Summary for Pond 80B: Pond/Basin

Inflow Area = 14.390 ac, 34.89% Impervious, Inflow Depth > 4.69" for 100-yr event
 Inflow = 86.38 cfs @ 12.22 hrs, Volume= 5.619 af
 Outflow = 11.97 cfs @ 12.80 hrs, Volume= 4.930 af, Atten= 86%, Lag= 34.5 min
 Discarded = 0.36 cfs @ 12.80 hrs, Volume= 0.378 af
 Primary = 11.61 cfs @ 12.80 hrs, Volume= 4.552 af

Routing by Sim-Route method, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs
 Peak Elev= 214.95' @ 12.80 hrs Surf.Area= 0.577 ac Storage= 3.297 af

Plug-Flow detention time= 230.8 min calculated for 4.930 af (88% of inflow)
 Center-of-Mass det. time= 184.0 min (970.7 - 786.7)

Volume	Invert	Avail.Storage	Storage Description
#1	212.00'	2.593 af	Larger Pond (Conic) Listed below (Recalc) -Impervious
#2	212.00'	0.702 af	Smaller Pond (Conic) Listed below (Recalc) -Impervious
#3	211.50'	2.948 af	Infiltration Basin (Conic) Listed below (Recalc)
6.243 af			Total Available Storage

Elevation (feet)	Surf.Area (acres)	Inc.Store (acre-feet)	Cum.Store (acre-feet)	Wet.Area (acres)
212.00	0.360	0.000	0.000	0.360
213.00	0.410	0.385	0.385	0.411
214.00	0.480	0.445	0.829	0.482
215.00	0.540	0.510	1.339	0.543
216.00	0.620	0.580	1.919	0.624
217.00	0.730	0.674	2.593	0.735

Elevation (feet)	Surf.Area (acres)	Inc.Store (acre-feet)	Cum.Store (acre-feet)	Wet.Area (acres)
212.00	0.080	0.000	0.000	0.080
213.00	0.110	0.095	0.095	0.110
213.50	0.120	0.057	0.152	0.121
214.00	0.140	0.065	0.217	0.141
215.00	0.150	0.145	0.362	0.153
216.00	0.170	0.160	0.522	0.174
217.00	0.190	0.180	0.702	0.195

Elevation (feet)	Surf.Area (acres)	Inc.Store (acre-feet)	Cum.Store (acre-feet)	Wet.Area (acres)
211.50	0.370	0.000	0.000	0.370
212.00	0.390	0.190	0.190	0.391
213.00	0.460	0.425	0.614	0.462
214.00	0.530	0.495	1.109	0.533
215.00	0.580	0.555	1.664	0.584
216.00	0.640	0.610	2.274	0.646
217.00	0.710	0.675	2.948	0.717

Proposed_006_REVISED

Prepared by HP Inc.

HydroCAD® 10.00-25 s/n 11025 © 2019 HydroCAD Software Solutions LLC

MSE 24-hr 3 100-yr Rainfall=6.18"

Printed 1/24/2021

Page 112


Device	Routing	Invert	Outlet Devices
#1	Discarded	211.50'	0.500 in/hr Exfiltration over Wetted area Conductivity to Groundwater Elevation = 200.00' Phase-In= 0.01'
#2	Primary	211.00'	18.0" Round Culvert L= 30.0' RCP, square edge headwall, Ke= 0.500 Inlet / Outlet Invert= 211.00' / 209.70' S= 0.0433 '/' Cc= 0.900 n= 0.013, Flow Area= 1.77 sf
#3	Device 2	212.00'	12.0" Vert. Orifice/Grate C= 0.600
#4	Device 2	214.25'	3.0' long Sharp-Crested Rectangular Weir 0 End Contraction(s)

Discarded OutFlow Max=0.36 cfs @ 12.80 hrs HW=214.95' (Free Discharge)
 ↗ 1=Exfiltration (Controls 0.36 cfs)

Primary OutFlow Max=11.61 cfs @ 12.80 hrs HW=214.95' TW=0.00' (Dynamic Tailwater)
 ↗ 2=Culvert (Passes 11.61 cfs of 15.21 cfs potential flow)
 ↗ 3=Orifice/Grate (Orifice Controls 5.91 cfs @ 7.53 fps)
 ↗ 4=Sharp-Crested Rectangular Weir (Weir Controls 5.70 cfs @ 2.73 fps)

Pond 80B: Pond/Basin

Hydrograph




Summary for Link 15L: North Drainage

Inflow Area = 22.460 ac, 30.17% Impervious, Inflow Depth > 3.95" for 100-yr event

Inflow = 60.01 cfs @ 12.48 hrs, Volume= 7.399 af

Primary = 60.01 cfs @ 12.49 hrs, Volume= 7.399 af, Atten= 0%, Lag= 0.6 min

Primary outflow = Inflow, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs

Link 15L: North Drainage**Hydrograph**


Summary for Link 35L: East to White Oak Way

Inflow Area = 18.050 ac, 31.24% Impervious, Inflow Depth > 4.21" for 100-yr event

Inflow = 57.33 cfs @ 12.41 hrs, Volume= 6.338 af

Primary = 57.33 cfs @ 12.42 hrs, Volume= 6.338 af, Atten= 0%, Lag= 0.6 min

Primary outflow = Inflow, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs

Link 35L: East to White Oak Way**Hydrograph**


Summary for Link 45L: East to Hawthorn Hill Drive

Inflow Area = 1.690 ac, 37.04% Impervious, Inflow Depth > 4.68" for 100-yr event

Inflow = 8.11 cfs @ 12.33 hrs, Volume= 0.660 af

Primary = 8.11 cfs @ 12.34 hrs, Volume= 0.660 af, Atten= 0%, Lag= 0.6 min

Primary outflow = Inflow, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs

Link 45L: East to Hawthorn Hill Drive


Summary for Link 55: East to Summit Avenue

Inflow Area = 2.510 ac, 20.72% Impervious, Inflow Depth > 4.36" for 100-yr event

Inflow = 15.41 cfs @ 12.20 hrs, Volume= 0.912 af

Primary = 15.41 cfs @ 12.21 hrs, Volume= 0.912 af, Atten= 0%, Lag= 0.6 min

Primary outflow = Inflow, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs

Link 55: East to Summit Avenue


Summary for Link 95: West Drainage

Inflow Area = 35.190 ac, 32.80% Impervious, Inflow Depth > 4.08" for 100-yr event

Inflow = 59.30 cfs @ 12.49 hrs, Volume= 11.958 af

Primary = 59.30 cfs @ 12.50 hrs, Volume= 11.958 af, Atten= 0%, Lag= 0.6 min

Primary outflow = Inflow, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs

Link 95: West Drainage**Hydrograph**


Summary for Link 99: Total Existing Flow

Inflow Area = 79.900 ac, 31.42% Impervious, Inflow Depth > 4.09" for 100-yr event

Inflow = 187.44 cfs @ 12.44 hrs, Volume= 27.263 af

Primary = 187.44 cfs @ 12.45 hrs, Volume= 27.263 af, Atten= 0%, Lag= 0.6 min

Primary outflow = Inflow, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs

Link 99: Total Existing Flow**Hydrograph**

SLAMM ANALYSIS

SLAMM Analysis Results

FOR: Skyline Subdivision
 LOCATION: Waukesha, Wisconsin

Land Use	Particulate Solids (lbs)						
	Roof	Drive	Street	Sidewalk	Landscape	Undeveloped	Total
Subarea 5	378.2	997.1	1539.0	298.6	1131.5	1.0	4345.4
Subarea 10 - undetained	67.1			107.9			175.0
Subarea 20	100.7	265.9	488.6	89.9	298.6		1243.7
Subarea 25 - undetained	64.9			104.3			169.2
Subarea 30	183.5	487.5	1222.0	197.9	586.6	1.9	2679.3
Subarea 40 - undetained	91.7	236.3	407.8	75.5	217.53		1028.9
Subarea 50 - undetained	40.3			64.7			105.0
Subarea 60 - undetained	33.6			54.0			87.5
Subarea 70	246.1	649.9	1652.0	266.2	794.6		3608.8
Subarea 80	331.2	878.9	1554.0	284.2	1129.4	0.3	4178.0
Subarea 90 - undetained							0.0
Total	1537.3	3515.6	6863.4	1543.3	4158.2	3.2	17620.9

Treatment System	% Removed	
Ibs IN	Ibs OUT	
4345.4	714.0	84%
175.0	15.8	91%
1243.7	304.8	75%
169.2	15.3	91%
2679.3	506.1	81%
1028.9	1028.9	0%
105.0	9.5	91%
87.5	7.9	91%
3608.8	519.9	86%
4178.0	399.0	90%
17620.9	3521.1	80%

NR151.122 TSS Removal Summary

Redevelopment ~ 4.41 acres @ 40% TSS
 New Development ~ 75.49 acres @ 80% TSS
 Total Site ~ 79.90 acres

Weighted Removal Rate: 78%