FORESTRY TRUCK BODIES

RRB | Removable Roof Bodies **BODY SPECIFICATIONS**

Standard Features

- · Rust-resistant, heavy-gauge galvanneal steel construction, including a double-paneled galvanneal steel tailgate and a galvanneal floor with 3-inch structural cross members
- Ladder box with pole pruner shelf and rear lockable door
- Body cleaned with a high-temperature, high-pressure chemical wash to etch the steel before applying a high-grade automotive primer to ensure a durable finish
- Undercoating on underside of floor and toolboxes to enhance durability
- Coal tar epoxy bed liner for a rugged, corrosion-resistant interior finish
- White or black finish paint (Additional colors are optional)
- Fully enclosed lights and wiring harness that are weather- and debris-resistant



Covered by ARBORTECH's



STEP 01



Lift rear sections off

STEP 02



Slide/remove front section

STEP 03



OPTIONAL FEATURES

HELPING YOU CUSTOMIZE THE RIGHT FORESTRY BODY FOR YOU, WE OFFER AN ARRAY OF OPTIONAL FEATURES INCLUDING:

- Ball/pintle hook combo
- Electric trailer brake control
- Full-width rooftop ladder rack
- Rooftop amber strobe light
- 4-head LED flashing light
- Tool boxes

- Plywood / Alturna Mat storage compartment
- Rear underbody boxes
- Back-up alarm
- Rear stirrup step and grab handle
- Wheel chock holders

- Front bumper cone holders
- D.O.T. 5 lb. fire extinguisher with mounting bracket
- D.O.T. roadside triangle kit
- LED light package
- Cab guard

Dimensional Data

Description:	11-ft	14-ft	16-ft		
Cab-to-axle (C.A.) Recommendation:	84"	102" to 120"	126" to 138"		
GVWR Recommendation:	19,500 lbs. min.	25,999 lbs. min.	28,000 lbs. min.		
Dimensions (L x H x W) [Weight* / Useable Capacity**]					
With no cutout for tool box:	11' X 66" X 96" [3,286 lbs. /12.75-yd ³ .]	14′ X 72″ X 96″ [4,477 lbs. / 20.75-yd ³ .]	16′ X 78″ X 96″ [4,150 lbs./27.6-yd ³ .]		
With cutout for tool box:	11' X 66" X 96" [3,092 lbs./11.75-yd ³ .]	14′ X 72″ X 96″ [4,268 lbs. /19.5-yd³.]	16' X 78" X 96" [4,000 lbs. /26.5-yd ³ .]		

Standard Package Includes:			
LED Light Package (Stop/Tail/Turn w-4 LED Strobes) [12 lbs.]	~	V	~
Hoist Assembly with 12V Electric Pump [600 lbs.]	~		
Hoist Assembly with Hydraulic Pump (P.T.O. required***) [600 lbs.]		V	V
"L" Tool Box (48"W x 51"H x 96"D) [900 lbs.]	V	V	V
Hitch Pkg. w/T-60 Pintle (15K# - GTW) [150 lbs.]	~		
Hitch Pkg. w/T-60 Pintle (20K# - GTW) [175 lbs.]		V	~
Wheel Chock Bracket Assembly (Pair) [22 lbs.]	~	V	V
Rubber Wheel Chocks (Pair) [16 lbs.]	~	V	~

Roof Sections:			
(2) 48" X 16" Roof Sections included	✓ †	✓ †	
(1) 36" X 16" Roof Section included	✓ †		
(2) 36" X 16" Roof Sections included		✓ [†]	
(4) 48" X 16" Roof Sections included			✓ †

Optional Equipment:			
"I" Tool Box (24"W x 51"H x 96"D) (in lieu of "L" Box) [675 lbs.]	~	~	~
"L" Tool Box (72"W x 51"H x 96"D) (in lieu of std. "L" Box) [1075 lbs.]		V	~
Fixed Cone Holder (Front Bumper) [8 lbs.]	V	V	V
3-Bow Ladder Rack, with Steps and Roller Assembly [53 lbs.]	V	~	V
Underbody Tool Box (32"W x 22"H x 22"D) aft of rear axle [120 lbs.]		V	V
Hitch Pkg. w/T-60 Pintle (30K# GTW) (in lieu of 10K# Pintle) [190 lbs.]		V	~

yd ³ = Cubic Yards

FOR MORE INFORMATION ON ALL OF ARBORTECH'S PRODUCTS VISIT OUR WEBSITE:

ARBORTECHCHIPBODIES.COM

Due to constant product evaluations and improvements, specifications are subject to change without notice.

ARBORTECH / Scott Fetzer Company

3203 W. Old Lincoln Way Wooster, OH 44691

P: 800.255.5715 F: 330.264.7428 arbortechchipbodies.com



[†] Weight Includes Roof Sections

^{**} Estimated weight capacity equals cubic yards X 500 lbs.

^{***} P.T.O. not included with Chip Body Package