

Chapter 22.05. Building Design Standards

22.05.01. General Provisions	1
22.05.02. Multi-Unit Residential, Mixed-Use, and Non-Residential Design Standards	2
22.05.03. Rowhome Design Standards	11
22.05.04. Triplex, Quadplex, and Cottage Home/ Tiny Home Court Design Standards	13
22.05.05. Multibuilding Development Standards	15

22.05.01. General Provisions

- A. **Purpose.** The purpose of the building design standards is to:
1. Ensure that the physical characteristics of proposed development are compatible with the context of surrounding areas,
 2. Preserve the unique visual character and streetscapes of Waukesha,
 3. Create unique and inspiring places that support the pedestrian experience and promote economic vitality, and
 4. Encourage creativity and innovation while avoiding obtrusive, incongruous structures.
- B. **Applicability.** The standards of this Chapter shall apply as detailed in Table ####.

Table #### Building Design Standards Applicability Overview						
Key:		New development	Major redevelopment	Intermediate redevelopment	Minor redevelopment	Change of use
● = Standards apply to entire development site						
○ = Standards apply to portion of site or building(s) impacted by development activity						
Blank = Standards do not apply						
Standard	Reference					
Multi-Unit Residential, Mixed-Use, and Non-Residential Design Standards [1]	####	●	●	○		
Rowhome Design Standards	####	●	●			
Triplex, Quadplex, and Cottage Home/ Tiny Home Court Design Standards	####	●	●			
Multibuilding Development Standards	####	●	●	○		

Table ##### Building Design Standards Applicability Overview

Key:		New development	Major redevelopment	Intermediate redevelopment	Minor redevelopment	Change of use
● = Standards apply to entire development site						
○ = Standards apply to portion of site or building(s) impacted by development activity						
Blank = Standards do not apply						
Standard	Reference					
Notes						
[1] These standards shall not apply to single-family, detached residential uses in districts where multi-family development is permitted.						

22.05.02. Multi-Unit Residential, Mixed-Use, and Non-Residential Design Standards

- A. **Applicability.** The standards of this Section shall apply to all multi-unit residential dwellings, mixed-uses, and uses in the public and institutional, commercial, and industrial and automotive land use categories, including buildings with a mix of uses, as detailed in Table #####.
- B. **Exterior Building Cladding Materials.**
1. **Establishment of Exterior Building Cladding Material Tiers.**
 - a. **Tier I Materials.** Tier I materials are characterized by their high quality and long-lasting durability. These materials may commonly reflect traditional building methods and serve as a unifying element throughout buildings in the City. Tier I materials shall include:
 - i. Solid brick,
 - ii. Natural and manufactured stone,
 - iii. Engineered wood, natural wood, and wood composite siding,
 - iv. Brick/stone veneer with a minimum thickness of one and three quarters inches, and
 - v. Fiber cement siding.
 - b. **Tier II Materials.** Tier II materials are characterized by their medium-to-high quality with lasting durability, but more frequent maintenance required than Tier I materials. Tier II materials are generally lower cost than Tier I materials. These materials provide variety and design expressions on the building and have scale, texture and pattern creating visual interest. Tier II materials shall include:
 - i. Non-corrugated metal or metal composite panels,
 - ii. Precast concrete,
 - iii. Metal composite panels, and
 - iv. Architectural concrete masonry units.

- c. **Tier III Materials.** Tier III materials are medium quality materials and/or monolithic in visual appearance. These materials may require more frequent maintenance than Tier I or Tier II materials but provide up-front cost savings. These materials contribute to variety and design expression. Tier III materials shall include:

- i. Natural stucco,
- ii. Corrugated metal, and
- iii. Synthetic stucco
 - a) Allowed as an accent material only, and
 - b) Shall terminate no lower than three feet above finished grade.

- d. **Prohibited Materials.** The following materials are prohibited on all façades.

- i. Vinyl siding, and.
- ii. Unfinished concrete block.

2. **Exterior Building Cladding Material Tier Requirements.** Table #### below details the requirements for exterior building cladding materials on front and street side yard facing building façades, by district. Glazing and building entrances shall not be included in the material calculations.

Table #### Exterior Building Cladding Material Tier Requirements			
Zoning District	Tier I	Tier II	Tier III
RN-3, RN-4	Minimum 50%	Maximum 50%	Maximum 25%
MU, DC	Minimum 75%	Maximum 25%	Prohibited
GC, CC, I	Minimum 25%	Maximum 75%	Maximum 50%
LM, GM, MM, OM	Minimum 0%	Maximum 75%	Maximum 25%

DIAGRAM TO BE INSERTED HERE LATER IN PROCESS

3. **Exterior Building Cladding Material Colors.** The use of high-intensity, metallic, fluorescent, day glow, or neon colors is prohibited.

C. Glazing.

1. **Ground Floor Requirements.** The ground floor of front and street side yard facing façades shall include a minimum percentage of glazing, as detailed in Table ####.

Table #### Minimum Required Ground Floor Glazing		
Zoning District	Front Yard Facing Façade	Street Side Yard Facing Façade
MU, DC	60%	40%
RN-3, RN-4, GC, CC, I	40%	20%
LM, GM, MM, OM	20%	n/a

2. **Administrative Adjustment.** An administrative adjustment may allow a reduction in the ground floor glazing requirements if:
 - a. The building contains industrial uses or full glazing is not feasible.
 - b. The adjustment applies only to façades where industrial operations occur or where glazing is not feasible.
 - c. The applicant provides alternative design treatments to enhance the façade, such as pilasters, changes in depth, decorative brick patterns, murals, or other architectural features.
3. **Materials.** Required glazing shall not be mirrored or tinted in a manner that renders the glass opaque.
4. **Maintenance.** Required glazing shall not be obstructed by interior walls, window displays, or other permanent installations at all times, unless otherwise permitted by this Code.

D. Building Entryway Design.

1. Building entryway design standards shall apply to each building entrance on a front or street side yard facing façade, including entrances at a chamfered corner, and shall include one or more of the features included in Table ####.

DIAGRAM TO BE INSERTED HERE LATER IN PROCESS


Table ### Building Entryway Design Standards	
Standards	Diagram
1. Canopy / Roof Overhang	
a. Shall be located above all ground floor windows and doors. b. Shall project a minimum of three and a maximum of six feet from the façade of the building.	EXAMPLE DIAGRAM ONLY – REFERENCE MAY NOT MATCH TEXT 
2. Portico	
a. Shall project a minimum of eight feet from the façade of the building.	EXAMPLE DIAGRAM ONLY – REFERENCE MAY NOT MATCH TEXT

Table ### Building Entryway Design Standards


Standards	Diagram
b. Shall extend a minimum of five feet from either side of the building entry. c. Portico columns shall be wrapped with one of the required exterior building cladding materials utilized on the building.	
3. Plaza	
a. Shall be located within a recessed portion of the building that is enclosed on two or three sides.	EXAMPLE DIAGRAM ONLY - REFERENCE MAY NOT MATCH TEXT 
b. Shall have a minimum area and dimensions proportional to the height of the building to ensure adequate light, air, and usable space. - Minimum depth - at least 1/3 of the building height. - Minimum width - at least 1/2 of the building height.	
c. Shall be improved as a community space in accordance with Section ####.	
a. Shall run the full length of the building façade.	EXAMPLE DIAGRAM ONLY - REFERENCE MAY NOT MATCH TEXT
b. Shall project over the full width of the on-site pedestrian walkway.	
c. Shall have a minimum depth of six feet.	
d. Pedestrian arcade columns shall be wrapped with one of the required exterior building	

Table ### Building Entryway Design Standards



Standards	Diagram
cladding materials utilized on the building.	
5. Landscape Forecourt	
Shall meet standards from 22.07.05 of this Code.	EXAMPLE DIAGRAM ONLY – REFERENCE MAY NOT MATCH TEXT 
6. Courtyard	
a. The portion of the building façade with the entry, with a minimum width of 10 feet, shall be recessed from the primary façade a minimum of eight feet.	EXAMPLE DIAGRAM ONLY – REFERENCE MAY NOT MATCH TEXT
b. A fence or wall, comprised of the allowed materials detailed in Section ### , or a landscape hedge shall extend from the primary façade of the building to create a sense of enclosure in the courtyard.	

Table ### Building Entryway Design Standards



Standards	Diagram
c. The fence, wall, or landscape hedge shall have a minimum height of three feet and a maximum height of four feet if more than 20 percent opaque. d. The fence, wall, or landscape hedge shall have a minimum height of three feet and a maximum height of six feet if 20 percent or less opaque.	
7. Recessed Entrance	
a. Shall apply to buildings with zero-foot front yard setback only. b. The recessed area shall be proportionally wider than it is deep and shall have a minimum depth of four feet. c. The recessed area shall be decorative through the incorporation of design elements including but not limited to a mosaic tile floor, angled storefront windows, use of accent building materials, or other as approved by the Community Development Director or their Designee.	EXAMPLE DIAGRAM ONLY – REFERENCE MAY NOT MATCH TEXT 
8. Masonry Surround	
a. Shall apply to buildings with zero-foot front yard setback only. b. Masonry shall be permanently applied to the sides and top of building entry.	

Table ### Building Entryway Design Standards

Standards	Diagram
c. Masonry shall have a minimum width of one foot.	EXAMPLE DIAGRAM ONLY – REFERENCE MAY NOT MATCH TEXT 

2. **Exceptions.** The requirements of **Section ####** shall not apply to a development that meets all of the following criteria:
 - a. The building entrance complies with circulation, safety, and accessibility standards as determined by the Community Development Director or their designee, and
 - b. Site constraints, building layout, or topography preclude strict compliance with the entryway design standards.
3. **Façade Articulation.**
 - a. **Applicability.** Façade articulation standards shall apply to all buildings located within the following zoning districts: RN-2, RN-3, RN-4, MU, DC, GC, CC, and I.
 - b. **Single-Tenant and Common Entrance Buildings.**
 - i. **Bay / Section Façade Articulation Requirements.** The front and street side yard facing façade of a single-tenant or common entrance building shall be divided into architecturally distinct sections or bays with each section taller than it is wide. In no instance shall the width of a bay / section exceed the height of the façade.
 - ii. **Dividing Elements.**
 - a) Sections or bays shall be visually established by dividing elements such as columns, ribs, pilasters or piers, changes in plane, or an equivalent element, as approved by the Community Development Director or their designee, that visually subdivides the wall with a roof or cap feature that provides a rational terminus and integrates with the overall design of the façade.

- b) Required dividing elements shall extend at least the full height of the ground floor of the building.
- c) The width of required dividing elements shall be a minimum of 12 inches.
- d) The required projection of dividing elements shall be based on the width of the dividing element in accordance with **Table ####**:

Table ####: Minimum Projection of Façade Dividing Elements	
<i>Width of Façade Dividing Element</i>	<i>Minimum Projection of Façade Dividing Element</i>
12 - 23.99 inches	4 inches
24 - 35.99 inches	8 inches
36 or more inches	12 inches

DIAGRAM TO BE INSERTED HERE LATER IN PROCESS

c. Multi-Tenant Buildings.

- i. On all façades of a multi-tenant building, ground floor tenant spaces shall be visually distinguished from one another through the use of two of the following:
 - a) Dividing elements that meet the standards of **####** above,
 - b) Different building entryway designs per **Section ####**, or
 - c) Variated exterior building cladding materials including:
 - (i) Solid brick,
 - (ii) Brick/stone veneer with a minimum thickness of one and three quarters inches,
 - (iii) Architectural concrete masonry units,
 - (iv) Fiber cement, engineered wood, natural wood, and wood composite siding, or
 - (v) Non-corrugated metal or metal composite panels.
- ii. The design element applied to a tenant space shall not be repeated on immediately adjacent tenant spaces on the same façade.
- iii. On the front and street side yard facing façades of a multi-tenant building, upper floors shall meet the façade articulation requirements of **####** above.

DIAGRAM TO BE INSERTED HERE LATER IN PROCESS

d. All Building facades.

- i. At least one horizontal or vertical change in wall plane is required with a minimum depth of two feet for every 60 linear feet of wall length. No single wall plane may extend more than 80 percent of the length of the façade. This standard shall apply to all elevations.
 - ii. Any building wall greater than 250 linear feet shall provide a recess in the wall plane with a minimum depth of five feet.
4. **Façade Requirements.** If visible from a parking area, adjacent lot, or public right-of-way, expanses of blank facades shall not exceed 20 feet in length unless at least one of the following is provided:
 - i. Glazing,
 - ii. Public art,
 - iii. Social gathering space in accordance with Section ####,
 - iv. Vertical trellises or planters with landscaping integrated with the building wall,
 - v. Canopies with a minimum depth of three feet,
 - vi. At least one horizontal or vertical change in wall plane with a minimum depth of two feet for every 60 linear feet of wall length, or
 - vii. Decorative masonry such as soldier course, rowlock quoins, flat or segmental arches, or protruding brickwork. Decorative masonry may be done with solid brick or brick/stone veneer with a minimum thickness of one and three quarters inches.
5. **Roofline Articulation.** The following standards shall apply to applicable buildings in RN-2, RN-3, RN-4, MU, DC, GC, CC, and I Districts.
 - a. Roofline articulation shall be provided every 60 feet of roof length. An Administrative Adjustment (Section ####) may be approved for alternate distribution of roofline change features.
 - b. Requirements for roofline articulation may be met by:
 - i. Distinctions in roof pitch, such as through the use gables, dormers, shed dormers, flat roofs, or towers, that are visually apparent as seen from the ground,
 - ii. Variation in roof materials, such as on roof accent elements, or
 - iii. Variation of at least two feet in building section height.

DIAGRAM TO BE INSERTED HERE LATER IN PROCESS

c. **Parapet Walls.**

- i. All flat roofs shall include parapet walls.

- ii. Parapet walls shall be designed in a manner that prevents views of the rear of the parapet wall or to any portion of the roof from any adjacent property or right-of-way

22.05.03. Rowhome Design Standards

A. **Applicability.** The standards of this Section shall apply to dwelling-rowhome units and clusters.

B. **Exterior Building Cladding Materials.**

1. **Establishment of Exterior Building Cladding Material Tiers.**

- a. **Tier I Materials.** Tier I materials are characterized by their high quality and long-lasting durability. These materials may commonly reflect traditional building methods and serve as a unifying element throughout buildings in the City. Tier I materials shall include:
 - i. Solid brick,
 - ii. Natural and manufactured stone,
 - iii. Brick/stone veneer with a minimum thickness of one and three quarters inches,
 - iv. Engineered wood, natural wood, and wood composite siding, and
 - v. Fiber cement siding.
- b. **Tier II Materials.** Tier II materials are characterized by their medium-to-high quality with lasting durability, but more frequent maintenance required than Tier I materials. Tier II materials are generally lower cost than Tier I materials. These materials provide variety and design expressions on the building and have scale, texture and pattern creating visual interest. Tier II materials shall include:
 - i. Natural stucco,
 - ii. Vinyl siding, and
 - iii. Synthetic stucco
 - a) Allowed as an accent material only, and
 - b) Shall terminate no lower than three feet above finished grade.
- c. **Tier III Materials.** Tier III materials are medium quality materials and/or monolithic in visual appearance. These materials may require more frequent maintenance than Tier I or Tier II materials but provide up-front cost savings. These materials contribute to variety and design expression. Tier III materials shall include:
 - i. Architectural concrete masonry units,
 - ii. Non-corrugated metal or metal composite panels, and
 - iii. Precast concrete.

d. **Prohibited Materials.** The following materials are prohibited on all façades.

- i. Unfinished concrete block and
- ii. Corrugated metal.

2. **Exterior Building Cladding Material Tier Requirements.** Table ##### below details the requirements for exterior building cladding materials on front and street side yard facing building façades, by district. Glazing and building entrances shall not be included in the material calculations.

Table ##### Exterior Building Cladding Material Tier Requirements			
Zoning District	Tier I	Tier I	Tier III
R-2	Minimum 50%	Maximum 50%	Maximum 10%
R-3, R-4	Minimum 50%	Maximum 50%	Maximum 25%
MU	Minimum 75%	Maximum 25%	Maximum 10%

DIAGRAM TO BE INSERTED HERE LATER IN PROCESS

3. **Exterior Building Cladding Material Colors.** The use of high-intensity, metallic, fluorescent, day glow, or neon colors is prohibited.

C. **Orientation.** Rowhome units shall be oriented with their primary entrances either:

- 1. Toward the designated front lot line (the primary entrance of end unit rowhome on corner lots may be oriented toward the designated front or street side lot line), or
- 2. Toward an internal courtyard space (the primary entrance of end unit rowhomes closest to the designated front lot line shall be oriented toward the designated front lot line).

DIAGRAM TO BE INSERTED HERE LATER IN PROCESS

D. **Rowhome Clusters.**

- 1. A maximum of eight rowhome units shall be allowed in a rowhome cluster.
- 2. Individual rowhome units in a cluster shall be articulated via:
 - a. Dividing elements that meet the standards of Section #####,
 - b. Different unit entryway designs including a minimum of one of the following options:
 - i. Porches,
 - ii. Canopies,
 - iii. Covered stoops, or
 - iv. Recessed vestibules,

- c. Variation in Tier I or Tier II exterior building cladding materials,
 - d. Variation in exterior building cladding material colors,
 - e. Distinctions in roof pitch, such as through the use gables, dormers, shed dormers, flat roofs, or towers, that are visually apparent as seen from the ground,
 - f. Variation in roof materials, such as on roof accent elements, or
 - g. Variation of at least two feet in unit height.
3. The siting of rowhome units in a cluster shall be staggered in order to define street edges, entry points, and public gathering spaces.

DIAGRAM TO BE INSERTED HERE LATER IN PROCESS

- E. **Attached Front Yard Facing Façade Garages.** An attached garage shall be allowed on the front yard facing façade of a rowhome unit if one of the following standards is met:
- 1. The second story of the unit extends above the attached garage. In this case, up to a two-car garage is allowed.
 - 2. The garage shall be recessed a minimum of five feet from the front elevation or front porch of the unit. In this configuration, a two-car garage shall be permitted, provided each car shall have a separate entrance.
 - 3. The garage shall be aligned with the front elevation or front porch of the unit. In this configuration, a single-car garage or two tandem parking spaces shall be permitted.

22.05.04. Triplex, Quadplex, and Cottage Home/ Tiny Home Court Design Standards

- A. **Applicability.** The standards in this Section shall apply to triplex, and quadplex dwelling units, as well as cottage homes and tiny home courts.
- B. **Establishment of Exterior Building Cladding Material Tiers.**
- 1. **Tier I Materials.** Tier I materials are characterized by their high quality and long-lasting durability. These materials may commonly reflect traditional building methods and serve as a unifying element throughout buildings in the City. Tier I materials shall include:
 - a. Brick,
 - b. Natural and manufactured stone, and
 - c. Fiber cement, LP Smart Side, Everlast composite, natural wood, and wood composite siding.
 - 2. **Tier II Materials.** Tier II materials are characterized by their medium-to-high quality with lasting durability, but more frequent maintenance required than Tier I materials. Tier II

materials are generally lower cost than Tier I. These materials provide variety and design expressions on the building and have scale, texture and pattern creating visual interest. Tier II materials shall include:

- a. Natural and synthetic stucco,
- b. Vinyl siding,
- c. Architectural concrete masonry units, and
- d. Architectural metal panels.

3. **Prohibited Materials.** The following materials are prohibited on all façades of the building:

- a. Corrugated metal siding,
- b. Unfinished concrete block, and
- c. Precast concrete, and

C. **Exterior Building Cladding Materials.** Table ##### below details the requirements for exterior building cladding materials. Glazing and doors shall not be included in the material calculations.

Table ##### Required Exterior Building Cladding Materials		
Building Façade Elevation	Tier I	Tier II
Front and Street Side [1]	Minimum 50%	Maximum 50%
Interior Side and Rear	N/A	N/A
Note		
[1] Street-side exterior building cladding material requirements shall also apply to façades facing private streets.		

D. **Orientation.** A minimum of one and maximum of two dwelling entrances shall be oriented toward the front lot line.

E. **Roof Type.** A pitched roof shall be required.

F. **Garages.**

1. **Attached Front Yard-Facing Garages.** Attached garages on the front elevation of triplexes, quadplexes, and tiny home/cottage court developments shall be prohibited.
2. **Street-Facing Garages.** Garages facing a public street shall include at least one of the following architectural features visible from the street:
 - a. Raised or recessed panels on the garage door,
 - b. Trim or molding around the garage door, or
 - c. Material or color accents that match or complement the primary building façade.

22.05.05. Multibuilding Development Standards

- A. **Applicability.** Multibuilding development standards shall apply to developments with multiple principal buildings and internal access drives (Section #####).
- B. **Building Separation.** Buildings within a multibuilding development shall maintain a minimum separation of 15 feet, measured between the nearest points of building walls.
- C. **Relation to Other Requirements.** Design standards established for all buildings in Section ##### of this Code include varying standards based on which yard the façade faces. In multibuilding developments, rather than applying the requirements based on which yard the façade faces, the application of the requirements shall be as detailed below.
 1. **Front / Street Side.** Requirements for front and street-side yard-facing façades shall apply to any façade that:
 - a. Perimeter public right-of-way,
 - b. Primary internal street, or
 - c. Park or other community and open space/social gathering space.
 2. **Interior Side.** Requirements applicable to side yard facing facades shall be applied to a façade without a building entrance if it faces an off-street parking area.
 3. **Rear.** Requirements applicable to rear yard facing facades shall be applicable to a façade without a building entrance if it faces:
 - a. The rear or side of adjacent buildings, or
 - b. Loading/service areas.

