





Plan View
Scale - 1" = 20ft

Schedule											
Symbol	Label	Image	QTY	Catalog Number	Description	Lamp	Number Lamps	Lumens per Lamp	LLF	Wattage	Polar Plot
	OA		1	ESX1 LED P4 40K R3	ESX LED Area Luminaire Size 1 P4 Lumen Package 4000K CCT Type R3 Distribution		1	25034	1	189.98	 Max: 13735cd
	OB		2	ESX1 LED P4 40K R3 HS	ESX Area Luminaire Size 1 P4 Lumen Package 4000K CCT Type R3 Distribution with House-side shield		1	20467	1	189.9758	 Max: 13653cd
	OW1		1	WPX0 LED ALO (High) SWW2 MVOL PE DDBXD	WPX0 LED, 1650 Lumen setting, 4000K Setting, 120-277V		1	1645	1	12.4511	 Max: 752cd

Luminaire Locations										
		Location					Aim			
No.	Label	X	Y	Z	MH	Orientation	Tilt	X	Y	Z
1	OA	695550.30	167666.40	25.00	25.00	249.15	0.00	695548.90	167665.90	0.00
1	OB	695474.40	167693.30	25.00	25.00	90.90	0.00	695475.90	167693.30	0.00
2	OB	695533.10	167747.40	25.00	25.00	164.70	0.00	695533.50	167746.00	0.00
1	OW1	695597.60	167699.60	8.00	8.00	75.00	0.00	695597.60	167699.60	0.00

Statistics							
Description	Symbol	Avg	Max	Min	Max/Min	Avg/Min	
Back Asphalt At Grade	+	1.82 fc	8.79 fc	0.13 fc	67.6:1	14.0:1	
Calc Zone #4	+	3.99 fc	7.35 fc	0.21 fc	35.0:1	19.0:1	
PROP LINE	+	0.86 fc	4.53 fc	0.02 fc	226.5:1	43.0:1	